

UPL by SER as on 04.07.2025

Sr.	Rly	Req.No./Date	PL Grp	Item Description
1	CR	32508 19-09-18	56158014	SEALED MAINTENANCE FREE VRLA BATTERY SET OF 60 CELLS (STACKABLE), IN COMBINATION OF 55+5 CELLS FOR SMPS BASED INTEGRATED POWER SUPPLY SYSTEM, EACH CELL OF 2 VOLT/200 AH CAPACITY, FULLY CHARGED, CONFORMING TO RDSO SPECIFICATION NO. IRS : S:93/96(A) WITH LATEST AMENDMENTS, COMPLETE WITH CONNECTING LINKS AND SUITABLY NUMBERED IN STACKABLE RACKS ALONG WITH USER MANUALS. VENDOR SHALL BE BORN ON RDSO'S APPROVAL LIST. INSPECTION BY RDSO.
2	CR	79511 10-02-20	75908451	Industrial Safety Helmet - ISI marked safety Helmet to IS 2925-1984 (modified in 2010) with detachable Miner's light with flexible rotation provided with strap and rechargeable heavy duty battery detail requirement as per annexure specification for Industrial Safety Helmet with miner's light.
3	CR	90567 12-08-20	56500324	TRACK FEED BATTERY CHARGER INPUT 110V AC SINGLE PHASE,OUTPUT 10 A FOR CHARGING 1 OR 2 OR 3 OR 4 LEAD ACID BATTERIES OF 80AH CAPACITY CONFIRMING TO RDSO SPECIFICATION NO.IRS:S:89/2013 VERSION 1.0 WITH LATEST AMENDMENTS.
4	CR	135081 23-06-22	76010582	Manual Metal Arc Welding Electrode size 5x450mm. R.D.S.O. Approved Class A3 as per IRS M28/2020, Code: EB5326H2X, IS:814/2004, AWS : A 5.1 : E7016
5	ER	13 19-08-16	75400250	DECORATIVE THERMOSETTING SYNTHETIC RESIN BONDED LAMINATED SHEETS SIZE-2440 mm. X 1220 mm.X 3 mm. THICKNESS AS PER RDSO's SPEC. No. C-K514 (REV.0 OF DEC, 2005) WITH CORRIGENDUM SLIP NO.1 OF JAN 2006, WITH ALL 6 AMENDMENTS (LAST AMENDMENT SLIP NO.6 ISSUED ON SEPT. 2015) AND WITH CORRIGENDUM NO.1 OF JUNE 2015 OF AMENDMENT SLIP NO.5 , COLOUR SHADE CODE NO. AC-SP-02.
6	ER	181 25-11-16	76050038	Manual Metal Arc Welding Electrodes class A3 for Stainless Steel Wagon (Size- 4 x 450 mm)
7	ER	179 25-11-16	76050040	Manual Metal Arc Welding Electrodes ClassM2 for Stainless Steel Wagon (Size- 4 x 350 mm)
8	ER	5372 12-05-17	75050018	Cover for 16 Cylinder Crank Case as per DLCF's Drg No - DLCF/TNP/01
9	ER	10903 09-10-17	56500294	Insulation Joint set for Gauge Tie Plate as per RDSO specification Nylon IRS:S 40/84 with Amdt-1 (amdt upto date if any). Set consisting of : j) Space plate to Drg No. T-10372 Adv. Alt 2(Latest) = 01 No. k) Bush to Drg No. T-10368(Latest) = 03 Nos. l) Washer to Drg No. T-10371(Latest) = 06 Nos.
10	ER	10907 09-10-17	56500300	NYlon Insulation set for Stretcher Bar as per RDSO specification No. IRS:S 40/84 with Amdt-1(amdt upto date if any). Set consisting of : a) Space Plate to Drg.No. T-10367(Latest)=01 No. b) Bush to Drg.No. T-10368(Latest)= 02 Nos. c) Washer to Drg. No. T-10371 (Latest) =04 Nos
11	ER	11526 17-10-17	76217024	Copper Nozzle for oxycutting with LPG size-3/64" type B , make/brand ARCON/ L & T / ESAB /ADOR welding IS 7653/1975
12	ER	10890 09-10-17	56900016	HIGH INTENCITY GRADE RETRO REFLECTIVE FILM RED.DETAILS SPECIFICATION AS FOLLOWS:(i) thickness - 0.25 mm to 0.3 mm,(ii) type of adhesive - pressure sensitive(PS type) (iii) minimum reflectivity - 170 for yellow colour, 45 for red colour for black not required (iv) weather resistance - should be able to withstand following climatic test as per IS 9000 (ee) Dry heat test at 70 degree centigrade plus minus 2 degree centigrade for 2 Hrs (ff) cold test at 10 degree centigrade plus minus 3 degree centigrade for 16 Hrs (gg) Damp heat cycle test- 3 cycles (12 plus 12 Hrs) of 2 Hrs each (hh) Dust test for 1 Hr (ii) Driving rain test - for 2 Hrs, After these tests there should not be more than 5% deterioration in the reflectivity , (v) Grade- high intensity with micro sized glass beads encapsulated uniformly all over (vi) Guarantee Life - 5 Years minimum (vii) ISO 9002 certification- Firm should be certified for consistent quality (viii) Size of yellow/black piece = 305 mm x 290 mm for Red from any standard available (size) length mfd by firms , ref : RDSO L/No - STS/MM/LBG Dated 09/02/99, para - 4.1 annexure 1 & 4.
13	ER	130797 28-04-22	75610085	Supply & Apply of Two part Epoxy resin coating set, fire safe solvent free for flooring in Indian railways Coach Toilets, RCF Specification MDTs 44289 Rev-00, consisting of i) Two Part primer -250 Grams / set, ii) Two part Epoxy Main coat-2500 Grams /Set, iii)Two part PU sealer-225 Grams /Set, iv) Two pat IR sealer -160 Grams/set, v) Chips /flakes-10 Grams /set
14	ER	130766 28-04-22	76210200	Heavy duty Air Plasma Cutting Nozzle & Electrode consisting of 10 Items (One set consisting of 5 Nos. Nozzel & 5 Nos. electrode). suitable for Air Plasma cutting machine Model No.-INV-100 Part No. TPA (Size-1.5mm dia) Make-Technology Promoters india Pvt. Ltd. or similar as per Attached Annexure.
15	ER	170020 23-09-23	76011380	Electrodes I R S class D Heavy coated Size: 3.15 x 450mm conforming to IRS-M-28-2017
16	ER	185369 03-05-24	76110059	Solid MIG/MAG Welding Filler Wire, Class VII, Spec No. IRS M 46/13 with amendment No. - 1. Grade ER 309 AS as per AWS : A 5.9, Wire Size 1.2 mm dia, Net Weight per spool not more than 12.50 Kgs.
17	ER	185367 03-05-24	76114030	Copper Coated Solid MIG/MAG wire, Class IV to IRS M : 46-2013, Ver. 1 , Spec No. : AWS Code :-A5.28-10, Grade - 80S-G Diameter of Wire = 1.2 mm. Weight of Wire Spool = Approx. 12.5 Kg.
18	ER	185368 03-05-24	76116220	Solid MIG/MAG Welding Filler Wire, Class VI Size 1.2 mm (Spec No. IRS M-46/13 or latest with Amendment No.1 Grade ER 308 L as per AWS : A5.9-10) in Spool of 12.5 Kgs/Roll.
19	ER	182697 29-03-24	75209548	Leather Gauntlets (hand gloves) 350 mm for Fitters to IS: 2573/2023 (Rev-03) or latest Type-II.
20	ER	191743 16-07-24	76213018	DUST PROOF FACTORY GOGGLES FOR GRINDING, CLW Specn No. MSO/33/Specn/VI-01,Rev.0.01. Dated.20-4-11 HSN CODE-9004 (SHELF LIFE 36 MONTHS)
21	ER	212418 28-03-25	56118314	48 Fiber Armoured OFC cable conforming to RDSO Specification No. RDSO/SPN/TC/110/2020 Revision-0 or latest if any up to date of tender opening.
22	ER	214830 30-04-25	56040386	CPU2 card for SSDAC(Model-G36R) as per RDSO spec. No. RDSO/SPN/177/2012 (Ver. 3.0) or latest. Make: G.G TRONICS.
23	ER	214829 30-04-25	56040222	Supply of Central Processing Unit card CPU1 for single section digital type axel counter as per RDSO specification RDSO/SPN/177/2012 (Ver.3) or latest version & amendment upto date if any. Make: G.G. Tronics India Pvt. Ltd.
24	ER	214828 30-04-25	56040090	Supply of Phase Detector Card PD2 25 KHZ for single section digital axel counter as per RDSO specification RDSO/SPN/177/2012 (Ver.3) or latest version & amendment upto date if any. Make: G.G.Tronics India Pvt. Ltd.

25	ER	214825 30-04-25	56040260	Supply of Phase Detector card PD1 for single section digital type axel counter as per RDSO specification RDSO/SPN/177/2012 (Ver.3) or latest version & amendment upto date if any. Make: G.G.Tronics India Pvt. Ltd.
26	ER	214848 30-04-25	56040398	Supply of Relay Drive Card RD2 for single section digital type axel counter as per RDSO specification RDSO/SPN/177/2012 (Ver.3) or latest version & amendment upto date if any. Make: G.G.Tronics India Pvt. Ltd.
27	ER	214823 30-04-25	56040404	Supply of Relay Drive Card RD1 card for single section digital type axel counter as per RDSO specification RDSO/SPN/177/2012 (Ver.3) or latest version & amendment upto date if any. Make: G.G.Tronics India Pvt. Ltd.
28	ER	214819 30-04-25	56040416	Supply of Communication Card COM1 for single section digital type axel counter as per RDSO specification RDSO/SPN/177/2012 (Ver.3) or latest version & amendment upto date if any. Make: G.G.Tronics India Pvt. Ltd.
29	ER	214821 30-04-25	56040428	Supply of Communication Card COM2 for single section digital type axel counter as per RDSO specification RDSO/SPN/177/2012 (Ver.3) or latest version & amendment upto date if any. Make: G.G.Tronics India Pvt. Ltd.
30	ER	214837 30-04-25	56040430	Supply of DC-DC Converter card for single section digital type axel counter as per RDSO specification RDSO/SPN/177/2012 (Ver.3) or latest version & amendment upto date if any. Make: G.G.Tronics India Pvt. Ltd.
31	ER	214831 30-04-25	56040441	Supply of Tx Transmitter coil assembly 21 KHZ/25 KHZ for single section digital axel counter as per RDSO spec. No. RDSO/SPN/177/2012(Ver. 3) latest version & amendment upto date if any. Make: G.G.Tronics India Pvt. Ltd.
32	ER	207872 30-01-25	54420088	SPARE ROTARY SWITCH (4 POLE/2WAY) FOR DOMINO TYPE CONTROL CUM INDICATION PANEL OF LC GATES OR SIMILAR. ROTARY SWITCH (4 POLE/2 WAY) IS A PART OF LC GATE PANEL . SPECIFICATION NO OF LC GATE PANEL IRS : S- 36/87. MAKE-JAI BALAJI or Deltron or RDSO approved brand.
33	ER	212527 01-04-25	56900041	Desktop Computer for Datalogger with following specification USB key board and mouse, (i) Processor description-Intel core i3-12100 windows 11 professional, 12 th Gen processor, (ii) Ram-8 GB, (iii)HDD-512 GB, (iv) Screen-21.5 HD LED Monitor, (v)Port-2USB ports, (vi)Key board and mouse (vii)Graphics-Integrated, (viii)OS-Windows 11 professional, (ix)Warranty-03 years on site. Make-HP(Intel Core i3 13100) /DELL/LENEVO/ACAR/HCL or similar. Inspection-Consignee..
34	ER	214834 30-04-25	56040120	Supply of Rx Receiver coil Assembly 21KHZ/25KHZ for Single Section Digital Axle Counter as per RDSO spec. No. RDSO/SPN/177/2012 (Ver.3) or latest version & amendment upto date if any. Make: G.G.Tronics India Pvt. Ltd.
35	ER	212532 01-04-25	56110169	Supply of 6 Core Armoured OFC Cable (Single Mode) as per latest TEC Specification TEC/GR/TX/OFC20/01/MAR -2011 or latest if any up to the date of tender opening.
36	ER	212534 01-04-25	54220117	Gear Box Assembly set suitable for ELB (RDSO Spn. No. RDSO/SPN/208/2012 version 2.0 or latest) with clutch stage combination Helical & worm wheel gear drive with hard crank insert internal locking feature, oil filled & sealed type unit with connecting link on output shaft suitable for G.I. Boom barrier. DRG. No. S&T/MFT/6000/ADV.1. Make: AEW or GLOBAL or URBAN or similar. Inspection by RDSO.
37	ER	212417 28-03-25	56110170	Single core PVC insulated unsheathed copper conductor cables in voltage grade 1100 V as per IS 5831, Conforming to IRS:S 76-89, nominal cross sectional area of conductor is 2.5 sq mm, Multistrand (36/0.3), thickness of insulation - 0.8 mm, overall dia meter (appx) 3.8 mm. The cable shall be ISI marked and standard colour: Green (for earthing) to be supplied in 100 mtrs length. Inspection by RDSO.
38	ER	212413 28-03-25	56110194	Single core PVC insulated unsheathed copper conductor cables in voltage grade 1100 V as per IS 5831, Conforming to IRS:S 76-89, nominal cross sectional area of conductor is 2.5 sq mm, Multistrand (36/0.3), thickness of insultaion - 0.8 mm, overall dia meter (appx) 3.8 mm. The cable shall be ISI marked and standard colour : Black, to be supplied in 100 mtrs length. Inspection by RDSO.
39	ER	212414 28-03-25	56110200	Single core PVC insulated unsheathed copper conductor cables in voltage grade 1100 V as per IS 5831, Conforming to IRS:S 76-89, nominal cross sectional area of conductor is 2.5 sq mm, Multistrand (36/0.3), thickness of insulataion - 0.8 mm, overall dia meter (appx) 3.8 mm. The cable shall be ISI marked and standard colour : Blue to be supplied in 100 mtrs length. Inspection by RDSO.
40	ER	212415 28-03-25	56119586	Single core PVC insulated unsheathed copper conductor cables in voltage grade 1100 V as per IS 5831, Conforming to IRS:S 76-89, nominal cross sectional area of conductor is 2.5 sq mm, Multistrand (36/0.3), thickness of insulation - 0.8 mm, overall dia meter (appx) 3.8 mm. The cable shall be ISI marked and standard colour: Red to be supplied in 100 mtrs length. Inspection by RDSO.
41	ER	212416 28-03-25	56119598	Single core PVC insulated unsheathed copper conductor cables in voltage grade 1100 V as per IS 5831, Conforming to IRS:S 76-89, nominal cross sectional area of conductor is 2.5 sq mm, Multistrand (36/0.3), thickness of insulation - 0.8 mm, overall dia meter (appx) 3.8 mm. The cable shall be ISI marked and standard colour: Yellow to be supplied in 100 mtrs length. Inspection by RDSO.
42	ER	212521 01-04-25	56900053	Laser Technology Mouse(Wired). Detail specification attached in Annexure-A.
43	ER	212410 28-03-25	54100033	Supply of Digital Clamp Earth tester/meter, with memory storage facility. Make: Motwane/Maco/ Fluke or similar.
44	ER	212524 01-04-25	56900065	Standard keyboard(wired) . Detailed specification attached in Annexure-A.
45	NR	4410 06-04-17	76010922	MANUAL METAL ARC WELDING ELECTRODES CLASS A-2 (RUTILE TYPE) TYPE OF COATING MEDIUM SIZE 5MM DIA X 450MM LENGTH SPECN. IRS:M 28-12, SPEC. NO.- AS PER IS 814 - 2004.
46	NR	4257 31-03-17	76011513	MANUAL METAL ARC WELDING ELECTRODES CLASS A-3, TYPE OF COATING HEAVY, SIZE 4.00 MM X 450 MM, SPECN. NO. IRS M-28-12, CODE AS PER IS 814-2004.
47	NR	4256 31-03-17	76011150	MANUAL METAL ARC WELDING ELECTRODES CLASS A-2 (RUTILE TYPE) TYPE OF COATING MEDIUM SIZE 5MM DIA X 450MM LENGTH SPECN. IRS:M 28-12, SPEC. NO.- AS PER IS 814 - 2004.
48	NR	4416 06-04-17	76010582	MANUAL METAL ARC WELDING ELECTRODES CLASS A-3, TYPE OF COATING HEAVY, SIZE 4.00 MM X 450 MM, SPECN. NO. IRS M-28-12, CODE AS PER IS 814-2004.
49	NR	4412 06-04-17	76010545	MANUAL METAL ARC WELDING ELECTRODES CLASS A-2 (RUTILE TYPE) TYPE OF COATING MEDIUM SIZE 5MM DIA X 450MM LENGTH SPECN. IRS:M 28-12, SPEC. NO.- AS PER IS 814 - 2004.
50	NR	5100 27-04-17	75612173	FLEXIBLE POLY VINYL CHLORIDE (PVC) FLOORING FOR AC COACHES ALONG WITH 2MM DIA PVC WELDING
51	NR	5642 30-05-17	76300018	NOZZLE OF CNC PLASMA MACHINE SPECIFICATION NO- 100 AMPS. AIR SET HY- SPEED PART NO- 020611

52	NR	5640 30-05-17	76300020	NOZZLE FOR CNC PLASMA MACHINE SPECIFICATION NO- 200 AMP. AIR SET HY SPEED PART NO- 020608.
53	NR	8052 29-07-17	76010314	MANUAL METAL ARC WELDING ELECTRODES CLASS A-2 (RUTILE TYPE) TYPE OF COATING MEDIUM SIZE 5MM DIA X 450MM LENGTH SPECN. IRS:M 28-12, SPEC. NO.- AS PER IS 814 - 2004.
54	NR	50491 27-03-19	56509583	TRACK LEAD JUNCTION BOX
55	NR	50585 27-03-19	56500361	AUTO BATTERY CHARGER,INPUT 230 VAC,OUTPUT 24VDC, 10AMP,FOR SIGNALING PURPOSE TO IRS-S- 86/2000 WITH AMENDMENT No. 4 OR LATEST.
56	NR	50592 27-03-19	56500440	AUTO BATTERY CHARGER,INPUT 230 VAC,OUTPUT 60 VDC, 20 AMP., FOR SIGNALING PURPOSES TO IRS-S-86-2000 WITH AMENDMENT No. 4 OR LATEST.
57	NR	46445 18-02-19	75900087	ISI MARKED LEATHER SAFETY FOOTWEAR FOR PROFESSIONAL USE. NR.SAFETY SHOES/MECHANICAL/DSL/01 REV-7(DEC-2014)
58	NR	36742 13-11-18	76902006	"ENCEE" S" SILVER ALLOY -SIL . 60%+-1% AS PER GR. BACUAG.6 OF IS:29/27/75 SIZE: 1.6X500MM AS PER FOLL OWING COMPLSITION: AG.60-62% CU.27.5-29.5% ZN.9-11%. E
59	NR	50951 29-03-19	76011380	Welding electrode class-D, Size-3.15 MM. AWSE8018W2 EB5326 H2x
60	NR	32100 12-09-18	55630273	STEEL WIRE ROPE 6MM DIA WITH STEEL CORE (WSC) 6X19 (12-6-1) CONSTRUCTION GALVANISED WIRE TYPE A GRADE-1 FREEDOM FROM DEFECTS RIGHT ORDINARY LAY CONF. TO IS 3459-1977 IS: 1835-1976 AND IS : 6594-2001 WITH 2.00 MM UNIFORM WALL THICK BLACK PVC SHEATHING OF TYPE-B CONF. TO IS 1554PT-2 1988 AND IS: 5831 OF 1984 PACKING IN THE REELS OF 1000 METERS STRANDS OF WIRE SHOULD NOT BE OPENED AFTER REMOVAL PVC SHEATHING THE SWG-GZB SHOULD BE MARKED ON THE WIRE ROPE AT EVERY METER LENGTH.
61	NR	135840 08-07-22	75202888	key man tool kit bag
62	NR	108931 06-07-21	76114030	Copper Coated Solid MIG/MAG wire, Class IV to IRS M: 46-2013, Ver. 1, Spec. No.: AWS Code- A5.28-10, Grade-ER 80S-G Diameter of wire = 1.2 mm. Weight of wire spool = Approx. 12.5 kg.
63	NR	136049 12-07-22	56500130	KLCR(KEY LOCK PROVING RELAY) WORKING ON 24V DC WITH MINIMUM 2F/2B CONTACT WITH DIFFERENT WARD COMBINATION
64	NR	136114 13-07-22	56500324	Track Feed Battery Charger 10Amp.
65	NR	136067 12-07-22	56040118	HASSDAC OF M/S CEL MAKE
66	NR	136062 12-07-22	54420015	Spare boom for Electric Lifting Barrier.
67	NR	136059 12-07-22	54420052	Spare part of 110V AC Electric lifting barrier consisting of: 1. Limit Switch 2NO and 2NC 2. Limit Switch 1No and 1NC 3. Limit Switch(one lever type, two top roller type) 4. Timing belt big for pedestal (L285/L300/L322) 5. Timing belt for locking (L98) 6. Push button complete with element.
68	NR	130249 22-04-22	56304572	SWITCH EXTENSION BRACKET AS PER DRG. No RDSO / S -3264 WITH ALT -2.
69	NR	148564 08-12-22	75402178	Vinyl coated upholstery fabric (Artificial Leather) for Humsafar Coaches, Colour- Beige with printed pattern., Spec.: RDSO Spec. No. RDSO 2008/CG-07 (with 5 amendments. Last amendment No. 5 issued in August-2016 and corrigendum-1 of May 2015)
70	NR	148556 08-12-22	75401708	Vinyl coated upholstery fabric (Artificial Leather) for Humsafar Coaches, Colour- Grey-Black, Spec.: RDSO Spec. No. RDSO 2008/CG-07 (with 5 amendments. Last amendment No. 5 issued in August-2016 and corrigendum-1 of May 2015)
71	NR	159147 28-04-23	75403419	Pre-Laminated Shaded Compreg (one side laminated), Specification:- C -K513 (Rev.-0) with 6 amendments & corrigendum. -1 Shade: - Star dust Grey color (one side) Size-1740X580X4mm
72	NR	156622 24-03-23	75400108	Vinyl Coated Upholstery Fabric (Artificial Leather)-Green Colour, Specification:- RDSO/2008/CG-07 (Rev.-0) of August 2008 with five amendments. Last amendment no. 5 issued in August 2016 & corrigendum-1 of May, 2015 Size width 127 cm minimum in roll of 30 meters minimum length.
73	NR	190531 26-06-24	75904287	HPL SHEET 3X1220X2440MM SHADE RAL-9006, MATT FINISH, GLOSS VALUE 10-12 AT 45 DEGREE
74	NR	176370 08-01-24	75030147	Hose assembly for BP for Vande Bharat Express.
75	NR	176487 08-01-24	75320393	Articulated blade B14039 (1000mm) Make Benson or equivalent for Vande Bharat express.
76	NR	176362 08-01-24	75030366	Hose assembly for MR For Vande Bharat Express.
77	NR	177465 23-01-24	75550040	Breakable Cover for Emergency isolation handle for Vande Bharat Express.
78	NR	177463 23-01-24	75030160	Hose pipe for Brake caliper of MR 600 foe Vande Bharat Express
79	NER	656 06-01-17	76218041	HOLDERS ELECTRODE 400 AMPS
80	NER	3546 09-03-17	56507598	TERMINAL BLOCK 6 WAY
81	NER	4895 21-04-17	76015208	MANUAL METAL ARC WELDING ELECTRODE, CLASS-M5, TYPE OF COATING: HEAVY, SPECIFICATION NO.IRS-M-28/2012, SIZE 4.00 X 350 MM AS PER IS: 5206-03, E18.8 Mn R-26 [HEAVY COATED].
82	NER	5308 10-05-17	56500350	BATTERY CHARGER 110 V 12 AC 30 AMP
83	NER	5307 10-05-17	56500336	battery charger 220 V/12 V 2 15 CELLS 160 AMP
84	NER	5305 10-05-17	56468027	Led Based Rout Signal
85	NER	7173 19-07-17	56452081	Handle Support Assly & details for "Q" Type Relay, Drg. No. SWA/QR/99/3 Alt-1. (Approved PL.No. by NER GKP is 56981727)
86	NER	7169 19-07-17	56452093	Cover for "Q" Type Relay for "Q" Type Relay to Drg.No. SW/QR/902/41 Alt-2 (Approved PL No. of NER GKP-56981715)

87	NER	7154 19-07-17	56450084	Set of Molding item for "Q" type Relay as per details. Base of "Q" Type Relay drg. No. SW/QR/90/1A, Alt-2 Qty 01 No, 2, Plug Boar for "Q" Type relay Drg. No SW/QR/90/42. Alt-3 Qty-01 Nos 3. Retaining plate for "Q" Type relay Drg. No-SW.QR/2016/4, Alt-1 Qty-01 No. 4-Molded Block set (a) Standard contact Block Spigoted series Drg. No SW/QR/2016/1, Alt-1 Qty 28 Nos (b) Contact Block Double Spigot Spigoted series Drg.No SW/QR/2016/, Alt-1 Qty-4 Nos (C) Insulated Eng Block for "Q" Type Relay Drg.No SW/QR/2016/3, Alt-1 Qty 02 nos (b) Sealing Plug for Handle used on "Q" type relay Drg. No SW/QR/90/41 Alt-0 (Approved PL by NER GKP is 56981703)
88	NER	7143 19-07-17	56452123	Relay Non AC immunized plug in type style QT-2DC neutral track 9 ohms 2F.2B contacts metal to carbon, complete plug board, retaining clip and connectors confirming to BRS-938A, IRS:S-34 and IRS:23 as applicable. The interlocking code for this unit shall be "DEFIX" (Allotted PL by NER is 56981570)
89	NER	7120 19-07-17	56468003	LED based Shunt Signal Aspect with inbuilt current regulator as per RDSO specification No. RDSO/SPN/153/2011 Rev.4.1 (Approved P.L.No. in NER is 56981569)
90	NER	7116 19-07-17	56503027	TPU Insulating Rail Joint 52 kgs. As per RDSO Specification No. RDSO/SPN/168/2005 Rev.2 and Drg.No. SA-22101 Alt-6. Each set consisting of (1) Channel side plate-04 nos. (2) End Post-01 no. (3) Insulating plate-04 nos. (4) Insulating Bush-08 nos. (Approved PL. in NER is 56981417)
91	NER	7298 20-07-17	56488051	Set of Key Box Assembly for IRS Electric Point Machine as per Specification No IRS : S-24-2002 AMD – 1 (A) Key Box Assembly , Drg. No RDSO/S- 10880 Alt – 2 Qty 1 No (B) Key Drg. No RDSO/S- 10907 –A , Alt – 1, Qty 1 No (Allotted P.L.No. 56981910 by NER GKP)
92	NER	7294 20-07-17	56488178	Set of Lug & Bracket for I.R.S. Electric Point Machine 143 mm , IRS:S-24-2002 AMD – 1 (A) Lock Rod Lug for E.P.M. (R), Drg. No RDSO/S- 3275 Qty 02 Nos. (B)Detector Rod Lug for E.P.M. (R) Drg. No RDSO/S- (ADV) Qty 02 Nos. (C) Switch Extension Bracket Drg. No RDSO/S- 3264 , Alt -3 , Qty 02 Nos. (D) M.S. Washer 33 mm ZN Plated , Qty 02 Nos. (E) M.S. Hex Lock Nut 33 mm ZN Plated , Qty 02 Nos. (F) M.S. Hex Nut -33 mm zinc Plated Qty- 02 Nos.(G) Drive LUG Drg. No RDSO/S- 8806 Qty 01 No (Allotted P.L.No. -56981909 by NER GKP)
93	NER	7293 20-07-17	56488075	Tool Kit for Electrical Point Machine IRS:S 24-2002 AMD -1 (A) Tool Box Drg. No ,According tools Qty 01 Set (B) Cutting Pliers (6 Inches) Qty- 01 Set (C) Nose Plier (6 inches) Qty 01 Set (D) Plier Cutter (6 inches) Qty 01 Set (E) Screw Driver Set to IS : 844 (SIMLAR to TO PARIA Make) Qty 01 Set (F) Screw Driver Large (12 inches) IS : 844 Qty 01 Set (G) Adjustable wrench spanner (12 Inches) Qty 01 Set (H) Double End Spanner (17x19) IS : 2028 Qty 01 Set (I) Double end spanner (30 x 36) IS : 2028 Qty 01 Set (J) Double end Spanner (30 x 32) IS : 2028 Qty 01 Set (K) Single End Spanner 48 mm Qty 01 Set (L) Box Spanner IS : 7381 Of following Size (10mm , 13 mm, 19 mm, & 30 mm ,) Qty 01 Nos Each (M) T – Rod to Suit M6 to M 24 Box Spanner IS : 7975 Qty 01 Set (N) Extension Rod 10 inch to Suit T-Rod or Box Spanner m6 to M 24, IS : 7991 Qty 01 Set (O) Ball Pin Hammer (1L.B.S.) Qty 01 Set (P) Gress Gun Lever Type G – 509 of Prima Make or similar Qty 01 Set. (Allotted P.L.No.56981892 by NER GKP)
94	NER	7291 20-07-17	56488087	Set of Fasteners for IRS Electric Point Machine IRS:S-24 – 2002 Amd-1 as per details:- (1). Bolt ZN plated M. S. Hex ,HD, 12X110mm Qty.-02 Nos. (2). Bolt ZN plated M.S.Hex, HD 12X45mm. Qty.-11 Nos.(3). Washer Machined M 12 mm ZN plated Qty.-13 Nos. (4). Screw M.S. CH,HD,2BA X 12 mm ZN plated.Qty.-08 Nos. (5). Screw M.S. CH,HD,OBA X 12 mm ZN plated.Qty.-08 Nos (6).Lock Nut M.S.M20ZN plated Drg. No. S/10800 (O) Qty.-04 Nos.(7). Lock Nut M.S.Hex M24 ZN plated Drg. No. S/10800 (L) Qty.-04 Nos (8). Washer Punched MS, M24 mm ZN plated.Qty.-04 nos. (9). Washer Punched MS, M20 mm ZN plated Qty.-04 Nos.(10). Nut MS M 24 mm ZN plated. Qty.-04 Nos.(11). Nut MS M 20 mm ZN plated. Qty.-04 Nos (12). Grease Nipple M 5 mm Qty.-05 Nos. (13). Grease Nipple M 8 mm Qty.-02 Nos (14).MS Spring Washer M 20 ZN plated Drg. No.S/10800(O) Qty. 04 Nos. (15). MS Spring Washer M 24 ZN plated Drg. No.S/10800(R) Qty. 04 Nos (Allotted P.L.NO. 56981867 By NER GKP)
95	NER	7288 20-07-17	56488099	Base Assembly set for IRS Electric Point Machine 143 mm IRS : S -24 -2002 AMD-1 Containing items (A) Base Drg. No RDSO/S -10801 Alt – 5 Qty 01 No (B) Bracket R.H Drg. No RDSO/S -10804 Alt – 4 , Qty 01 No (C) Bracket L.H Drg. No RDSO/S -10805 Alt – 4 Qty 01 No(D) Detector Rod bracket Drg. No RDSO/S -10812, Alt – 4 Qty 02 No. (E) Pin Drg. No RDSO/S -10969 . Alt – 1 Qty 14 No(F) Socket head Bolt M.S. M 12 x 20 , Qty 01 No (G) Washer Rubber For M 12 , Qty -01 (H) Drive Rod Cover Plate Drg. No RDSO/S -10808 Alt – 2 Qty 02 No (I) Lock Rod Cover Plate Drg. No RDSO/S -10809A Alt – 1 Qty 02 Nos (J) Detector Rod Cover Plate Drg. No RDSO/S -10813 Alt – 2 Qty 02 No (K) Drive Rod Rubber Gasket Drg. No RDSO/S -10809, Alt – 2 Qty 02 No (L) Lock Rod Rubber Gasket Drg. No RDSO/S -10809B , Alt – 1, Qty- 02 No.(M) Detector Rod Rubber Bracket Drg. No RDSO/S -10814 Alt – 3 Qty 02 No (N) Cable Hole Rubber Gasket Drg. No RDSO/S -10968 , Qty 01 No (Allotted P.L.No.56981820 by NER GKP)
96	NER	7285 20-07-17	56452135	Set of Magnetic path Assembly for QN-1 Relay (1) Heel Piece (complete) for QN-1 & QNA -1 Relays Drg. No – SWA/QR/90/2, Alt - Qty – 01 No (2) Armature Assembly for Q Type relay Drg. No – SWA/QR/90/3, Qty – 01 No (3) Coil Assembly for QNA -1 Relay Drg. No – SWA/QNA-1/02/4, Alt -2 , Qty – 01 No (Total three Assemblies in one set) (Allotted P.L.NO.56981806)
97	NER	7280 20-07-17	56452147	Set of Magnetic path Assembly for QN-1 Relay (12F / 4B) Relay .(1) Heel piece for QN-1 and QNA-1 Relays Drg. No SWA/QR/90/2, Alt -1 , Qty 01 No (2) Armature Assembly for 'Q' type relay Drg. No SWA/QR/90/3, Qty 01 No (3) Coil Assembly for QN-1 type relays Drg. No SWA/QR/90/33, Alt -2 , Qty 01 No total 3 Assemblies in 1 set (Allotted P.L.No.56981790 by NER GKP)
98	NER	7276 20-07-17	56452159	Set of Magnetic path Assembly for QN-1 Relay (8F / 8B) Relay.(1) Heel piece (complete) for QN-1 and QNA-1 Relays Drg. No SWA/QR/90/2, Alt -1 , Qty 01 No (2) Armature Assembly for 'Q' type relay Drg. No SWA/QR/90/3, Qty 01 No (3) Coil for 8F / 8B used in QN-1 type relays Drg. No SWA/QR/92/54, Alt -2 , Qty 01 No (Allotted P.L.NO. 56981788 by NER GKP)
99	NER	7272 20-07-17	56452172	Fasteners Set used in 'Q' type Relay (Pocket -1) :- (1) Special Screw for 'Q' type relay Drg. No SW/QR/96/12, Alt -1 Qty 01 (2) Self Locking Nut for 'Q' type Relay Drg. No SW/QR/96/8, Alt -1 Qty 01 Nos (3) Licking collar for Q type relay drg. No SW/QR/90/24, Alt -1 Qty 01 Nos (4) Operating Arm Pin for 'Q' type relay Drg. No SW/QR/90/20, Qty 01 No (5) Helical Comp. Spring for 'Q' Type relay Drg. No SW/QR/90/23, Alt -2 Qty 01 No (6) Helical comp . spring up to ½ " dia for 'Q' type relay Drg . No SW/QR/90/25, Alt -1 Qty 01 No (7) Washer for 'Q' type relay Drg. No SW/QR/91/52, Qty 01 No . (Pocket -2) :- (1) Stack Screw (short) 'Q' Type relay Drg . No SW/QR/96/7, Alt -3 Qty 02 No (2) Stack Screw (Long) 'Q' type relay Drg . No SW/QR/96/7, Alt -3 Qty 02 No (3) Stack Screw (Hex Nut- M3.5) 'Q' Type relay Drg . No SW/QR/96/7, Alt -3 Qty 02 No (4) Plain Washer for 6 BA Screw 'Q' type Relay Drg . No SW/QR/91/48, Alt -1 Qty 04 Nos (pocket -3) :- (1) Screw for insert 'Q' type relay Drg . No SW/QR/91/47, Qty 02 No (2) Inter Locking Pin for 'Q' type relay Drg . No SW/QR/96/10, Alt -1 Qty 05 No (3) Rubber Washer for 'q' type relay Drg . No SW/QR/91/51, Qty 02 No (Pocket No -4) :- (1) Relay Retaining Click for 'Q' type relay Drg . No SW/QR/90/39, Alt -2 Qty 01 No (Allotted P.L.No 56981764 by NER GKP)
100	NER	7383 20-07-17	76010016	Manual Metal Arc welding Electrode size 4.00x450 mm IRS Class D, Coating Heavy to IRS Specn. No. M: 28/2012 (Allotted P.L.No.-76986184 by NER GKP)

101	NER	7379 20-07-17	76010077	Manual Metal Arc Welding Electrode Size - 3.15x350 mm, Class-D, Heavy Coating to Specn. No. IRS M: 28/2012 IS/AWA Code E8018W2 (Allotted P.L.no.-76986160 by NER/GKP)
102	NER	7374 20-07-17	56488117	Set of Main Gear Assembly for IRS Electric Point Machine 143 mm as per Specification No. IRS:S-24-2002 AMD-1 and details:- (A). Main Gear Assembly Drg. No. RDSO/S-10835 Alt-3 Qty.-01 No. (B). Sealing arrangement with seal Drg. No. SW/PM/2002/12 Qty.-01 No. (C). Gear Box Bracket Drg. No. RDSO/S-10869 Alt-3 Qty-01 No.(D). Gear Box Bracket Bush Drg. No. RDSO/S-10868 Alt-2 Qty.-01 No. (E).Main Gear Bracket Drg. No. RDSO/S-10845 Alt-2 Qty.-02 Nos. (F). Main Gear Bracket Bush Drg. No. RDSO/S-10846 Alt-2 Qty.-02 Nos. (G). Drive Rod Drg. No. RDSO/S-10803 Alt-4 Qty.-01 No. (H). Lock Rod (R.H) Drg. No. RDSO/S-10806 Alt-6 Qty.-01 No. (I).Lock Rod (L.H) Drg. No. RDSO/S-10807 Alt-6 Qty. 01 No. (J).Detector Rod (L.H) Drg. No. RDASO/S-10810 Alt-4 Qty.-01 No. (K). Detector Rod (R.H) Drg. No. RDSO/S-10811 Alt-4 Qty.01 No. (Allotted P.L.No.-56981843 by NER GKP)
103	NER	7308 20-07-17	56488129	Solid Joint (But End) for IRS Electric Point Machine (A) Solid Joint (But End)32 mm Drg. No SA 6050/M Alt – 3 Qty -01 No . (Allotted P.L.NO. 56981934 by NER GKP)
104	NER	7304 20-07-17	56488142	Cover Assembly and slide cover set for IRS Electric Point Machine IRS -24- 2002 (A) Cover Assembly Drg. No RDSO/S- 10865 Alt – 2 Qty 01 No(B) Oil Felt Arrangement Drg. No RDSO/S- 10956 Alt – 1 Qty 1 No (C) Slide cover complete for drive rod & Lock Rod Drg. No RDSO/S- 10848 A Alt – 2 Qty 2 No (D) Slide cover complete for detector Rod Drg. No RDSO/S- 10848 B Alt – 2 Qty 2 No (E) Anodized Label Drg. No SW/PM/05/2 , Qty 1 No (F) Anodized circuit diagram Drg. No SW/PM/2000/38 ,Qty 01 No (Allotted P.L.No. 56981922 by NER/GKP)
105	NER	7216 20-07-17	56488154	Wiring set complete for IRS Electric Point Machine, IRS:24-2002 Amd-1 (A) Terminal Wire used for Drg. No SW/PM/2006/9, Qty-1 set (B) Terminal Wire used for Electric Point Machine (Rotary) Drg. No.- SW/PM/2006/10, Qty-01 set (Allotted P.L.No.-56981880 by NER GKP)
106	NER	7212 20-07-17	56300529	Contactor Unit Assembly for IRS EPM 143 mm As per details:-Contractor Unit Assembly Drg. No. RDSO/S-10911 Alt-2 (Alloted P.L.No. 56981855 by NER/GKP)
107	NER	7209 20-07-17	56488166	D.C, Motor Assembly for IRS Electric Point Machine as per Specification IRS:S-37/82 Alt-3 and details:- (A)D. C. Motor Drg.No.RDSO/S-10910 Alt-3. (B) Gear Box Drg. No. RDSO/S-10850 Alt-2. (Allotted P.L.NO. 56981331 by NER GKP)
108	NER	7206 20-07-17	56450047	Packing Box (Thermocol Container) for "Q" type Relay to Drg. No. SW/QR/91/53, Alt-2 (Allotted P.L.No. -56981818 by NER GKP)
109	NER	7203 20-07-17	56452184	Contact Tip for plug in Relay Style "Q", Drg. No. SW/QR/90/K, Alt-4 (Allotted P.L.NO. 56981776 by NER GKP)
110	NER	7199 20-07-17	56452196	Punching Item set used in Contact group Assembly for "Q" type Relay Packet No:-1. (1) Coil Lead Conector for "Q" Type Relay Drg. No. SW/QR/90/17, Alt-1 Qty 02 No (2) Connector for "Q" Type relay Drg. No. SW/QR/90/18, Alt-1 Qty 02 no. (3) Stack Retaining plate for "Q" type relay Drg No. SW/QR/90/136, Alt-12 Qty 01 no (4) Metal End Stack Block for "Q" type relay Drg. No.SW/QR/96/11, Alt-1 Qty 04 Nos (5) Double Anchor Block for "Q" type relay Drg. no. SW/QR/90/7, Alt-1 Qty 0 no. (6) Wavey Washer 0.25 mm thick for "Q" type relay Drg No. SW/QR/90/13, Qty 04 nos. (7) Armature Retaining strip for "Q" type relay Drg. No. SW/QR/90/28m Qty 01 no. (Packot 02):- (1) Wavey washer 0.4 mm thic for "Q" type relay Drg. No SW/QR/90/6, Qty 01 No, (2) Operating Arm for "Q" type relay Drg. No. SW/QR/90/19, Alt-2 Qty 04 Nos (3) Adjustment Card for "Q" type relay Drg. No. SW/QR/90/21, Alt-1 Qty 04 Nos. (4) Spring Retaining cup for "q" type relay to Drg. No SW/QR/96/9, Alt-2 Qty 01 no (Pocket-+3)L-(1) Carbon Clip for "Q" Type relay Drg. No. SW/QR/90/M Qty 16 nos (Pocket 4): (1) Connect to used on qN-1 Relay Drg. Nos SW/QR/91/44, Alt-3 Qty 36 Nos. (Alloted P.L.No.-56981752 by NER GKPD)
111	NER	7192 20-07-17	56452202	Silver Impregnated Graphite (SIG) contact for plug in type Relay, Clause 8:to:Specn.No.IRS:S-67/85 (Amendment-2) (Alloted PL no. 56981740 by NER GKP)
112	NER	7190 20-07-17	56452214	Spring Set used in Contact Group Assembly for "Q" Type Relay as per details. Fixed spring for QN-1, QNA-1 Drg. No SW/QR/90/L, Alt-II, Qty 60 Nos, 2. Moving Spring for QN-1, QNA-1 Drg. No. SW/QR/901/1, Alt-2 qty 16 Nos, 3- Support for "Q" Type Relay Drg. No. QR/90/16, Alt-2 Qty 04 Nos. (Approved PI by NER GKP is 56981739)
113	NER	7540 22-07-17	76010089	Welding electrode class-G "medium coated ENIFCG-16Size 4mm RDSO Approved (Running P.L. at GKPD is 76986240)
114	NER	914 20-01-17	56234193	Gate Indicator Lamp Crank LH & RH Drg. No. S8200M & S-8199M (allotted P.L.by NER GKP 56982021)
115	NER	8198 01-08-17	75613840	FLEXIBLE PVC FLOORING WITH PVC ELECTRODE FOR NON-AC COACHES SIZE-14000 MM L X 1620 MM W X 2 MM THICK CONFORMING TO RDSO Specn. NO. RDSO/2006/CG-12 (REV.1) OF Aug. 08 and COLOUR SAMPLE CODE NO. NAC FLG-02
116	NER	8047 28-07-17	76210042	CUTTING TORCH CUTOGEN-5 IS-7653/1975
117	NER	8160 01-08-17	75403651	DECORETIVE THROMESETING RISEN BONDED.LAMINATED SHEET CONFIRMING TOBE REFFID STEPILETED IN RDSO LUCKNOW SHIDULE NO.C-9602 OF FEB 1997 WITH AMDT SLIP NO.2 OF JAN 2000 SIZE 2.44MX 1.22MMX3.00MM THIKNESS COULER CREAM MORVEL
118	NER	8715 11-08-17	76010016	Electrode Class- D Size 4.0 x 450 MM
119	NER	8724 11-08-17	76010041	Cutting & Chamfering Electrode Size 3.15 x 350 MM Class- N2
120	NER	8720 11-08-17	76218697	Double Stage Regulator with flow Meter, Type of Gas CO-2, Max Inlet Pressure (BAR)- 200, Flow: LIT/MIN 35 Ft3 /h:74,INLET Connection: 0.860 x 14 TPI R/H (Female) Out Let Connection: 3/8" R/H (Male)
121	NER	5303 10-05-17	54900761	Flange Plate for L.B.gate
122	NER	4991 25-04-17	54900761	Flange Plate for L/B Gate Drg. No. SW/91/14 (Alloted P.L.NO.-56981958 by NER Gorakhpur)
123	NER	9835 07-09-17	76050040	Manual Metal Arc Welding Electrode , CClass M2, Size 3.15 x 350 Mm, Type of coating- Heavy (Spec. No. IRSM-28-12, code as per IS: 5206-2003)
124	NER	9834 07-09-17	76010594	Manual Metal Arc Welding Electrode , Class- M4 Size 3.15 x 350 Mm, Type of Coating- Heavy (Spec. No- IRSM-28-12, code as per: 5206-2003)
125	NER	7223 20-07-17	54900785	Pedestal Drg. No. SWA/LB/2015/40 (Allotted P.L.NO. 56981946 by NER GKP)
126	NER	7231 20-07-17	54900748	Flange Plate for LB gate as per Drg. No. SW/LB-06/30 (Allotted P.L.No. -56981960 by NER GKP)
127	NER	7313 20-07-17	54900736	Drum Wheel LH & RH Drg. No S-8125 M , Alt -4 and S-8126 & Alt -3 (Allotted P.L.NO.-56981971 by NER GKP)

128	NER	7323 20-07-17	54900712	Gate Indicator Lamp CAM LH & RH RDSO Drg. No S-8196 /M & S-81195/M (Allotted P.L.No.56982010 by NER GKP)
129	NER	7329 20-07-17	54900177	Set up casting item for boom tail Assembly of Lifting Barrier Gate (1) TRRUNION Bracket Assembly : (A) TRRUNION Bracket (R.H) Drg. No S 8099 A/M Alt – 02 , Qty 01 No (B) TRRUNION Bracket (L.H) Drg. No S 8099 B/M, Alt – 02 , Qty 01 No (C) DRUM - PIN Drg. No S 8127/M Alt – 01 , Qty 02 No (D) Drum – Roller Drg. No S 8129/M , Alt – 01 Qty- 02 No (E) CLAMP –A Drg. No S 8104/M, Alt – 01 , Qty 02 No (F) CLAMP – B Drg. No S 8105 /M, Alt – 01 , Qty 02 No (2) Tubular Pole Plug –B, Drg. No S 8012/M Alt – 01 , Qty 02 No (3) Tubular Pole Cylindrical Weight. Drg. No S 8011/M ,Alt – 01 , Qty. 22 No (Allotted P.L.No.-56982033 by NER GKP)
130	NER	7330 20-07-17	54900578	Set up Counter weight for L. B. Gate (A) Balance Weight Weight Drg. No S – 8096 /M , qty 04 Nos (B) Balance weight Auxiliary weight Drg. No S- 8098 /M Alt -01 Qty 04 Nos (Allotted P.L.No.-56982045 by NER GKP)
131	NER	7332 20-07-17	54900566	Set up Misc costing item for LB Gate (1) Lifting barrier Bearing Drg. No S-8102 /M Alt 01 Qty 04 Nos (2) Drum – Bracket Drg. No S-8130 , Alt 01 Qty 02 Nos (3) Stop Post Base for Lifting Barrier Drg. No SW/LB/2015/39 Qty 02 Nos (4) Lifting Barrier Distance Piece Drg. No S-8131 /B/M , Alt 01 Qty 02 Nos (Allotted P.L.No.-56982057 by NER GKP)
132	NER	7558 22-07-17	76210042	GAS CUTTING TORCH CUTOGEN-5
133	NER	7535 22-07-17	56452111	Relay AC immune plug in type style QBCAI DC based point contactor 24V 2F HD 4B contacts front contacts heavy duty and back contacts metal to carbon, complete plug board , retaining clip and connectors confirming to BRS-943, IRS :S-34 and IRS:23 as applicable. The interlocking code for this unit shall be 'BCEJK' .
134	NER	7504 21-07-17	75612185	SYNTHETIC RUBBERISED CORK SHEET CONFIRMING IS: 4253 Pt-II 1980 IN TG- 7 G GRADE 915X610X10 MM GRRC 70. "
135	NER	7449 21-07-17	76100029	SOLID TIG welding rod/filler wire for welding of aluminium and aluminium alloy to AWS class-ER.4043 As per specification-AWS.5.10 SIZE 3.2 x 1000mm. with silicon content-6.0%
136	NER	7321 20-07-17	54900724	Lifting Barrier winch Assembly , Drg. No SA-8132A Alt-1 (Allotted P.L.No.56981995 by NER/GKP)
137	NER	7112 19-07-17	56500257	Thermo Sink Jointing Kit for jointing underground PIJF cable 20 pairs, 0.63 mm cojdutor dia as per RDSO Spec.No. RDSO/SPN/TC/57/2015 Rev.-1 with latest amendment. (Approved P.L. of NER is 56980346)
138	NER	7113 19-07-17	56500282	Thermo Sink Jointing Kit for jointing underground Quad Cable 0.9 mm conductor dia as per Specification No. IRS:TC 77/2012 Rev.3.0 with latest amendment.(Approved P.L. of NER-56980541)
139	NER	10793 07-10-17	56480891	TELESCOPIC PIPE FOR I.R.S.,ELECTRIC POINT MACHINE 143 MM IRS:S-24-2002 AMD-1
140	NER	13182 23-11-17	76010272	Electrod 10 SWG for welding ,Class A1size -3.15mmx350mm as per Spec. no.IRS M-28/12 Amendment no. 1 of March 2003&Amendment no.2 of Sep.2003 and as per IS-814/2004
141	NER	13186 23-11-17	76010259	M.S.Welding Electrod Class A1,Size -4x450mm to IRMS -28/02 Amendment no. 1 of March 2003 and Amendment No. 2 of Sep. 2003, Code as per IS-B14/2004 RDSO approved brand
142	NER	17553 13-02-18	75403705	DECORATIVE THERMOSETTING SYNTHETIC RESIN BONDED LAMINATED SHEET of size 2.44M x 1.22 M x 3.0MM thick conforming to RDSO Specn. No. C-K514 with corrigendum slip No. 1 of Jan. 2006 and amdt.slip No. 3 of Jan. 2010. Surface finish- sami matt. Colour. As per sample code No. AC-SP02. Note - Marking particulars on each L.P. sheet should be as per para 6.1 of the RDSO specn.
143	NER	17550 13-02-18	75403640	DECORETIVE THROMESETING RISEN BONDED.LAMINATED SHEET CONFIRMING TOBE REFFID STEPILETED IN RDSO LUCKNOW SHIDULE NO.C-9602 OF FEB 1997 WITH AMDT SLIP NO.2 OF JAN 2000 SIZE 2.44MX 1.22MMX3.00MM THIKNESS COULER CREAM MORVEL
144	NER	21368 30-03-18	56150064	LOW MAINTENANCE LEAD ACID STATIONARY SECONDARY CELLS 300AH-2VOLT FOR S&T INSTALLATION AS PER RDSO SPN NO.IRS:S-88/2004 OR LATEST
145	NER	30388 16-08-18	75403638	Decorative thermosetting synthetic resin bonded laminated sheet of size- 2.44M x 1.22M x 3.0 mm thick confirming to RDSO Spec. No. C- K514 with corrigendum slip No. 1 of Jan.2006 and Amndt. slip No.5 of April2015, Surface finish - Semi-matt. Colour-Star dust grey. Note:- Marking particulars on each L.P. sheet should be of as per para 6.1 of RDSO spec. No. C-K514.
146	NER	30389 16-08-18	75440015	Belt Fastener for 75 mm Train Lighting Belting complete with plates and pin as per RDSO Drg. No. SKEL-3714 Alt-1 (Part 3-B), Dimensions as per RDSO Drg. no. SKEL-3714 Alt-1(part-1)
147	NER	34386 15-10-18	56060129	INSULATION RAIL JOINT KIT 60 R AS PER IRS SPECIFICATION NO-IRS-S-40/84 AND DRG NO-SA-22131 OR LATEST ONE KIT CONSISTING OF(!)END POST=01NO(!)INSULATINGPLATE =04 NO(!) CHANNELSIDE PLATE LH=02 NOS (!V)CHANNEL SIDE PLATE RH=02 NO(V)BUSH=08 NO.
148	NER	36658 13-11-18	56060040	Insulator Light weight Unbreakable Poly Carbonate Specn NO_IRS;TC;32-07(Amdt NO 1
149	NER	40463 18-12-18	75904214	Decorative thermosetting synthetic resin bonded laminated sheet of size 2.44M X 1.22M X 3.0mm thick conforming to RDSO Specn. No. C-K514 with corrigendum slip No. 1 of Jan. 2006 and amdt. slip No. 3 of Jan. 2010. Surface finish-semi-mat colour Star Dust Brown. Note- Marking particulars on each L.P. sheet should be as per para 6.1 of the RDSO Spccn.
150	NER	40785 22-12-18	75320174	Densified Thermal Bonded Polyester block for Transverse sheet for A.C. Three Tier coach Drg. No. A.E.-61442 Size 1822x625x95mm
151	NER	40783 22-12-18	75320186	Densified Thermal Bonded Polyester block for Back Rest Cum Berth (Short) for A.C. Three Tier Coach Drg No. A.E. 61457 Size1- 910x566x49mm, Size2-1003x566x58mm , Size3-785x566x49mm, Size4- 767x566x58mm = 1 Set
152	NER	40780 22-12-18	75320204	DENSIFIED THERMAL BONDED POLYESTER BLOCKS For middle and upper Berth for A.C. Three Tier Coach Drg. No. A.E.-61444, A.E.-61446 Size-1795x583x95 mm RDSO Spec.No. CK607-Rev-I
153	NER	45901 12-02-19	76014228	Manual Metal ARC welding electrode class N-1 DRG NO IRS ; M-28-02 AMMNDT NO 1 OF MARCH 2003 & AMMND NO 2 OF SEPT 2003 .
154	NER	53646 22-04-19	55630133	WIRE ROPE STEEL GALVANISED RDSO Specification No. IRS:S-11/62
155	NER	56569 28-05-19	56300050	Cover Assembly Set for EPM-220mm as per attached list
156	NER	56568 28-05-19	56304559	Set of Main Gear Assembly for EPM-220mm as per attached list.
157	NER	56564 28-05-19	56300270	Set of Assembly parts of-60kg TWS clamp point lock with ground connections as per attached list1&2
158	NER	56561 28-05-19	56300256	Set of insulating Bush and Washer for EPM -220mm

159	NER	70422 23-10-19	56480908	Base assembly Set for EPM-220mm AS per attached list
160	NER	107698 18-06-21	56300074	SET OF COVER ASSEMBLY WITH KEY BOX ASSEMBLY FOR EPM 220 MM AS PER ANNEXURE
161	NER	130159 21-04-22	56301601	D.C. Motor Assembly for IRS Electric Point Machine as per Specification IRS:S-37/82 Alt-3 and details:-(A)D. C. Motor Drg.No.RDSO/S-10910 Alt-3. (B) Gear Box Drg. No. RDSO/S-10850 Alt-2.
162	NER	132413 19-05-22	75107612	Pliers proof low density polyethylene sealing tablets for Relays with six digit higher raised number with ELS/CNB emboss, one locking male connected female by high Co-polymer one groove resister pattern in red colour as per drg. No. A3/2010/CNB/2368/5067/RQL
163	NER	139040 20-08-22	56301571	IRS Type Ground Connection for Electric Point Machine - 143 mm Stroke as per Attached Annexure
164	NER	154253 16-02-23	75401964	SOLID LAYER VINYL COATED FABRICS, SHADE BLUE AS PER RDSO SPEC.NO.RDSO/2008/CG-07 [Rev.0 of AUG.08 WITH AMENDMENT-01NOV.08]Or Latest.
165	NER	128798 01-04-22	75030019	FABRICATED RUBBER HOSE PIPE INNER DIA 100 MM, OUTER DIA-114 MM , LENGTH 36", IS:444/1987
166	NER	128917 05-04-22	75033306	FABRICATED RUBBER HOSE PIPE LENGTH- 36 INCH , INNER DIA-32 MM, THICKNESS-05MM, IS:444-1987
167	NER	174399 07-12-23	76011460	Manual Metal Arc Welding Electrode, Dia: 4mm, Class E2, Type of Coating: Heavy, Conforming to Spec. No. IRS: M-28/2020, Code 'E55BG1Ni26' as per IS:1395-2003.
168	NER	182769 29-03-24	75320230	Grooved Rubber Profile for safety strap of retention tank as per drawing-No. ICF/SK3-6-3-201 Alt.-Nil or Latest
169	NER	181304 15-03-24	75400066	HPL SHEET 3X1220X2440MM SHADE RAL-9006, MATT FINISH, GLOSS VALUE 10-12 AT 45 DEGREE as per Drg.No. MDTs-086 REVISION-01, Packing Instruction - PI119 VER2.0
170	NER	181300 15-03-24	75613438	PVC FLOORING ROLL 2X1850X14000MM, COLOUR AS PER SAMPLE NO. NACFLG-02 FOR LHB COACHES as per Drg.No. RDSO/2006/CG-12 REVISION 1 WITH AMENDMENT SLIP (WARRANTY CLAIM WILL BE AS PER MCF DESIGN LETTER NO. RBL-MD33151 DATED 19.11.2018), Packing Instruction - PI163
171	NER	197141 21-09-24	76011811	MMAW ELECTRODE, SIZE:- 3.15 MM DIA X 350 MM, CLASS-M5 TO CODE: E18.8MnR26 (HEAVY COATED) OF IS: 5206- 2013. DRAWING NO.: ----- MATL. & SPEC.: IRS: M28/2020
172	NER	186666 14-05-24	75400133	REXINE FOR HUMSAFAR COACH , WIDTH - 1370 M COLOUR , SHADE AND PATTERN AS PER 02 NOS SAMPLE ATTACHED (EACH SAMPLE REQUIRED EQUAL QUANTITY , SAMPLE NO-1 AND SAMPLE NO-2) AS PER RDSO SPECIFICATION NO- RDSO/2007/CG-7 , REVISION -NIL, WITH AMENDMENT SLIP NO- 4 NOTE- SAMPLE TO BE APPROVED BY CONSIGNEE AGAINST COLOUR, SHADE AND PATTERN REF. ONLY BEFORE BULK SUPPLY IT IS ICF RESERVE ITEM
173	NER	192755 30-07-24	75101099	Supply of Bellow duct with Meta/Para Aramide Fabric Bellow duct for LHB AC coaches,(EOG TYPE AC Coaches) conforming to RDSO Specification No. RDSO/PE/SPEC/AC-0197-2020(Rev-0) as per Scope of Supply per RMPU Consisting of 1 No. of supply air bellow, 2 No. of Fresh Air bellow and 2 No. of Return Air bellow Duct With metallic frames as per RDSO Drg No. RDSO/PE/SK/AC/0069-2004(Rev-3). material to be procured from RDSO Approved suppliers. Warranty must be covered railway board letter no. EL/7.2.2. Bellow duct/main dt. 23.11.2023
174	NER	182763 29-03-24	75402245	Rexine Economy (Colour shade PF DK Gray) RDSO/2008/CG- 07 REV-Nil
175	NFR	873 19-01-17	76115100	UNF ELECTRODE WIRE FOR MIG/MAG
176	NFR	925 20-01-17	76210560	UNF GAS SHIELDED FLUX STAINLESS STEEL
177	NFR	30408 16-08-18	75613827	PVC flooring Almond Brown Roll, 11200005/12206905 sheet to size: 2 x 1850 x 14000mm, of premier vinyl or similar as per RDSO SK. No. 90068.
178	NFR	67335 12-09-19	75401721	Rexin in width of 1370 mm to Specification RDSO/208/CG-07 revision nil with amendment slip No.04 for Humsafar AC coaches, color shade and pattern as per Humsafar RCF/MCF.
179	NFR	138043 05-08-22	76016845	MANUAL METAL ARC WELDING ELECTRODE, CLASS-M5, TYPE OF COATING : HEAVY, (SPECN. NO. IRS:M-28/12 AMENDMENT-1& 2), SIZE 4.00 X 350 MM. CODE E 18.8 MnR 26.
180	NFR	129432 13-04-22	76014046	Stainless steel Electrode Size 3.15mm dia. & length 350 mm Approved by RDSO class M-4 heavy coated, code E 2313-R-26 as per ISO 5206/83 IRS:M-28/2020 amendment 1 and 2 or latest.
181	NFR	129503 15-04-22	76015282	MANUAL METAL WELDING ELECTRODE IRS CLASS M-2, FOR BOXN HL WAGON IS CODE E-19-9 LR-26 HEAVY COATED TO IRS M 28/2020 OR LATEST WITH LATEST AMND SIZE 4MM DIA INTO 350mm LENGTH.
182	NFR	159869 12-05-23	76900605	STAINLESS STEEL GAS SHIELDED FLUX CORED MIG/MAG FILLER WIRE ELECTRODE OF SIZE: 1.2 MM DIA, IRS CLASS-VII CONFORMING TO IRS SPECN. NO. M-46/2020, EQUIVALENT GRADE AS PER AWS: A 5.22/A5.22M:2012
183	NFR	159865 12-05-23	76115604	Flux cored MIG/MAG welding filler wire size 1.2 mm with shielded gas, class IV to (Spec. No. IRS M-46/2020, Grade as per AWS:A5.29-10, Grade-E81T1-W2C).
184	NFR	154467 20-02-23	75300011	Scrapper Mat for Lavatory Floor of IR Coaches as per RCF Kapurthala's Specification MDTs-229 Rev-00 except thickness which will be 4 mm to 4.5 mm instead of 5.3 mm and width 1.05 meter instead 0.91 meter. Length of the item:- 1.20 meter. (Technical Specification Attached).
185	NFR	130314 22-04-22	56118351	PVC Insulation underground unscreened Railway Power Cable (2x25 sq.mm) as per RDSO Spec. No. IRS:S-63/2014 & IS:1554 (Part-1)(Rev.4.0)
186	NFR	187097 20-05-24	76210224	Nozzles with Electrode/fidder of plasma cutting Torch Model P80-60A(5M) machine Model no -CUT60(WC60) or CUT100(WC10A). Make Make-Rail wolf
187	NFR	187140 20-05-24	76210170	Nozzle pt no 420134 and Electrode pt no 420132 for use in professional Plasma cutting machine. Make :- Hypertherm or similar. Model no-Powermax30 AIR
188	NFR	193067 04-08-24	76010521	Manual Metal Arc welding electrodes, Class-A2(Rutile type), Type of coating: Medium,(Specn. No.IRS-M-28/12, Code as per IS:- 814-2004), Size-3.15mm X 350mm.
189	SR	15436 10-01-18	56119033	CABLE PVC INSULATED ARMOURED UNSCREENED RAILWAY SIGNALLING CABLE OF SIZE 19C x 1.5 sqmm (REV 4.0) IRS:S-63/2014 OR LATEST
190	SR	15430 10-01-18	56509960	- CABLE PVC INSULATED ARMOURED UN SCREENED UNDER GROUND POWER CABLE OF SIZE 2C x 25sqmm ALUMINIUM IRS:S-63/2007 WITH AMENDMENT No.3 IS.1554/PART-1 OR LATEST
191	SR	15429 10-01-18	56500178	SPACER (PB) TO DRG.No.QCA 35971 ALT.3 FOR Q SERIES RELAYS

192	SR	15376 09-01-18	56500180	SUPPORT BRACKET TO DRG.No.QCA 12970/2 OF 2 ALT-5 FOR PSECIAL TYPE RELAYS.
193	SR	15375 09-01-18	56500543	PIVOT PLATE (WITH HARD CHROME PLATING) TO DRG. No. QSC 02970 ALT-2 FOR QT2, QTA2, QBAT, AND QSPA1 RELAYS.
194	SR	15374 09-01-18	56452081	HANDLE SUPPORT TO DRG. No.QSB 01970 ALT-2 FOR QT2, QTA2, QBAT AND QSPA1 RELAYS.
195	SR	15373 09-01-18	56503118	SLUG COPPER TO DRG.No.CWM 06507 ALT-1 FOR QTA2 RELAYS
196	SR	15372 09-01-18	56503120	SLUG COPPER TO DRG.No.QBT 05970 ALT-2 FOR QBAT RELAYS
197	SR	15368 09-01-18	56300037	NAME PLATE AND WIRING DIAGRAM PLATE IN SET FOR IRS POINT MACHINE. ONE SET COMPRISING OF (1) NAME PLATE TO DRG. No.CWM 02502 ALT-1 - 1 No. (2) NAME PLATE TO DRG. No. CWM 05707 - 1 No. (3) WIRING DIAGRAM PLATE TO DRG. No. CWM 02602 ALT-2 - 1 No. (THREE ITEMS ONLY) EACH SET TO BE PACKED SEPERATELY.
198	SR	15367 09-01-18	56300219	THREADED END FOR LOCK ROD TO DRG. No. CWM 03105 (TO BE SUPPLIED WITHOUT DRILLING 8.2 mm DIA 2 HOLES AND WITHOUT ZINC PLATING)
199	SR	15365 09-01-18	56500191	SHUNT (SOFT MAGNETIC IRON) TO DRG. No.QBT 06970 ALT-2 FOR QBAT AND QNA1K RELAYS.
200	SR	15362 09-01-18	56462050	AC SHUNT SIGNAL (LED) WITH INBUILT CURRENT REGULATOR WITH RDSO INSPECTION. RDSO SPE. NO. RDSO/SPN/153/2011 (REVISION-4.1)
201	SR	15360 09-01-18	56468064	- CALLING ON LED SIGNAL LIGHTING UNIT 100VAC RE-PROFITABLE IN EXISTING CLS HOUSING AND COMPATIBLE WITH AC LED ECR. RDSO SPECIFICATION NO.RDSO/SPN/153/2004 REV.3.0 DRAFT OR LATEST.
202	SR	15358 09-01-18	56468027	ROUTE LED SIGNAL LIGHTING UNIT 100V AC RE-PROFITABLE IN EXISTING CLS HOUSING AND COMPATIBLE WITH AC LED ECR. RDSO SPECIFICATION NO.RDSO/SPN/153/2004 REV.3.0 DRAFT OR LATESTv
203	SR	15494 11-01-18	56020790	- DYNAMIC HANDSET FOR BLOCK INSTRUMENT AS PER SPECIFICATION No.S&T/S.033 OF S&T WOTKSHOPS, PODANUR
204	SR	15495 11-01-18	56500208	PURE IRON FLAT TO SIZE 4mm THICK (+/- 0.15mm) X 55MM WIDTH (+/- 0.5mm) X 900mm-1000mm LONG FOR QTA2 SHUNT.MATERIAL PROPERTIES: 1) HIGH PURITY IRON WITH LOW RESIDUAL ELEMENTS. 2) IMPURITIES MAX:- C=0.01% MIN=0.20%. S=0.015%, P=0.15%, 3)COLD ROLLED IN ANNEALED CONDITIOIN. TEST CERTIFICATE FOR THE CHEMICAL COMPOSITION SHALL BE SUBMITTED ALONG WITH THE SUPPLY
205	SR	15496 11-01-18	56500210	SPECIAL SCREW 4BA TO DRG.No.QSC 10970 ALT-3 FOR QT2, QTA2, QB3, QBAT AND QSPA1 RELAYS
206	SR	16818 02-02-18	76011800	Stainles steel MMAW Electrodes size.4mm x350mm to specification E.19.9LR26(heavy Coated of IRS M28/12 M2 Class of Table 1 with amendment 1 of 2016.IRS.M28/12,M2 class of Table 1 with Amendment 1 of 2016
207	SR	6716 13-07-17	56110029	CABLE PVC INSULATED ARMOURED UNSCREENED UNDERGROUND POWER CABLE 3C X 10 SQ.MM
208	SR	25271 05-06-18	56450485	SPRING WASHER (PB) TO DRG NO QSA 05971 ALT-4 FOR QNA1 & QBAT RELAY.
209	SR	30857 25-08-18	75900063	SLEEVES LEATHER- SHEEP-SKIN-THICKNESS 1.25mm TO 1.5mm 450mm LONG (THE LEATHER SHALL BE SOFT PLIABLE SHEEP-SKIN FREE FROM PIN HOLES AND OTHER VISIBLE (DEFECTS) OR LOOSE FIBRES WHICH COULD ADVERSELY AFFECT ITS SERVICIABILITY AND STRENGTH. FURTHER THIS SHALL NOT BE TREATED AS TO OBSCURE DEFECTS OR BE STAINED WITH COMPOUNDS OF IRON WHICH WOULD MAKE IT WROUGHT UNDER HUMID CONDITIONS) TO IS 1640/60.SRIC.NO.300
210	SR	34425 16-10-18	75905012	: Acrylic sheet, size 1220 x 915 x 5mm, transparent to IS:7569-87 or latest.
211	SR	49984 25-03-19	56500350	BATTERY CHARGER 110V AC 24V DC 30 AMPS TO SPECN.IRS-S-86/2000.WITH AMENDMENT-4 or latest.
212	SR	47439 01-03-19	76011331	Manual metal Arc welding Electrode,2.5mm x 350mm long, class D, Type of coating- Heavy specification No. IRS M-28/17. Code E8018 W2 as per AWS 5.5.
213	SR	49986 25-03-19	56500452	BATTERY CHARGER 230V AC 110V DC 30 AMPS SPECN.No.IRS-S-86/2000 WITH AMENDMENT - 4. OR LATEST.
214	SR	42731 18-01-19	76216135	FLASH BACK ARRESTOR(DRY TYPE) FOR TORCH END OF OXYGEN LINES TO PREVENT FLASH BACKS IN OXY FUEL SYSTEM CONFORMING TO EN 730/ISO 5175-1/IS 11006 STANDARDS WITH FLAME ARRESTOR(FA) AND NON RETURN VALVE(NRV) WORKING PRESSURE: 15 BAR. END CONNECTIONS G 3/8" RH TO EN 560/ISO 3253 STANDARDS. MAKE: MESSER(CG-91 OXY) OR ESAB (FR-18) OR GCE(FR-20T OXY) ONLY. NOTE:1) OFFERS OF OEMs OR THEIR AUTHORISED DEALERS ENCLOSING VALID AUTHORISED DEALERSHIP CERTIFICATE ONLY WILL BE CONSIDERED. 2) THE SUPPLIERS SHALL SEND TEST CERTIFICATE FROM GOVT. AUTHORISED TEST HOUSE. IN CASE OF INTERNATIONAL BRAND, THE TEST CERTIFICATE FROM REPUTED INSTITUTE LIKE BAM, GERMANY IS MANDATORY. 3) THE SUPPLIERS SHOULD HAVE EQUIPMENTS FOR TESTING OF FLASH BACK ARRESTORS AND CALIBRATION. THE PURCHASER HAS THE RIGHT TO INSPECT THESE INSTALLATIONS.
215	SR	42734 18-01-19	76216020	FLASH BACK ARRESTOR(DRY TYPE) FOR REGULATOR END OF OXYGEN LINES TO PREVENT FLASH BACKS IN OXY FUEL SYSTEM CONFORMING TO EN 730/ISO 5175-1/IS 11006 STANDARDS WITH FLAME ARRESTOR(FA) AND NON RETURN VALVE(NRV) AND THERMAL CUT OFF VALVE(TV) WORKING PRESSURE: 15 BAR. END CONNECTIONS G 3/8" RH TO EN 560/ISO 3253 STANDARDS. MAKE: MESSER(DGN OXY) OR ESAB(PROTEX RO) OR GCE(FR-34 R OXY) ONLY. NOTE:1) OFFERS OF OEMs OR THEIR AUTHORISED DEALERS ENCLOSING VALID AUTHORISED DEALERSHIP CERTIFICATE ONLY WILL BE CONSIDERED. 2) THE SUPPLIERS SHALL SEND TEST CERTIFICATE FROM GOVT. AUTHORISED TEST HOUSE. IN CASE OF INTERNATIONAL BRAND, THE TEST CERTIFICATE FROM REPUTED INSTITUTE LIKE BAM, GERMANY IS MANDATORY. 3) THE SUPPLIERS SHOULD HAVE EQUIPMENTS FOR TESTING OF FLASH BACK ARRESTORS AND CALIBRATION. THE PURCHASER HAS THE RIGHT TO INSPECT THESE INSTALLATIONS.

216	SR	42737 18-01-19	76216111	FLASH BACK ARRESTOR(DRY TYPE) FOR TORCH END OF ACETYLENE/LPG LINES TO PREVENT FLASH BACKS IN OXY FUEL SYSTEM CONFORMING TO EN 730/ISO 5175-1/IS 11006 STANDARDS WITH FLAME ARRESTOR(FA) AND NON RETURN VALVE(NRV) WORKING PRESSURE: 1.5 BAR FOR ACETYLENE/5.0 BAR FOR LPG. END CONNECTIONS G 3/8" LH TO EN 560/ISO 3253 STANDARDS. MAKE: MESSER(CG-91 FUEL) OR ESAB(FR-18) OR GCE(FR-20T FUEL) ONLY. NOTE:1) OFFERS OF OEMs OR THEIR AUTHORISED DEALERS ENCLOSING VALID AUTHORISED DEALERSHIP CERTIFICATE ONLY WILL BE CONSIDERED. 2) THE SUPPLIERS SHALL SEND TEST CERTIFICATE FROM GOVT. AUTHORISED TEST HOUSE. IN CASE OF INTERNATIONAL BRAND, THE TEST CERTIFICATE FROM REPUTED INSTITUTE LIKE BAM, GERMANY IS MANDATORY. 3) THE SUPPLIERS SHOULD HAVE EQUIPMENTS FOR TESTING OF FLASH BACK ARRESTORS AND CALIBRATION. THE PURCHASER HAS THE RIGHT TO INSPECT THESE INSTALLATIONS.
217	SR	42740 18-01-19	76216123	FLASH BACK ARRESTOR(DRY TYPE) FOR REGULATOR END OF ACETYLENE/LPG LINES TO PREVENT FLASH BACKS IN OXY FUEL SYSTEM CONFORMING TO EN 730/ISO 5175-1/IS 11006 STANDARDS WITH FLAME ARRESTOR(FA) AND NON RETURN VALVE(NRV) AND THERMAL CUT OFF VALVE(TV) WORKING PRESSURE: 1.5 BAR FOR ACETYLENE/5.0 BAR FOR LPG. END CONNECTIONS G 3/8" LH TO EN 560/ISO 3253 STANDARDS. MAKE: MESSER(DGN FUEL) OR ESAB(PROTEX RA) OR GCE(FR-34 R FUEL) ONLY. NOTE:1) OFFERS OF OEMs OR THEIR AUTHORISED DEALERS ENCLOSING VALID AUTHORISED DEALERSHIP CERTIFICATE ONLY WILL BE CONSIDERED. 2) THE SUPPLIERS SHALL SEND TEST CERTIFICATE FROM GOVT. AUTHORISED TEST HOUSE. IN CASE OF INTERNATIONAL BRAND, THE TEST CERTIFICATE FROM REPUTED INSTITUTE LIKE BAM, GERMANY IS MANDATORY. 3) THE SUPPLIERS SHOULD HAVE EQUIPMENTS FOR TESTING OF FLASH BACK ARRESTORS AND CALIBRATION. THE PURCHASER HAS THE RIGHT TO INSPECT THESE INSTALLATIONS.
218	SR	58304 17-06-19	56500361	Battery Charger 230V/24V 50 amps. As per RDSO Specn. No. IRS.S.86/2000 (Amndt.-4) or latest
219	SR	51130 01-04-19	75201320	FULLY NITRILE DIPPED COTTON GLOVES 10" DARK GREEN COLOUR WITH BLUE LINE EN 388 WITH CE APPROVED
220	SR	66630 06-09-19	75900105	PHENOLIC MOULDING POWDER BLACK NYLON FILLED TO Gr.PF2E2 OF IS: 1300 . FLOW RATE SHALL BE SUITABLE FOR BOTH COMPRESSION AND TRANSFER MOULDING. MOULD SHRINKAGE SHALL BE 0.010 TO 0.015 Cm/Cm. TEST CERTIFICATE FROM THE MANUFACTURER OR GOVERNMENT LABORATORY SHALL ACCOMPANY THE SUPPLY. SUPPLY SHALL BE MADE IN ORIGINAL PACKING OF THE MANUFACTURER.
221	SR	67374 13-09-19	56450242	SLUG COPPER TO DRG.No.QBT 05970 ALT-2 FOR QBAT RELAYS
222	SR	67377 13-09-19	56450266	SUPPORT BRACKET TO DRG.No.QCA 12970/2 OF 2 ALT-5 FOR PSECIAL TYPE RELAYS.
223	SR	67378 13-09-19	56900028	PURE IRON FLAT TO SIZE 4mm THICK (+/- 0.15mm) X 55MM WIDTH (+/- 0.5mm) X 900mm-1000mm LONG FOR QTA2 SHUNT.MATERIAL PROPERTIES: 1) HIGH PURITY IRON WITH LOW RESIDUAL ELEMENTS. 2) IMPURITIES MAX:- C=0.01% MIN=0.20%. S=0.015%, P=0.15%, 3)COLD ROLLED IN ANNEALED CONDIOIN. TEST CERTIFICATE FOR THE CHEMICAL COMPOSITION SHALL BE SUBMITTED ALONG WITH THE SUPPLY.
224	SR	67395 13-09-19	56450280	SPECIAL SCREW 4BA TO DRG.No.QSC 10970 ALT-3 FOR QT2, QTA2, QB3, QBAT AND QSPA1 RELAYS.
225	SR	67399 13-09-19	56450321	SPACER (PB) TO DRG.No.QCA 35971 ALT.3 FOR Q SERIES RELAYS.
226	SR	67400 13-09-19	56900030	THREADED END FOR LOCK ROD TO DRG. No. CWM 03105 (TO BE SUPPLIED WITHOUT DRILLING 8.2 mm DIA 2 HOLES AND WITHOUT ZINC PLATING)
227	SR	67404 13-09-19	56450310	SHUNT (SOFT MAGNETIC IRON) TO DRG. No.QBT 06970 ALT-2 FOR QBAT AND QNA1K RELAYS.
228	SR	69809 16-10-19	75203479	ECO- FRIENDLY OXO BIO-DEGRADABLE PLASTIC BAGS TO A SIZE OF HEIGHT 45 INCHES MINIMUM AND WIDTH 20 INCHES MINIMUM WITH A CARRYING CAPACITY OF 25 KG MINIMUM TO SPEC. ASTM D 5208 & ASTM D3826/ISO/IS 17088-2008-COLOUR- GREEN AND BLACK IN EQUAL QUANTIYT. (QUANTITY STRICTLY TO BE SUPPLIED IN NUMBERS ONLY AND NOT IN WEIGHT)
229	SR	103733 29-03-21	56300074	Cover Locking Hook Assembly to Drg. No. RDSO/S/10961 Alt-3 consisting of Locking Hook – S.10962 Alt-4 :- 1 No, Fixing Plate – S.10963 Alt-2 :- 1 No, Packing Piece – S.10964 Alt-2:- 1 No. and Fasteners as mentioned in drawing. HSN Code : 8608, Inspection : Consignee.
230	SR	103821 30-03-21	56300074	Cable Hole Cover to Drg.No. RDSO/S.10967 Alt-4 for Electric Point Machine. Components shall be painted with priming coat and a finish coat of smoke grey paint to IS: 123. HSN Code: 8608, Inspection: Consignee.
231	SR	103824 30-03-21	56300130	Cover Latch Pin with M8 Nut & B-8 Washer in set. Each set comprising of :- Cover Latch Pin to Drg. No. RDSO/S.10970 Alt-2 :- 1 No Nut MS Hex M8 to IS: 1363 Part-3 :- 1 No, Spring Washer B-8 to IS: 3063 :- 1 No. All items shall be Zinc plated and yellow passivated. Supply shall be made in assembled condition. HSN code : 8608, Inspection : Consignee
232	SR	103878 31-03-21	56300141	Eyelet Copper Tinned M5. Thickness (0.8mm ±0.06mm) and the tolerance for thickness to IS: 1987-2008. HSN Code: 8308, Inspection: Consignee.
233	SR	103902 31-03-21	56300153	Eyelet Copper Tinned M6. Thickness (0.8mm ±0.06mm) and the tolerance for thickness to IS: 1987-2008. HSN Code: 8308, Inspection: Consignee.
234	SR	104538 12-04-21	56500518	Finger Sheath in set, made out of Latex to IS: 13101. One set comprising of finger sheath for five fingers. The supply shall effected in quarterly phased manner.
235	SR	104547 12-04-21	56450760	Locking Collar to Drg.No. QNC 08971 Alt-1 for Q Series Relays
236	SR	104548 12-04-21	56010035	Aluminium Gongs in set for Bell Unit of DLB & TLB Instrument. Each set comprising of:- 1) Gong (sheep) to Drg.No.CWM 5/91 Part-1 :- 1 No. 2) Gong (flat) to Drg.No.CWM 5/91 Part-2 :- 1 No. Each item to be packed separately.
237	SR	104549 12-04-21	56010102	Aluminium Bracket and Lock Coil Mounting Bracket in set for DLB Instrument. Each set comprising of:- 1) Armature Bracket to Drg.No. WM 130/83 :- 1 No. 2) Lock Coil Mounting Bracket to Drg.No. WM 126/83 Alt-1 : - 1 No. Each item to be packed separately.
238	SR	104551 12-04-21	56010114	Aluminium Bracket to Drg.No. CWM SK.4/99 Alt-2 for Bell Unit of DLB & TLB Instrument. (Painting shall be as per Drawing)
239	SR	104552 12-04-21	56010126	Dial Plate Brass to Drg.no. WM 32/87 for DLB Instrument without painting. Note:- 57.50/57.30mm Dia Holes 2 Nos only to be provided in the Dial Plate and other holes shown in the drawing need not be drilled.

240	SR	104553 12-04-21	56010138	Dial Plate Anodised in set for DLB Instrument. One set consisting of:- 1) Dial Plate to Drg.No. WM 4/86/A Alt-3 :- 1 No. 2) Dial Plate to Drg.No. WM 4/86/B Alt-2 :- 1 No. Each item to be packed separately.
241	SR	104573 13-04-21	56010199	Plunger Rod & Plunger Head in set for DLB Instrument. Each set comprising of:- 1) Plunger Rod to Drg.No. WM 72/83 :- 1 No. 2) Plunger Head to Drg.No. WM 87/83 Alt-1 :- 1 No. Each set shall be packed separately.
242	SR	104579 13-04-21	56010163	Plunger Pin Stop and Plunger Rod Bush in set for DLB Instrument. Each set comprising of:- 1) Plunger Pin Stop to Drg.No. WM 185/83 Alt-1 :- 2 Nos 2) Plunger Rod Bush to Drg.No. WM 73/83 Alt-1 :- 1 No. Each item to be packed separately.
243	SR	104590 13-04-21	56010140	Ratchet to Drg.No. WM 82/83 Alt-1 for DLB Instrument.
244	SR	104594 13-04-21	56010345	Rubber Gasket in set for Polarised Relay. Each set consists of following items. 1. Rubber Gasket for Cover to WM 87/88 :- 1 No. per set 2. Rubber Washer for Glass to WM 86/88/1 Alt-2 :- 2 Nos per set 3. Rubber Washer for Coil to WM 86/88/2 Alt-2 :- 2 Nos per set 4. Rubber Washer for Pole Face WM 86/88/3 Alt-2 :- 6 Nos per set (1mm thick 2 /nos, 2mm thick 2 Nos and 3mm thick 2 Nos) Each set to be packed separately in polythene bags.
245	SR	104600 13-04-21	54900025	Lock Unit Spacer Pin to Drg.No. CWM 09597 Alt-1 for GRS Apparatus Case. HSN Code: 8608
246	SR	104605 13-04-21	54900130	Pad Lock Bracket to Drg.No. CWM 10097 for GRS Apparatus Cases. HSN Code: 8608, Inspection : Consignee
247	SR	104613 13-04-21	54900505	Nut Square MS M10 to Drg.No. CWM 01900 for GRS Apparatus Cases. HSN Code: 8608, Inspection : Consignee
248	SR	104617 13-04-21	54900499	Knob (MS) to Drg.No. CWM 010197 (Part) for GRS Apparatus Cases. HSN Code: 8608, Inspection : Consignee
249	SR	112403 19-08-21	76011811	Manual Metal Arc Welding Electrode, Class M-5, Type of coating -Heavy size 4mm (dia) x 350mm(length) to Spec IRS M 28/17, Code E18.8 MnR26 as per IS:5206/2003 - RDSO item. Class M-5, Type of coating-Heavy , size 4mm (dia) x 350mm (length) to Spec IRS M 28/17, Code E18.8MnR26 as per IS:5206/2003-RDSO item.
250	SR	113097 26-08-21	56300130	Lock Rod in sets for Point M/c-220mm stroke Point Machine. Each set comprising of 1) Lock Rod (RH) to Drg.No.RDSO/S.11006 Alt- PTJ-5 :- 1No 2) Lock Rod (LH) to drg.No.RDSO/S.11007 Alt- PTJ-5 :- 1No Each Lock Rod RH & LH shall be supplied with 2 Nos of Nut MS Hex M24x3mm pitch to IS:1364 part-3, 2 Nos of Lock Nut MS M24x3mm pitch to IS:1364 part-4, 2 Nos of Washer MS Punched M24 to IS:2016 Type-A and 2 Nos of Spring Washer B24 to IS:3063. All these fasteners are to be supplied in assembled condition and shall be Zinc plated to Grade Fe/Zn 25 to IS:1573 and yellow passivated to IS:1340. Ultrasonic testing to be conducted by the supplier on Lock rods to ensure the material is free from internal cracks/defects and for proof of this, test certificate from reputed testing labs shall be enclosed along with each supply. HSN Code : 8608 Inspection : RITES/Consignee
251	SR	113098 26-08-21	56300554	Power Transmission Assembly for 220mm Stroke Point Machine consisting of :- 1).Main Gear Assembly to Drg.No.CWM 01119 with Rack & Pinion to Drg.No.RDSO/S.11012 and Locking Pawl (Special) to Drg. No. RDSO/S.10838 Alt-6/PTJ : 1 No. 2).Drive Rod to Drg.No. RDSO/S.11003 Alt- 3/PTJ : 1 No. (Two items only) The load test for Power Transmission Assembly of 220 mm stroke Point Machine has to be carried out as per specification S.24/2002. HSN Code : 8608 Inspection : RITES
252	SR	113107 26-08-21	56304547	Cast Iron Components (Machined) in Set for 220mm stroke Point Machine. Each set comprising of following items in machined condition. 1) Bracket RH to Drg.No.RDSO.S.11004 Alt-5/ PTJ :- 1 No 2) Bracket LH to Drg.No.RDSO.S.11005 Alt-5/PTJ :- 1 No 3) Main Gear Bracket to Drg.No.RDSO/S.10845 Alt-6/PTJ with Bush (Cintered Bronze) to Drg.No.RDSO/S.10846 Alt-3 in assembled condition :-2Nos 4) Gear Box Bracket to Drg.No.RDSO/S.10869 Alt-9/PTJ with Bush (Cintered Bronze) to Drg.No.RDSO/S.10868 Alt-3 In assembled condition :- 1 No 5) Detector Rod Bracket to Drg.No.RDSO/S.10812 Alt-10/PT J :- 2 Nos (Total three items only) HSN Code : 8608 Inspection : RITES
253	SR	113109 26-08-21	56300499	Base (Cast Iron Machined) to Drg.No.RDSO/S.11001 Alt-7/PTJ for 220mm stroke Point Machine. HSN Code : 8608 Inspection : RITES
254	SR	113113 26-08-21	56300190	Detector Rod LH & RH for 220mm stroke point M/c in set. One set consists of :- 1. Detector Rod LH to Drg. No.RDSO.S.11010 Alt-2 : 1 No. 2. Detector Rod RH to Drg.No.RDSO.S.11011 Alt-2 : 1 No Each Detector Rod RH & LH shall be supplied with 2 Nos of Nut MS Hex M20x2.5mm pitch to IS:1364 part-3, 2 Nos of Lock Nut MS M20x2.5mm pitch to IS:1364 part-4, 2 Nos of Washer MS Punched M20 to IS:2016 Type-A and 2 Nos of Spring Washer B20 to IS:3063. All these fasteners are to be supplied in assembled condition and shall be Zinc plated to Grade Fe/Zn 25 to IS:1573 and yellow passivated to IS:1340. HSN Code : 8608 Inspection : RITES/Consignee
255	SR	113118 26-08-21	56300300	Components for Clamp Type Ground Connection for Point Machine 220mm Stroke. Consists of :- 1.Clamp Point Lock 60kg (TWS) for B.G to Drg.No. RDSO/S3395A- Alt-1 : 1 Set. 2.Drive rod to Drg.No. RDSO.S.3460 Alt- PTJ-1 : 1 No 3.Drive rod lug to Drg.No RDSO.S.3461 Alt- PTJ-4 : 1 No 4.Drop lug to Drg.No RDSO.S.3598 Alt-1 : 4 Nos 5.Switch Extension Bracket to Drg.No RDSO.S.3591, Alt-PTJ-1 : 2Nos 6.Bush to Drg.No RDSO.S.3463 : 1 No 7.Insulating Plate (RH) to Drg.No RDSO.S.3592 : 1 No 8.Insulating Plate (LH) to Drg.No RDSO.S.3593 : 1 No 9.Insulating Bush for Detector rod drop lug to Drg.No CWM 02120 : 2 Nos 10.Insulating Bush for Lock rod drop lug to Drg.No CWM 02220 :2 Nos 11. Insulating Washer to Drg.No S.8640 :8 Nos 12. Pin complete to Drg No. CWM 02320 :1 No HSN Code : 8608 Inspection : RITES/Consignee
256	SR	113123 26-08-21	56301560	Slide Cover for 220mm stroke Point machine in set. One set consists of :- 1. Slide cover to Drg.No.RDSO.S.10848 A Alt, PTJ-4 :2 Nos. 2. Slide cover to Drg.No.RDSO.S.10848 B Alt, PTJ-5 :2 Nos. (Two Items only) HSN Code : 8608 Inspection : RITES/Consignee
257	SR	113136 26-08-21	56301558	Aluminium Cover Plate in Set for Electric Point Machine 220mm stroke. One sets consists of 1) Alu.Cover plate for Drive rod to Drg.No.RDSO.S.11013 :- 2Nos 2) Alu.Cover plate for Detector rod to Drg.No.RDSO. S.10813 Alt-2 :- 2 Nos 3) Alu.Cover plate for Lock rod to Drg.No.RDSO.S.10809-A Alt, PTJ-3 :- 2 Nos (Total three items only, Each set to be packed in a separate cover) HSN Code : 8608 Inspection : CONSIGNEE/RITES
258	SR	113147 26-08-21	56300797	Rubber Gasket in Set for Electric Point Machine 220mm stroke. One sets consists of 1) Rubber Gasket for Drive rod to Drg.No.RDSO.S.11014 :- 2Nos 2) Rubber Gasket for Detector rod to Drg.No.RDSO.S.10814 Alt-6 :- 2 Nos 3) Rubber Gasket for Lock rod to Drg.No.RDSO.S.10809-B, Alt-5 PTJ :- 2 Nos 4) Rubber Gasket for Cable hole cover to Drg.No.RDSO.S.10968 Alt-4 :- 2 Nos (Total Four items only, Each set to be packed in a separate cover)) HSN Code : 4001 Inspection : CONSIGNEE/RITES
259	SR	125832 16-02-22	76115604	FLUX CORED MIG/MAG WELDING FILLER WIRE WITH SHIELDED GAS. CLASS IV SPECN IRS M-46-20 WITH AMENDMENT -1 GRADE AS PER AWS A5. 29-10 GRADE E81Ti-W2C SIZE1.2MM IN SPOOL OF 12.5 KGS EACH. MAKE AS PER RDSO APPROVED VENDOR LIST.

260	SR	129093 07-04-22	76019925	MANUAL METAL ARC WELDING ELECTRODE, IRS CLASS-M2 (STAINLESS STEEL) SIZE:- 4 MM X 350 MM.LONG TO SPECIFICATION NO. IRS-M-28-2020, TABLE1
261	SR	114975 24-09-21	75101099	BELLOW DUCT ASSEMBLY COMPLETE WITH METALLIC FRAMES, PROVIDED WITH FIRE RETARDANT EPDM GASKETS ON BOTH SIDES, 2 NOS EACH FOR FRESH AIR AND RETURN AIR AND 1 NO FOR SUPPLY AIR PER RMPU, MADE OF ARAMID/PARA ARAMID FABRIC WITH SILICON RUBBER COATING ON BOTH SIDES TO RDSO SPECN. NO: RDSO/PE/SPEC/AC/0197- 2020 (REV 0) FOR RMPU FOR LHB EOG/HOG TYPE AC COACHES AS PER DRAWING NO:RDSO/PE/SK0069-2004 (REV.3)
262	SR	114092 13-09-21	75101210	Bellow Duct Assembly complete with metallic frames, provided with Fire retardant EPDM gaskets on both sides, 2 Nos. each for Fresh Air & Return Air and One No. for Supply Air per RMPU, made of Meta Aramid /Para Aramid Fabric with Silicon Rubber Coating on both Sides to RDSO Specification No. RDSO/PE/SPEC/AC/0197 -2020 (Rev.0) for RMPU for LHB EOG/HOG type AC Coaches as per drawing No. RDSO/PE/SK/0069-2004 (Rev.3)
263	SR	145981 14-11-22	75326322	DENSIFIED THERMAL BONDED POLYESTER BLOCK CUSHION FOR TRANSVERSE LOWER BERTH OF LHB COACHES TO SIZE 1814X595X50MM TO ITEM NO: 6 OF RCF DRG NO: LS61177 ALT - NIL AND TO SPECIFICATION RDSO SPEC NO: C-K607 REV 2 OF DEC 2015 AMD NO: 1 OF AUG 2016.
264	SR	145982 14-11-22	75320848	DENSIFIED THERMAL BONDED POLYESTER BLOCK CUSHION FOR TRANSVERSE MIDDLE BERTH OF LHB COACHES TO SIZE 1794 X 601 X 38 MM TO ITEM NO: 6 OF RCF DRG NO: LS61184 ALT- NIL AND TO SPECIFICATION RDSO SPEC NO. C-K607 REV.2 OF DEC 2015 AND 1 OF AUG 2016
265	SR	144691 02-11-22	75030093	RUBBER HOSE FOR S-TRAP ARRANGEMENT TO RDSO DRAWING NO.CG16008 ITEM 4, ALT.2 NOMINAL DIA (BORE) 70 MM, TYPE B, LENGTH 375 MM WITH ONE SIDE END TAPERED TO NOMINAL DIA 45 MM COLOUR BLACK, MATERIAL AS PER IS:14933- 2001 RA 2020 TYPE B WITH LATEST AMENDMENT
266	SR	148689 09-12-22	76218934	Solid MIG/MAG Welding Filler wire - 1.2mm dia., Class – IV to IRS: M-46/13 with amendment no 1, Grade ER80S-G as per AWS: A 5.28-10. Shelf life: 9months from the date of receipt in stores or 12months from the date of manufacture whichever is more.
267	SR	138862 17-08-22	76114030	SOLID MIG/MAG WELDING FILLER WIRE 1.2 MM DIA, CLASS-IV TO SPEC: IRS:- M-46/20, GRADE ER80S-G & AS PER IS/AWS SPEC:AWS A5.28/A5.28M: 2020.
268	SR	153753 10-02-23	75324337	Neoprene Rubber sheets width 1 meter (one meter) x thickness 1.5mm, running length as per CLW Specification No.CLW/ES/R-24/D Spec:
269	SR	189557 14-06-24	75321026	DENSIFIED THERMAL BONDED POLYESTER BLOCK CUSHION (DTBPB) FOR LGS,GS COACHES FOUR SEATER (LONG SEAT) OF SIZE 40 X 562 X 1897 MM TO ITEM NO: 2 OF ICF DRAWING NO: ICF/SK 3-6-1- 098. MATERIAL SPECIFICATION TO RDSO SPEC. NO.CK- 607, REV.2 OF DEC.2015
270	SR	189554 14-06-24	75327314	DENSIFIED THERMAL BONDED POLYESTER BLOCK CUSHION (DTBPB) FOR LGS,GS COACHES FOUR SEATER BACK REST (LONG BACK REST) OF SIZE 25 X 562 X 1912 MM TO ITEM NO: 3 OF ICF DRAWING NO: ICF/SK 3-6-1-098. MATERIAL SPECIFICATION TO RDSO SPEC. NO.CK- 607, REV.2 OF DEC.2015
271	SR	189853 18-06-24	56790119	MS cabinet with required fasteners and nylon bush in assembled condition for CR test kit in set. One set consists of :- 1.Cabinet to Drg.No. CWM 03616 Alt-2, 2.Front Panel to Drg.No.CWM 03716 Alt-3, 3.Back Plate toDrg.No. CWM 03816 Alt-1, 4.Name Plate to Drg.No. CWM 03916. 5.Base to Drg.no. CWM 00519 Alt-1 Sample to be approved before commencement of bulk supply.
272	SR	190031 20-06-24	56790120	Components for Track Feed Battery Charger in set. One set consists of:- 1.M.S. Cabinet and Fasteners for Track Feed Battery Charger to RDSO Specification No:IRS S.89/2013 version 1.0 or latest with list of items in set as per the enclosed annexure-1. 2.Transformor and Choke for track Feed Battery Charger to RDSO specification No: IRS S.89/2013 version 1.0 in sets to specifications as per the enclosed annexure-2. One set consists of :- (i). Toroidal core Transformer - 1 No. (ii). Choke - 1 No. (Two items only) 3.Electronic Components and Accessories for Track Feed Battery Charger to RDSO Specification No.IRS S 89/2013 version 1.0 or latest in set as per the enclosed annexure-3. (Total Three items only).
273	SR	208537 05-02-25	56300335	Motor DC Series wound, Rated voltage-110V, 0.59HP, 1700 RPM, Max.Current 5.3Amps, 10 Minutes Rating to Specification IRS.S-37/82, IRS.S-23 & S-24 with Gear Box Complete to Drg.No.RDSO.S-10910 Alt-6/PTJ and RDSO.S-10850 Alt-3 respectively. (with 400V AC immunity & IP 67 protection.) (To be procured only from RDSO approved Sources with RDSO Inspection).
274	SR	210706 01-03-25	56790132	Electrical / Electronic Components, Digital Micro Ohm meter, Volt meter & Transformers in set for CR Test Kit for Q Relay as per the enclosed Annexure. Set consists of 1. Electrical / Electronic components listed page No.5 of annexure attached. 2. Digital Micro Ohm meter & Volt meter listed page No.1 of annexure attached. 3. Set of transformers for CR test kit listed page No.3 of annexure attached.
275	SCR	4766 18-04-17	56151433	2 Volts, 200 AH sealed maintenance free valve regulated lead acid stationary cells (MF-VRLA) batter as per RDSO Specn. IRS:S:93/96A with amendment 1 or latest confirming to voltage 48V-200AH @ 10hr. rate fully charged complete with accessories. Shelf Life = 4 years (One Set = 24 Nos.)
276	SCR	4768 18-04-17	56151410	48V-200 AH Valve regulated (Sealed) Lead Acid Stationary Battery to RDSO Specn. IRS:S/93/96/(A) (2 Volts x 24 Nos = 48 Volts)
277	SCR	11104 11-10-17	76300031	Manual Blow Pipe for cutting as per the following details. Type of Blow Pipe: Cutting Blow pipe for Fuel gas: Bharat metal cutting gas (LPG with additives) For Oxidizing Gas: Oxygen gas. Pressure, High pressure. Manual Blow Pipe should be complete with shank mixer, swaged tips of various sizes to cover cutting mild steel up to 50 mm, with a set of two nozzles for cutting MS in thickness range of 1-25mm- 1 No. and 25-50mm -1 No and two sets of hose coupling and nipples for 10 mm hose and complete assembly Packed in card board box and confirming to IS: 7653.
278	SCR	11151 12-10-17	56507586	Terminal Block One Way 60mm make of PBT as per Specification.NO.IRS-S-75/2006 (Rev.2) and as per Drawing.No.SA-23745(Alt-5).
279	SCR	11978 26-10-17	75500012	Door mats synthetic type blue/green of size 750mmx1460mm. Make: DUROTURF, ASTROTURF OR ULTIMATE. Spec. No. 1) Material: Synthetic Resin, 2) Under Lay: Latex budding (Anti Skid), 3) Flower bud per sq. inch: 6 nos. (Approx.) +/-5%, 4) No. of leaves per sq. inch: 48 nos. (Approx.) +/-10%, 5) No. of leaves per each bud: 8 nos. 6) Pile height: 14mm (+/- 2mm) width, 7) Both sides PVC heading.
280	SCR	11979 26-10-17	76300031	Manual Blow Pipe for cutting as per the following details. Type of Blow Pipe: Cutting Blow pipe for Fuel gas: Bharat metal cutting gas (LPG with additives) For Oxidizing Gas: Oxygen gas. Pressure, High pressure. Manual Blow Pipe should be complete with shank mixer, swaged tips of various sizes to cover cutting mild steel up to 50 mm, with a set of two nozzles for cutting MS in thickness range of 1-25mm-1 No. and 25-50mm -1 No and two sets of hose coupling and nipples for 10 mm hose and complete assembly Packed in card board box. And confirming to IS: 7653.
281	SCR	14111 08-12-17	76100030	Steel Wire 1.2 mm in spool of weight approx 15 kgs. Spec. No. EN.440-G3SII & PrEN-759 RCF PL. No. 76985635

282	SCR	52987 15-04-19	76210200	Hand torch T 45 V (For Hypertherm make air plasma cutting machine: Model : Powermax 45) part no. : 088008; size 06 Meters To be procured from Hypertherm (or) Authorised dealers with Hypertherm test certificate. This is used POH of BCNHL wagons and general purposes
283	SCR	87399 17-06-20	76014204	Manual metal arc welding electrodes of size 4x350mm, class M2, type heavy coating Specn-IRS M-28/12, Specn 5206 and IS/code E 19.9LR26.
284	SCR	87402 17-06-20	76300067	SHIELD (For Hypertherm make air plasma cutting machine: Model : Powermax 45) part no. : 220674. To be procured from Hypertherm (or) Authorised dealers with Hypertherm test certificate. (PAC item)
285	SCR	87404 17-06-20	76300018	NOZLES (For Hypertherm make air plasma cutting machine: Model : Powermax 45) part no. : 220671. To be procured from Hypertherm (or) Authorised dealers with Hypertherm test certificate. (PAC item)
286	SCR	87407 17-06-20	76300055	ELECTRODES (For Hypertherm make air plasma cutting machine: Model : Powermax 45) part no. : 220669. To be procured from Hypertherm (or) Authorised dealers with Hypertherm test certificate. (PAC item)
287	SCR	128225 23-03-22	56300554	Power Transmission assembly for 220mm Point Machine
288	SCR	128235 23-03-22	56301601	D.C. Motor with box for IRS point machine 143 & 220mm
289	SCR	128234 23-03-22	56506089	Clamp lock arrangement as per drg.No.RDSO/S:3395A and S: 3454 Alt "A" Ver.1 with latest Amndt. For electric point machine 220 for operating thick web switches.
290	SCR	128943 05-04-22	56300062	Semi assembled 143mm point machine as per enclosed detailed description consisting of (1) BASE (cast iron machined and painted)-01 No. RD (2) cast iron brackets (machined and painted) (main gear BKT, Detector rod BKT, gear box BKT and BKT LH/RH)-01 Set. (3) contactor unit assembly-01 No. (4) lock rod LH and RH with nut and washers-01Set. (5) detector rod LH and RH with nut and washers-01Set. (6) cover assembly, key box assembly and oil felt arrangement 01 Set (7) slide cover compete (04 Nos./Set)-01 Set. (8) aluminum cover plate in set-01 set (9) rubber gasket in set (6 Nos./Set)-01Set. (10) 1 way terminal (IRS:S-75/2006(Rev. 2) Drg.no.SA-23741A-16 Nos. with wiring, lacing, sleeving, ferruling and terminated with copper lugs.) (11) crank handle- 01 No. to Drg.No.RDSO/S 10973 A-E all of the above components shall be assembled using required fasteners as per point machine assembly to Drg. No. RDSO/S.10800 Alt 6 or latest. The above material shall be supplied as per the revised/latest Drawing issued by RDSO.
291	SCR	128944 05-04-22	56304547	Supply of following items for 220mm point machine (components) as per drawing. 1. Base RDSO/S/11001 (or) latest. 2. Bracket RH-RDSO/S/11004 (or) latest. 3. Bracket LH-RDSO/S/11005 (or) latest. 4. Detector rod bracket - RDSO/S/10812 (or) latest. 5. Main gear bracket- RDSO/S/10845 Alt-2 (or) latest. 6. Gear box bracket- RDSO/S/10869 Alt-3 (or) latest. 7. Lock rod RH- RDSO/S/11006 (or) latest. 8. Lock rod L.H.- RDSO/S/11007 (or) latest. 9. Detector rod L.H.- RDSO/S/11010 (or) latest. 10. Detector rod R.H.- RDSO/S/11010 (or) latest. 11. Cover plate - RDSO/S/11013 (or) latest. 12. Cover plate- RDSO/S/10813 Alt-2 (or) latest. 13. Cover plate- RDSO/S/10809A Alt-1 (or) latest. 14. Slide cover complete - RDSO/S/10848A Alt-4 (or) latest. 15. Slide cover complete - RDSO/S/10848B Alt-2 (or) latest. 16. Cover assembly - RDSO/S/10865 Alt-2 (or) latest. 17. Key box assembly - RDSO/S/10880Alt-2 (or) latest. 18. Oil felt arrangement - RDSO/S/10956 (or) latest. 19. Rubber gasket - RDSO/S/11014 (or) latest. 20. Rubber gasket - RDSO/S/10814 Alt-4 (or) latest. 21. Rubber gasket - RDSO/S/10809B Alt-1 (or) latest. 22. Contact unit assembly - RDSO/S/10911 Alt-2 (or) latest. 23. Crank handle-01 No. to Drg.No. - RDSO/S/10973 A-E (or) latest. 24. 1 way terminals (IRS:S-75/2006 (Rev.2) Drg.no.SA-23741/A or latest – 16 Nos. with wiring, lacing, sleeving, ferruling and terminated with copper lugs, Fasteners shall be supplied as per the requirement of this drawings for assembling.)
292	SCR	128966 06-04-22	56300529	Power Transmission assembly for electric point machine 143mm as per drg.no RDSO S-10835 with drive rod drg.no. RDSO S-10803 TO RDSO Specification No.IRS S:24/2002 or latest version .
293	SCR	140403 06-09-22	76050040	Manual metal arc welding electrode of size 4X450mm class A3 conforming to specification No. IRSM-28/20 code as per IS:814-2004 & AWS code as per EB5326H2X. Type of coating: Heavy
294	SCR	142798 17-10-22	75614467	PV Expansion Flat moulding of size 32X3X2000 mm length to Drg. No. PD/TPYS/SCR/C&W-143, item No.1, Note: colour of the mouldings to be light blue
295	SCR	143276 20-10-22	75909716	PV Expansion angle moulding of size 32X32X2.5X2000 mm length to Drg. No. PD/TPYS/SCR/C&W-143, item No.3, Note: colour of the mouldings to be light blue
296	SCR	143280 20-10-22	75909777	PV Expansion Flat moulding of size 50X3X1900 mm length to Drg. No. PD/TPYS/SCR/C&W-143, item No.2, Note: colour of the mouldings to be light blue
297	SCR	153560 08-02-23	76216020	FLASH ARRESTOR (DRY TYPE) FOR REGULATOR END OXYGEN LINES TO PREVENT FLASH BACK IN OXY FUEL SYSTEM CONFORMING TO EN 730/ISO 5175-1/15 11006 STANDARDS WITH FLAME ARRESTOR(FA) AND NON RETURN VALVE(NRV) AND THERMAL CUT OFF VALVE(TV) WORKING PRESSURE 15 BAR END CONNECTION G 3/8" RH TO EN 560/ISO 3253 STANDARDS MAKE MESSER (DGN OXY) OR GCE(FR-34 R OXY) OR WITT (OXYGEN RF53N ONLY NOTE: 1) OFFERS ON OEMS OR THEIR AUTHORISED DEALERS ENCLOSING VALIED AUTHORISED DELERSHIP CLARIFICATION ON WILL BE CONSIDERED. 2) THE SUPPLIERS SHALL SEND TEST CERTIFICATION FROM GOVT. AUTHERISED TEST HOUSE IN CASE OF IN IN CASE OF INTERNTIONAL BRAND THE TEST CERTIFICATE FROM REPUTED INSTITUE LIKE BAM GERMANY IS MANDATORY. 3) THE SUPLIER SHOULD HAVE EQUIPMENT FOR TESTING OF FLASH BACK ARRESTORS AND CALIBRATION. THE PURCHASER HAS THE RIGHT TO INSPECT THESE INSTALLATIONS. SPEC: EN 730/ISO 5175-1/15 11006
298	SCR	157644 04-04-23	76216111	Flash back arrestor (Dry type) for Torch end of acetylene/LPG lines to prevent flash backs in Oxy fuel system conforming to EN 730/ISO 5175-1/IS 11006 standards with flame arrestor (FA) and non return valve (NRV) working pressure: 1.5 BAR for Acetylene/5.0 BAR for LPG End connections G 3/8" LH to EN 560/ISO 3253 standards. Make: MESSER (CG-91 FUEL) or ESAB (FR-18) or GCE(FR-20T FUEL) or WITT (LPG E460-3) only. Note: 1) Offers of OEMs or their authorised dealers enclosing valid authorised dealership certificate only will be considered. 2) The suppliers shall send test certificate from Govt. Authorised test house. in case of international brand, the test certificate from reputed institute like BAM, Germany is mandatory. 3) The suppliers should have equipments for testing of flash back arrestors and calibration. The purchaser has the right to inspect these installations. Specn: EN 730/ISO 5175-1/IS 11006

299	SCR	157645 04-04-23	76216135	Flash back arrestor (Dry type) for Torch end of Oxygen lines to prevent flash backs in Oxy fuel system conforming to EN 730/ISO 5175-1/IS 11006 standards with flame arrestor (FA) and non return valve (NRV) working pressure: 15 BAR End connections G 3/8" RH to EN 560/ISO 3253 standards. Make: MESSER (CG-91 OXY) or ESAB (FR-18) or GCE(FR-20T OXY) or WITT (OXYGEN E460-3) only. Note: 1) Offers of OEMs or their authorised dealers enclosing valid authorised dealership certificate only will be considered. 2) The suppliers shall send test certificate from Govt. Authorised test house. in case of international brand, the test certificate from reputed institute like BAM, Germany is mandatory. 3) The suppliers should have equipments for testing of flash back arrestors and calibration. The purchaser has the right to inspect these installations. Specn: EN 730/ISO 5175-1/IS 11006
300	SCR	157658 04-04-23	76014060	Manual Metal Arc Welding Electrodes Size 3.15 x 350mm, Class M4, Type of Coating: Heavy conforming to IRS M: 28-2020 Code as per IS: 5206-2013
301	SCR	158813 21-04-23	76216123	Flash back arrestor (Dry type) for regulator end of acetylene/LPG lines to prevent flash backs in Oxy fuel system conforming to EN 730/ISO 5175-1/IS 11006 standards with flame arrestor (FA) and non return valve (NRV) and Thermal cut off valve (TV) working pressure: 1.5 BAR for Acetylene/5.0 BAR for LPG End connections G 3/8" LH to EN 560/ISO 3253 standards. Make: MESSER (DGN FUEL) or ESAB (PROTEX RA) or GCE(FR-34 R FUEL) or WITT (LPG RF53N) only. Note: 1) Offers of OEMs or their authorised dealers enclosing valid authorised dealership certificate only will be considered. 2) The suppliers shall send test certificate from Govt. Authorised test house. in case of international brand, the test certificate from reputed institute like BAM, Germany is mandatory. 3) The suppliers should have equipments for testing of flash back arrestors and calibration. The purchaser has the right to inspect these installations. Specn: EN 730/ISO 5175-1/IS 11006
302	SCR	151969 23-01-23	75905000	Clear White Accrylic Sheet of size : Length : 1200 mm x Breadth : 900 mm x Thickness : 3 mm.
303	SCR	162546 14-06-23	54900530	EOLB COMPONENT consists of (A) All Gear Drive Mechanism for Electric Lifting Barrier to Drg.No. S&T/MFT/6000/ADV1 (drg. attached) with crank handle or latest amendments or with LATEST AMENDMENTS 1NO (B) Motorized Boom Lock for Electrically operated lifting barrier [lock consisting of 24V D.C.Motor], speed reduction unit with 3 [three] limit switches, counterweight limit switch-01 No. and enclosure Drg.No.S&T/MFT/4711/Adv 2 or with LATEST AMENDMENTS - 1NO (C) CIRCUIT CONTROLLER FOR ELECTRIC LIFTING BARRIER TO Drg NO : S&T/MFT/6046 TO 6065 or with LATEST AMENDMENTS - 1NO
304	SCR	162562 14-06-23	54220014	STOP BOARD OF SIZE 600MM DIAMETER MADE OUT OF 1MM THICK GI SHEET WITHHIGH INTENSIVE PRISMATIC RETRO REFLECTIVE SHEET AND BACKGROUND RED COLOUR ANDLETTERS IN THREE LANGUAGES ENGLISH, HINDI & TELUGU OF COLOUR WHITE AS PER THERAILWAY STANDARDS WITH MINIMUM REFLECTIVITY DISTANCE OF 250 MTRS WITH ALL NECESSARYFIXING CLAMPS, BOLTS AND NUTS TO SUIT FOR ELECTRIC LIFTING BARRIER AS PER DRG.No. S&T/MFT/6077.ADV.1 or Latest Ammendment
305	SCR	162564 14-06-23	54220038	1 IN 2 OUT 4 sq. mm TERMINAL BLOCKS Make: Wago 280-681 or Phoenix ST 4 - TWIN or Similar brand and part no
306	SCR	162566 14-06-23	54221456	BOOM ASSEMBLY AS PER DRG. No. RDSO/S/11600 WITH LASTEST AMMENDMENTS.
307	SCR	162567 14-06-23	54900566	OPERATING PANEL FOR Electrically Operated Lifting Barrier as per Drg. No. S&T/MFT/4707/1/ADV 1 along with top plate to Drg . No. S&T/MFT/4707/2/ADV 2 OR WITH LATEST AMMENDMENTS
308	SCR	162569 14-06-23	54220040	Thumb Switch 2 No-2nc [2no-2no's, 2nc-2 No's] 10 Amps Of Colour Black. Make: Recom Or Elcom Or Jai Balaji Or Salzer Or Elmax Or Kaycee , Only
309	SCR	162574 14-06-23	54252398	Key Lock('E' Type) for sliding boom type LC gate Drg No:S&T/MFT/3300A (Key Combinations (Drawing no: S3378A1/M-A31/M). Key Lock ('E' Type) for sliding boom type LC gate Drg No:S&T/MFT/3300B) (Key Combinations (Drawing no:S3378A1/M-A31/M) Qty & Key Combinations: As per Annexure Enclosed
310	SCR	162580 14-06-23	56460569	Light Unit Lense Ring as per RDSO Drawing No:S23025/M or Latest for CLS Signal.
311	SCR	162582 14-06-23	56130077	Name Plates & Circuit diagrams for Point machine 220mm a)As per Drg No:CWM/S&T/MFT/9005 Size Qty: 01 No, 150X130X0.9mm b)As per Drg No:CWM/S&T/MFT/9008 Size 80X42X0.9mm Qty:01 No, c)As per Drg No:CWM/S&T/MFT/9007 Size 85X66X0.9mm Qty:01 No.
312	SCR	162596 14-06-23	56790030	CELL SELECTOR SWITCH 1P/4WAY-16AMPS
313	SCR	162599 14-06-23	56790090	BATTERY TERMINALS Consists of BTI-30 RED-1 no,BTI-30 Black -01 no
314	SCR	162603 14-06-23	56501717	Electrolyte Capacitor -47000 Micro Farad/16 Volts with Holder
315	SCR	162611 14-06-23	56130030	BELL UNIT ASSEMBLY FOR DLBI
316	SCR	162627 15-06-23	56014156	NEEDLE INDICATOR ASSEMBLY TO DRG.NO.WM/93/83 COMPRISING OF 14 PART DRAWINGS MENTIONED IN THE ASSEMBLY DRAWING.
317	SCR	162629 15-06-23	56060087	Deflector Plate Locking Clamp (Top) to Drg No:- S&T/MFT/7062
318	SCR	162631 15-06-23	56060180	Deflector Plate Locking Clamp (Bottom)To Drg No:- S&T/MFT/7063
319	SCR	162633 15-06-23	56060210	Deflector Plate of axle Counter (RHS) & (LHS) To Drg No's S&T/MFT/7060 & S&T/MFT/7061
320	SCR	162637 15-06-23	56110157	GI flat of size 25x3x950 mm along GI nut/bolts of size 8X25mm with two flat and One spring washer of 23 sets & GI nut/bolts of size 12X40 mm with two flat and spring washer of 2 sets
321	SCR	162639 15-06-23	56030010	Box particulars Al sheet-Engraved(Powder coated yellow colour)-300*400mm
322	SCR	162644 15-06-23	56450175	Relay, AC immune, plug in type style QNA1,DC neutral line, 24V,8F,8B with plug board retaining clip and connectors
323	SCR	162645 15-06-23	56500142	Relay, AC Immune, plug-in-type, Style QNA1K, DC Neutral line, 24V, 1000 ohms 6F.6B with plug board, retaining clip & connectors
324	SCR	162646 15-06-23	56450850	Relay plug in type - Style QECX 61 (AC LED All aspects) 4F-4B with plug board retaining clip and connectors
325	SCR	162649 15-06-23	56115581	PVC insulated single core wire coils of size 28/0.3 No./mm multi strand flexible copper Conductor; Color: Black

326	SCR	162651 15-06-23	56117929	PVC insulated single core wire coils of size 28/0.3 No./mm multi strand flexible copper Conductor.Color: Red
327	SCR	162652 15-06-23	56112087	PVC Insulated wire copper conductor 16/0.2mm.Supply in two colors Red = 50% & Black = 50%
328	SCR	162554 14-06-23	56060348	PMDC MOTOR TO DRG No . S&T/MFT/4702/ADV.1 WITH MOUNTING BASE TO DRG.No. S&T/MFT/4702/1 conditions:(1) Type of enclosure: Totally enclosed (strong metallic weather proof case, the case of which shall be equipped with suitable fastening and when opened shall permit access to terminals, commutators & brushes) (2) The mounting base shall suit to pedestal assembly OR WITH LATEST AMMENDMENTS
329	SCR	162555 14-06-23	56060350	Counter weight for electric lifting barrier to Drg No. S&T/MFT/4635 ADV or with latest ammendments
330	SCR	162556 14-06-23	56080037	PRECISION LIMIT SWITCH WITH TOP PUSH ROLLER, 2 NO+2NC (ASSEMBLED IN LINE WITH CONTACT BLOCK). SWITCH HAVING EXPECTED LIFE OF ATLEAST 10X1000000 OPERATIONS. MAKE: JAI BALAJI OR RECOM OR SWITRON OR KAYCEE ONLY
331	SCR	162568 14-06-23	54220087	PUSH BUTTON SWITCH 2 NO-2NC CONTACTS 22.5 MM DIA [NO-2No'S. NC- 2No'S] RATING 10Amps. COLOUR:Green = 1 No; Yellow = 1 No; Red = 1 No. MAKE:Schneider OR Jai Balaji OR Switron only.
332	SCR	162572 14-06-23	54220099	Universal Point Rodding Consists set of 5 items mentioed below a) Lock Rod far End for CGL/IRS 52 Kgs one piece Rodding with solid jaw Drg No:S&T/MFT/7024/ADV.1 or Latest, material should be as per drawing confirm to Steel Class-1, IS 1875/1992 or Latest assembled With M.S.Square head Pin as per drg No. SA 54 A/M (ADV). Material Should be Confirm to RDSO SPN IRS S5-62.- each 01 NO b) Lock Rod Near End for CGL/IRS 52 Kgs one piece Rodding with solid jaw Drg No:S&T/MFT/7025/ADV 1 or Latest, material should be as per drawing confirm to Steel Class-1, IS 1875/1992 or Latest assembled With M.S.Square head Pin as per drg No. SA 54 A/M (ADV). Material Should be Confirm to RDSO SPN IRS S5-62- each 01 NO c) Detector Rod Far End for CGL/IRS 52 Kgs one piece Rodding with solid jaw Drg No:S&T/MFT/7022/ADV.1 or Latest, material should be as per drawing confirm to Steel Class-1, IS 1875/1992 or Latest assembled With M.S. Square head Pin as per drg No. SA 54 A/M (ADV). Material Should be Confirm to RDSO SPN IRS S5-62.- each 01 NO d) Detector Rod Near End for CGL/IRS 52 Kgs one piece Rodding with solid jaw Drg No: S&T/MFT/7023/ADV.1 or Latest, material should be as per drawing confirm to Steel Class-1, IS 1875/1992 or Latest assembled With M.S.Square head Pin as per drg No. SA 54 A/M (ADV). Material Should be Confirm to RDSO SPN IRS S5-62 - each 01 NO e) Drive rod for CGL/IRS 52 Kgs one piece Rodding with solid jaw Drg No:S&T/MFT/7026/ADV.1, material should be as per drawing confirm to Steel Class-1, IS 1875/1992 or Latest assembled With M.S.Square head Pin as per drg No. SA 54 A/M (ADV) or Latest. Material Should be Confirm to RDSO SPN IRS S5-62 – each 01 No.
333	SCR	162577 14-06-23	56460053	SIGNAL,COLOUR LIGHT-MOUNTING SOCKET (140mm.Ø.DIA) - Drg.No:RDSO:S 23005/M. or Latest
334	SCR	162579 14-06-23	56440078	Route Indicator Base as per Drg.No.S&T/MFT/4632
335	SCR	162581 14-06-23	56460065	Light Unit frame for CLS as per RDSO drawing No:S 23024/M.
336	SCR	162583 14-06-23	56790107	Encloser Base and Cover with mesh anodized circuit diagram to Drg. no. S & T /MFT/4629/ADV 3, S & T /MFT/4630/ADV 3. & S & T /MFT/4716/ADV 2 .with anodized name plate and screen printing particulars on front side of the box are latest amendments.
337	SCR	162595 14-06-23	56500520	TORIODAL TRANSFORMER -10 AMPS ALONG WITH CLAMPS
338	SCR	162605 14-06-23	56500658	METAL OXIDE VARIABLE RESISTOR [MOV] 150 VOLTS, 14 mm DISC Diameter
339	SCR	162606 14-06-23	56500786	CHOKE FOR TFBC 10 AMPS 360 MICRO H/100 HZ
340	SCR	162609 14-06-23	56500920	SENSOR PCB FOR 10 AMPS AS PER DRG S&T/MFT/4645/ADV 2
341	SCR	162610 14-06-23	56500968	5-Way Terminal
342	SCR	162635 15-06-23	56500970	E type locks along with key for Location Boxes
343	SCR	162641 15-06-23	56130089	Terminal Block 6 Way PBT (POLYBUTYLENE TEREPHTHALATE) 25mm (used for apparatus location boxes (pre wring)
344	SCR	162643 15-06-23	56500841	B type choke IRS:S: 65/83
345	SCR	162788 16-06-23	56501031	ND Knife Edge Fuse Block Suitable for Knife edge Links
346	SCR	163587 26-06-23	56501043	K4 Heat sink((Aluminium) with fastener). - 2Nos. Quantity as per enclosed Drg.No.S&T/MFT/6508/ADV.1 - 1No. and & Drg.No.S&T/MFT/6509/ADV.1 - 1No b) Bridge rectifier KBPC 3510 or MIC MB3510 or similar - 1No Diode 25NS40LP or equivalent - 25Amps/400Volts - 1No
347	SCR	163200 21-06-23	56180056	SWITCH EXTENSION BRACKET as per drawing :RDSO/S-3264 Alt2, painted with one coat of Red Oxide Premier.
348	SCR	162655 15-06-23	75900520	Hylum sheet 10 mm thickness size 1200x2400 mm Electrical grade
349	SCR	171005 10-10-23	76010144	Manual Metal Are Welding Electrodes Size 4 x 350mm, Class M4, Type of Coating: Heavy conforming to IRS M: 28-2020 CODE-E23. 12LR26, As Par IS 5206-2013.
350	SCR	171008 10-10-23	76900071	MIG/MAG welding filler wire to IRS-M46-2020, Class-VI. Type: Solid with shielding gas grade ER 308L, Size: dia 1.2mm net weight per spool not more then 12.50 kg.
351	SCR	176284 05-01-24	55900010	Electronic inverter (LED Driver) for LED Module, input voltage 110 V AC/DC, voltage range 90-140 V AC/DC, input current - (max.) 25 MA conforming to RCF Drg.NO. LW-76013 Alt-e suitable for LHB light fitting in night light (LED type) of LHB AC coaches. Make DR Auto model No. DR-30-DC-LED/ Integ/ Electronics best choice Model No. BS107/ Kwiklite or similar

352	SCR	174359 06-12-23	76110047	CO2 WELDING TORCH COMPATIBLE TO 400A MIG/MAG WELDING MACHINE, SELF COOLED, EURO CONNECTED 3M LONG OF ESAB MODEL Tbi 250 EXPERT (OR) OTC DAIHEN MODEL NO. WT2000-S (OR) KEMPPi MODEL NO. MTP 350 (OR) ABICOR BENZIL MODEL NO. MB GRIP 36 KD (OR) KEEAN PART NO. KMAB-38IK OR EQUIVALENT MODEL IN ADOR MTG 250 (E) SUITABLE FOR 1.2MM & 0.8MM SOLID AND FLUX CORED WIRE ONLY. (NOTE: THE ITEM MUST BE PROCURED FROM OEM/AUTHORISED DEALERS ONLY)
353	SCR	176797 12-01-24	75610115	PVC Sleeve of size 27 +/- 1 mm ID x 0.8 mm thick x 50 mtrs long (in a roll) of colour: French Blue shade no. 166 of IS: 5-2007 for berth chain in Non-AC coaches to Drg. no. PD/TPYS/SCR/DRG.No.C&W No.159
354	SCR	176799 12-01-24	75610036	PVC Sleeve of size 27 +/- 1 mm ID x 0.8 mm thick x 50 mtrs long (in a roll) of colour: Dark Brown shade no. 412 of IS: 5-2007 for berth chain in AC coaches to Drg. no. PD/ TPYS/SCR/DRG.No.C&W No.159.
355	SCR	209853 20-02-25	75034803	Flexible water pipe of size 20mm. Material with Thermo plastic with Synthetic reinforcement as per IS : 12585-88, type-2, Shall be covered with SS Sleeves, confirming to 19027 Rev.03 (item- 11 of Table-1)
356	SER	4867 20-04-17	56480891	ELECTRIC POINT OPERATING MACHINE,IRS TYPE 143 MM STROKE, AC IMMUNITY 160 V AC, NON-TRAILABLE TO OPERATE ON 110 V DC, WITH LOCK, DETECTOR, CABLE TERMINAL BOX WITH TWO NUMBERS OF TELESCOPIC PIPES AND SLIDES FOR LOCK & DETECTOR, ROTARY LOCKING, UNIVERSAL TYPE WITH GROUND CONNECTION COMPLETE FOR 52 KG./60 KG. POINT ON PSC SLEEPER, AS PER SPECN. NO. IRS-S-24/2002 AMENDMENT-1 OR LATEST WITH DRAWING NO. S-3361-62 & IRS-S-23/88 OR LATEST IF ANY. SPECN. NO. 37/82 AMD-3 & DRG. NO. S-10910 (143 MM THROW AS PER DRG. NO. RDSO/S-10800) ONE TOOL KIT SHALL CONSISTS OF FOLLOWING ITEMS. (ONE TOOL KIT SHAL BE
357	SER	11926 25-10-17	76011800	MANUAL METAL ARC WELDING ELECTRO SIZE 4MM X 350MM, CLASS-M2 FOR BOXNHL WAGON. HEAVY COATING TYPE. SPEC. IRS-M-28/12, CODE AS PER IS 5206-2003 E 19.9 LR 26
358	SER	17837 17-02-18	76013510	ALUMINIUM ELECTRODES 3.15MM DIA SPEC. TENSILE STRENGTH 24KGS/MM SQUARE TO IS 5897, FIRST REVISION AND REAFFIRMED 2003. SAMPLE TO BE APPROVED FROM CONSIGNEE BEFORE BULK SUPPLY
359	SER	22568 21-04-18	75613451	Flexible PVC flooring Sheet size- 2x1620x7000 mm for AC Coaches. Sample Code No-ACFLG-01. Matching quantity of PVC welding electrodes to be supplied along with PVC Sheets as per Clause No.2.7 of RDSO STR No. RDSO/2006/cg-12 (Rev-1)/August- 2008.
360	SER	23414 05-05-18	75400030	PRELAMINATED SHADED COMPREG, SIZE : 2.44 M x 1.22 M x 4mm COLOUR AND SHADE : RDSO SAMPLE CODE NO. AC-SP 02 MATERIAL SPECIFICATION : RDSO SPEC. NO. C-K 513/2005 WITH CORRIGENDUM I/ JUNE 2015 & AMEND. 5/ SEPT. 2015 REMARKS : RDSO'S SAMPLE CODE NO. AC-SP-02.
361	SER	24627 23-05-18	75400030	PRE LAMINATED SHADED COMPREG SHEET ,SIZE-2.44M X 1.22 M X 4 MM,COLOUR AND SHADE - RDSO'S SAMPLE CODE NO.AC-SP 02
362	SER	24626 23-05-18	75402257	PRE LAMINATION SHADED COMPREG SHEET, SIZE-2.44M X 1.22 X 4MM. COLOUR AND SHADE- RDSO'S SAMPLE CODE NO. NAC-SP 05.
363	SER	32546 20-09-18	56110091	PVC INSULATED UNDERGROUND, UNSCREENED CABLE FOR RAILWAY SIGNALLING 2 CORE x 2.5 SQ MM AS PER SPECIFICATION NO IRS-S-63/2014[REV. 4.0] INCLUDING LATEST AMENDMENT.THE CORE OF CABLE SHALL BE IDENTIFIED AS PER PARA 3.2.5 OF THE SPECIFICATION
364	SER	32553 20-09-18	56110108	UNDERGROUND RAILWAY SIGNALLING CABLE , UNSCREENED PVC INNER SHEATHED, ARMoured AND PVC OTHER JACKET WITH HIGH CONDUCTIVITY, ANNEALED COPPER CONDUCTOR,SIZE 18 CORE x 1.5 SQ MM CONFIRMING TO RDSO SPECN No. IRS-S-63/2014 [REV.4.0] WITH LATEST AMENDMENT
365	SER	32559 20-09-18	56110110	PVC INSULATED PVC SHEATHED ARMoured UNSCREENED UNDERGROUND RAILWAY SIGNALLING POWER CABLE 1100V GRADE 2 CORE x 70 SQ MM H2 GRADE ALUMINIUM CONDUCTOR AS PER SPECN No. IRS-S-63/2014 AND IS:1554[PART I] REV.4.0
366	SER	41537 03-01-19	75328203	Insulating pad for swivelling and fixed type Fan as per CEE'S Drg. No. CEE/G/A-3/TL-364 (Rev-1).
367	SER	60590 10-07-19	75613888	Flexible Poly vinyl Chloride (PVC) Flooring Sheet In rolls of Size:1850 mm widthX16.3 meter long of 2 mm nominal thickness for LHB NAC coaches. Note: firm should supply suitable PVC welding electrode of length 2XWXL RDSO Spec. no-RDSO/2006/CG-12(REV-1) with amendment slip no-4 august 2018 or latest. colour as per RDSO approved sample code NAC FLG-02
368	SER	60587 10-07-19	75614066	Flexible Poly vinyl Chloride(PVC)Flooring Sheet In rolls of Size:1850 mm widthX16.3 meter long of 2 mm nominal thickness for LHB AC coaches.Note:firm should supply suitable PVC welding electrode of length 2XWXL RDSO Spec.no-RDSO/2006/CG-12(REV-1) with amendment slip no-4 august 2018 or latest. colour as per RDSO approved sample code AC FLG-01
369	SER	80527 21-02-20	76904398	STAINLESS STEEL WIRE SPOOL FOR MIG WELDING, SPEC: STAINLESS STEEL 316L,(Weight of one spool 12.500 Kgs.)Size: Wire dia1.2 MM
370	SER	83305 27-03-20	75900117	DISPOSAL STERILE SURGICAL GLOVES (LATEX) PRE POWDERED, ANATOMICALLY SHAPED FOR COMFORT IN PAIR. SIZE : 6 Inch = 2000 PAIRS, 6.5 inch = 15000 PAIRS, 7 inch = 15000 PAIRS, 7.5 inch = 8000 PAIRS AND 8 inch = 1000 PAIRS.
371	SER	83304 27-03-20	75900129	Endo tracheal tube with high volume, low pressure cuff with self-sealing valve , Murphy eye made of PVC , Radio-opaque line and having Black encircling line near the tip (Inner diameter) 7 mm and 7.5 mm (450 nos each)
372	SER	83303 27-03-20	75900130	Turbo Closed Suction system with dynamic valve & isolated cleaning chamber with twin peep seal for normal intubated patient. (per pack size:- 20 nos. 12 fr = 10 nos., 14 fr = 10 nos.)
373	SER	83302 27-03-20	75900142	Plastic Apron (OT)
374	SER	83301 27-03-20	75900154	SHOE COVERS (In Pairs)
375	SER	83300 27-03-20	75900166	NON INVASIVE VENTILATOR BIPAP MACHINE. ACCEPTED MAKE AND MODEL : MAKE : RESMED INDIAN PVT. LTD., MODEL : LUMIS 150 DESCRIPTION AND SPECIFICATION, IN DETAILS, (AS PER DOCUMENTS ATTACHED).
376	SER	83299 26-03-20	75900210	Non-sterile gloves (in Pair)
377	SER	83298 26-03-20	75900178	Alcohol based (Ethanol + Chlorhexidine) Hand Sanitizer 500 ml bottle. Make: Dettol/ Himalaya/ Godrej/ Lifebouy (1 No. Unit = 1 bottle containing of 500 ml Hand Sanitizer)
378	SER	83297 26-03-20	75900180	Personal Protective Equipment (PPE) set.(N-95 respirator mask, Hood cover, Impermeable Surgicalgown, Gloves, Shoe cover) Basic Rate: Rs. 1,100.00 (R

379	SER	83296 26-03-20	75900191	N 95 MASK (specification attached)
380	SER	83295 26-03-20	75900208	Disposable Surgeons Caps (Non Woven and 3 Ply) (Box of 50 pcs) Firms Offer
381	SER	83306 27-03-20	75900233	Surface Disinfectant
382	SER	83309 27-03-20	75900221	3 Layer Mask
383	SER	83308 27-03-20	75900245	Face Shield
384	SER	83307 27-03-20	75900257	Infrared Thermometer
385	SER	83310 27-03-20	75900270	GLOVES
386	SER	83313 27-03-20	75900282	N-95 MASK
387	SER	83315 27-03-20	75900300	SANITIZER
388	SER	83317 27-03-20	75900312	GOWN
389	SER	83357 27-03-20	75900324	SAFETY GLASS FOR PROTECTION FROM BACTERIA AND VIRUS INFECTION AND FOR MEDICAL USE
390	SER	83370 27-03-20	75900336	GLOVES (NITRILE)
391	SER	83392 28-03-20	75900348	VIRAL TRANSPORT MEDIA---PLASTIC CONTAINER/ZIP POUCH
392	SER	83397 28-03-20	75900350	DEAD BODY BAG
393	SER	83414 28-03-20	75900361	DISPENSOR BOTTLE HAVING TOP DISPENSING NOZZLE, CAPACITY 500 ML
394	SER	83413 28-03-20	75900373	HYDROGEN PEROXIDE
395	SER	83412 28-03-20	75900385	GLYCERINE
396	SER	83411 28-03-20	75900397	ISO Propyle Alcohol (IPA)
397	SER	83553 02-04-20	75900403	ELECTRONIC BLOOD PRESURE MEASURING EQUIPMENT WITH LED DISPLAY
398	SER	83554 02-04-20	75900415	STETHOSCOPE WITH DUAL HEAD STAINLESS STEEL CHEST PEICE, EXCELLENT SOUND CONDUCTOR 48 MM DIAMETER OF MEMBRANE WITH CONNECTING SPRING EMBEDDED SINGLE PVC TUBING CE CERTIFIED AND US FDA APPROVED.
399	SER	83555 02-04-20	75900427	PULSE OXYMETER SPO2 FINGER PROBE (ADULT)
400	SER	83556 02-04-20	75900439	SUCTION MACHINE COMPLETE ABS-PLASTIC , MECHANICAL TYPE BACTERIAL FILTER AUTOCLAVE, SS VALVES
401	SER	83571 03-04-20	75900440	Medicine Trays
402	SER	83572 03-04-20	75900452	Emergency medical tray
403	SER	83573 03-04-20	75900464	Ice bags WHEREVER COMPLETE DESCRIPTION OF MATERIAL IS NOT AVAILABLE PURCHASE OFFICERS (Sr DMM/Dy.CMMS) ARE ADVISED TO DECIDE COMPLETE DESCRIPTION AT THE TIME OF TENDERING IN CONSULTATION WITH MEDICAL /MECHANICAL DEPARTMENT
404	SER	83575 03-04-20	75900476	Suction Catheters WHEREVER COMPLETE DESCRIPTION OF MATERIAL IS NOT AVAILABLE PURCHASE OFFICERS (Sr DMM/Dy.CMMS) ARE ADVISED TO DECIDE COMPLETE DESCRIPTION AT THE TIME OF TENDERING IN CONSULTATION WITH MEDICAL /MECHANICAL DEPARTMENT
405	SER	83576 03-04-20	75900488	Torch WHEREVER COMPLETE DESCRIPTION OF MATERIAL IS NOT AVAILABLE PURCHASE OFFICERS (Sr DMM/Dy.CMMS) ARE ADVISED TO DECIDE COMPLETE DESCRIPTION AT THE TIME OF TENDERING IN CONSULTATION WITH MEDICAL /MECHANICAL DEPARTMENT
406	SER	83577 03-04-20	75900490	Drinking water container WHEREVER COMPLETE DESCRIPTION OF MATERIAL IS NOT AVAILABLE PURCHASE OFFICERS (Sr DMM/Dy.CMMS) ARE ADVISED TO DECIDE COMPLETE DESCRIPTION AT THE TIME OF TENDERING IN CONSULTATION WITH MEDICAL /MECHANICAL DEPARTMENT
407	SER	83581 05-04-20	75900506	SODIUM HYPOCHLORIDE SOLUTION 4-6% AS PER SPECIFICATION IS 11673:1992 FIRST REV IN 05 LITRE JAR
408	SER	83633 06-04-20	75900518	LIQUID MEDICAL OXYGEN GAS FILLING OF CUBIC METER CAPACITY VESSEL IN CUBIC METER
409	SER	110300 27-07-21	56451120	Relay, AC Immune, plug in type, style QNA1. DC neutral line, 24V, 8F, 8B contacts, front and back contacts metal to carbon, with plug board, retaining clip and connectors conforming to BRS: 931A, IRS: S 60, IRS: S 34 & IRS: S 23 (as per applicable). The interlocking code for this unit shall be ABDGH.
410	SER	110304 27-07-21	56451143	Relay, Non AC Immune, plug in type, style QN1. DC neutral line, 24V, 8F, 8B contacts, front and back contacts metal to carbon, with plug board, retaining clip and connectors conforming to BRS: 930, IRS: S 60, IRS: S 34 & IRS: S 23 (as applicable). The interlocking code for this unit shall be ABCDF.
411	SER	110310 27-07-21	56451155	Relay, AC Immune, plug in type, style QNNA1. Twin DC neutral line, 24V, 6F, 2B contacts each for LH and RH, front and back contacts metal to carbon, complete with plug board, retaining clip and connectors conforming to BRS: 960, IRS: S 60, IRS: S 34 & IRS: S 23 (as per applicable). The interlocking code for this unit shall be CDEHX.
412	SER	110311 27-07-21	56110133	Cable fibre optical armoured 24 fiber as per specification no. IRS/TC/55/2006/Rev-I with amendment no. 3

413	SER	110319 27-07-21	56450588	Relay, non AC Immune, plug in type, style QN1. neutral line, 24V, 12F, 4B contacts metal to carbon, with plug board, retaining clip and connectors conforming to BRS: 930, IRS: S 34 & IRS: S 23 (as applicable). The interlocking code for this unit shall be ABCDE.
414	SER	110321 27-07-21	56450590	Relay, non Immune, plug in type, style QNN1. Twin DC neutral line, 24V, 4F, 4B contacts each for LH and RH, front and back contacts metal to carbon, complete with plug board, retaining clip and connectors conforming to BRS: 960, IRS: S 34 & IRS: S 23 (as applicable). This item is reserved for RDSO approved vendors or their authorized suppliers only.
415	SER	110329 27-07-21	56450620	Relay, AC Immune, plug in type, style QNA1. DC neutral line, 24V, 8F/ 8B contacts, front and back contacts metal to carbon, with plug board, retaining clip and connectors conforming to BRS: 931A, IRS: S 34 & S 23, S-60 (as applicable). The interlocking code for this unit shall be ABDGH.
416	SER	110330 27-07-21	56450722	Relay, Non-AC Immune, plug in type style QNN1. Twin DC neutral line, 24V, 6F, 2B contacts each for LH and RH, front and back contacts metal to carbon, complete with plug board, retaining clip and connectors conforming to BRS: 960, IRS: S 34 & IRS: S 23. The interlocking code for this unit shall be ACDEK.
417	SER	110331 27-07-21	56450734	Supply of Relay Immune plug in type style QNNA1. Twin DC neutral line, 24V, 4F/4B contacts each for LH and RH, front and back contacts metal to carbon, complete with plug board, retaining clip and connectors conforming to BRS: 960, IRS: S 60, IRS: S 34 & IRS: S 23 (as applicable). The interlocking code for this unit shall be ACDHJ. RDSO/SPN/84 VER: 2.0 INSPECTION BY RDSO. Accepted make/brand: Self
418	SER	110370 28-07-21	56480623	Electric Point operating Machine IRS Type 220 mm Throw, High Thrust, [AC Immunity 160V AC], Rotary Locking Type, Non-Trailable to operate on 110V DC, Complete with Lock & Detector Slide, Cable Terminal Box and clamp Lock & Ground Connection as per specification No. IRS: S-24/2002 Amd. - 1 and Assembly Drg. No. RDSO: S 11000 and RDSO: S-3395 and for Motor IRS: S-37/82 Amd. -3 with External Clamp Point Lock 60 kgs., TWS, as per Drg. No. RDSO: S-3454 and with Insulation Sets and Nuts, Bolts [suitable for 220 mm Throw IRS Point Machine] using 60 kg Rail. Make/Brand - VOSSLOH.
419	SER	112649 21-08-21	75030100	VINYLE HOSE 80 MM. DIA. FOR INTER VEHICULAR COUPLER UNIT (Z-S COUPLING) FITTED IN AC LHB EOG TYPE COCHES. AS PER RCF DRG. NO. EDTS-105, REV-E, AMDT. 1,2 & 3.
420	SER	148736 12-12-22	76018775	MANUAL METAL ARC WELDING ELECTRODE CLASS-M5, TYPE OF COATING: HEAVY, SPECIFICATION : IRS M-28/12, CODE AS PER IS: 5206-2003. SIZE: 4MM X 350 MM.
421	SER	148867 13-12-22	56110029	PVC INSULATED, ARMoured, UNSCREENED, UNDERGROUND ALUMINIUM CONDUCTOR POWER CABLE AS PER SPECIFICATION No. IRS: S-63/2014 & IS-1554 (PART-1) (REV. 4.0) OR LATEST.SIZE: 2 CORE x 35SQ.MM] MAKE: LASER (SELF)
422	SER	172807 07-11-23	76010156	MMAW Electrode, Size 3.15 x 350 mm, Class – M4 Type of coating: Heavy Coated as per Spec: IRS M-28/2020, Code E23.12LR26 as per IS: 5206-2019)
423	SER	172801 07-11-23	76050040	Manual Metal Arc Welding Electrode, Size 3.15 x 350 mm. IRS Class – M2, Coating – Heavy to IRS Specn. No. M: 28/2020, IS/AWS (Code: E19.9LR26 conforming to IS: 5206/2019).
424	SER	172799 07-11-23	76010168	Manual Metal Arc Welding Electrode, Size 3.15 x 350 mm, Class – M1, Type of coating: Heavy conforming to IRS M: 28-2020 (Code E19.9R26 as per IS: 5206-2019).
425	SER	172704 06-11-23	75207977	Leather hand gloves as per BLW specification no. MP/SAFETY/SPEC./PPE/1(Ed-9) valid from 20.08.2022.
426	SER	181407 16-03-24	76210157	Set of Electrode (Cathode) & Nozzle (Anode), size 1.5 mm dia, compatible for 100A Torch of Plasma Cutting Torch (P-80) of ADOR CHAMPCUT 25C or TP-INV-100 of TECHPRO Plasma Cutting Machine. Drg. No. i) Electrode to part no. S 17.01.003.1258 of ADOR or part no. Cathode TPC-1.5 of TECHPRO, Qty/set-1. ii) Nozzle to part no. S 17.01.003.1256 of ADOR or part no. Anode TPA-1.5 of TECHPRO, Qty/set-1. Mat. & Spec.: As per Drawing / Part No.
427	SER	181395 16-03-24	76900083	Copper coated MIG/MAG welding filler wire 1.2 mm dia (Solid), Spool size 5000 meter.
428	SER	181392 16-03-24	76210169	Plasma Cutting Torch with 10 mtr. long connecting cable suitable for plasma cutting Machine of ADOR CHAMPCUT 25C or TECHPRO TP-INV-100.
429	WR	165 23-11-16	75904366	BASE MOULDING OF PVC OF 2.5 +/- 0.25 MM THICKNESS. ONLY SHAPE & PROFILE AS PER ICF DRG NO. ICF/STD-4-2-002, ALT-B/2 AND MATERIAL CONFIRMING TO IS:6307-85, TYPE-I, COLOUR-SMOKE GREY TO SHADE NO.-692 OF IS:5-1994 (PERMISSIBLE WITH MINOR VARIATION)
430	WR	689 10-01-17	76010594	MANUAL METAL ARC WELDING ELECTRODES. DIA 4MM, CLASS M4 TYPE OF COATING HEAVY CONFIRMING SPECN NO. IRS-M-28/12, CODE-E23.12LR26 AS PER IS5206-2003.
431	WR	14671 20-12-17	76015385	"MANUAL METAL ARC WELDING ELECTRODE, CLASS-MI, SIZE-3.15X350 MM LONG, HEAVY COATED. CONFORMING TO SPECN. NO. IRS: M-28/12 OR LATEST. CODE E19.9R26 AS PER IS: 5206-83/2003. NOTE:-MATERIAL SHALL BE PROCURED FROM RDSO APPROVED SOURCES ONLY."
432	WR	32408 17-09-18	76019731	GRAPHITE DISC ELECTRODE MUST BE HIGH-PURITY GRAPHITE (SPECTRO GRAPHIC GRADE) SUITABLE FOR MOA II PLUS SPECTRO GRAPH METER SIZE:- 0.49 Inch Dia, 0.200 Inch WIDTH, 0.12 Inch inner Dia HOLE,ELEMENT: A1,B,Cr,Cu,Fe,Na,Mg,Ni,Ca,Si,Sn, Pb,Zn,Mo,P,Ag & Ti SHOULD BE 00 PPM Note: Per box contain 500 Nos. Discs. (Temp. PL no. 76980789)
433	WR	35924 02-11-18	56460016	LED SIGNAL LIGHTING UNIT 110V AC FOR POSITION LIGHT SHUNT SIGNAL IN RAILWAY SIGNALLING AS PER RDSO/SPN/153/2011 (REV. 4.1) (OLD PL NO. 56980413)
434	WR	36476 10-11-18	56460028	LED SIGNAL LIGHTING UNIT 110 V AC FOR MAIN COLOUR LIGHT SIGNAL IN RAILWAY SIGNALLING RETROFITABLE IN EXISTING CLS HOUSING . (SA:23002, 23024/M) AND COMPATABLE WITH AC LED ECR, ALL AS PER RDSO SPEC. NO. RDSO/SPN/199/2010 REV. 1.0 OR LATEST. ASPECT YELLOW. (OLD PL NO. 56980449)
435	WR	37638 24-11-18	76010727	"5 MM DIA. MANUAL METAL ARC WELDING Electrode CLASS 'B2', TYPE OF COATING : HEAVY, CONFORMING TO THE SPEC. NO. IRS : M-28/2012, CODE : EB5426H3JX as per IS : 814-04 WITH AMDT. NO.'1' OF 2005 & '2' OF MARCH '2008. (Temp. PI no. 76980947)
436	WR	23945 12-05-18	76010119	CUTTING ELECTRODE N-1 CLASS,SIZE 4X350 MM CLASS N1, CONFORMING TO SPEC.NO.IRS:M-28/17.
437	WR	38220 05-12-18	75320150	RUBBER SHEET FOR PASTING ON UIC VESTIBULE OF SIZE-1 METER X 1 METER X 2 MM THICK MATERIAL CONFIRMING TO RDSO SPEC.No.RDSO/2007/CG-05 WITH AMND. SLIP NO.-3 OF APRIL-2015 AND CORRIGENDUM SLIP NO.-2 OF JUNE-2015.(Temp. PL 75980265)
438	WR	37325 20-11-18	56460030	LED SIGNAL LIGHTING UNIT 110V AC FOR MAIN COLOUR LIGHT SIGNAL IN RAILWAY SIGNALLING RETROFITABLE IN EXISTING CLS HOUSING (SA .23002 S23024/M)AND COMPATIBLE WITH AC LED ECR ALL AS PER (OLD PL NO. 56980437) {UPL No. 56460028 is already allotted to another item i.e. LED SIGNAL LIGHTING UNIT 110 V AC FOR MAIN COLOUR LIGHT SIGNAL IN RAILWAY SIGNALLING RETROFITABLE IN EXISTING CLS HOUSING. (SA:23002, S:23024/M) AND COMPATIBLE WITH AC LED ECR, ALL AS PER RDSO SPEC. NO. RDSO/ SPN/199/2010 REV. 1.0 OR LATEST. ASPECT YELLOW. Please allotte another UPL for this item.)

439	WR	36439 10-11-18	56460041	LED SIGNAL LIGHTING UNIT 110 V AC FOR ROUTE INDICATOR SIGNAL IN SIGNAL IN RAILWAY SIGNALLING AS PER RDSO/SPN/153/2011 (REV 4.1) (OLD PL NO. 56980425) {UPL no. 56460028 is already allotted to another item. i.e. LED SIGNAL LIGHTING UNIT 110 V AC FOR MAIN COLOUR LIGHT SIGNAL IN RAILWAY SIGNALLING RETROFITTABLE IN EXISTING CLS HOUSING . (SA-23002, 23024/M) AND COMPATABLE WITH AC LED ECR, ALL AS PER RDSO SPEC. NO. RDSO/SPN/199/2010 REV. 1.0 OR LATEST. ASPECT YELLOW. Please allot another PL no. to this item}
440	WR	38360 06-12-18	76011148	LOW ALLOY WELDING ELECTRODE OF SIZE -3.15 MM X 450 MM OF BRAND NAME 1)FERRO WELD W 2 OF ESAB MAKE OR 2)SECHERON COROTHERME SPECIAL OF D&H SECHERON MAKE OR 3)ULTRA CORTEN-III OF ADOR MAKE (Temp PL No 76980017) (Note: This is the branded item and class is not mentioned by manufacturer)
441	WR	36111 05-11-18	75610036	PVC SLEEVE FOR COVERING BERTH CHAIN LINK AND SHACKLE, SIZE 30 +/-1 MM ID X 1.0 MM THICK X 50 MTR. LONG (IN A ROLL). MATERIAL SHALL BE CONFORMING TO IS: 5831-1984/2001, TYPE ST1. COLOUR SHADE OF MATERIAL AS PER RDSO SAMPLE CODE NO. AL-AC-01. NOTE: SAMPLE TO BE APPROVED BEFORE BULK SUPPLY.
442	WR	47175 28-02-19	76010120	LOW ALLOY WELDING ELECTRODE OF SIZE -3.15 MM X 450 MM OF BRAND NAME 1)FERRO WELD W 2 OF ESAB MAKE OR 2)SECHERON COROTHERME SPECIAL OF D&H SECHERON MAKE OR 3)ULTRA CORTEN-III OF ADOR MAKE (Temp. PL no. 76980017)(kindly allot unified PL no other than 76011148 which is already exists in W. Rly.)
443	WR	42055 08-01-19	75610048	SELF DRY SEALANT FOR WATER PROOFING AND CAULKING PURPOSE TO BE APPEARED GREY OR SILVER FINISH, AS PER SPECIFICATION. IS:1580-1991 GRADE-I.
444	WR	44470 31-01-19	75328203	RUBBER PACKING FOR CARRIAGE FAN CONFORMING TO ICF DRG. NO. ICF/SK 7-3-058 ITEM NO. 1 (OLD PL NO 45985662)
445	WR	48222 08-03-19	75200016	PVC Push type flush valve size 25mm (1") inner dia.
446	WR	72407 19-11-19	56468039	LED SIGNAL LIGHTING UNIT 110V AC FOR MAIN COLOUR LIGHT SIGNAL IN RAILWAY SIGNALLING RETROFITTABLE IN EXISTING CLS HOUSING (SA-.23002, S-23024/M)AND COMPATIBLE WITH AC LED ECR ALL AS PER RDSO /SPN/ 199/2010 REV 1.1 OR LATEST.ASPECT RED. (Temp. PL no. 56980437 and 56460030)
447	WR	108884 03-07-21	75905220	Polythene Bags of Minimum 400 mm width and 600 mm length. The thickness of polythene should be 0.127 mm minimum.
448	WR	135477 02-07-22	76114030	SOLID MIG/MAG WELDING FILLER WIRE OF 1.2 MM DIA. IRS CLASS-IV QUALITY, GRADE-ER80S-G AND AWS SPEC. NO. AWS A5.28/A5.28M:2020, AS PER IRS SPEC. NO. M-46/2020. WEIGHT OF WIRE SPOOL: 12.5 KGS APPROX.
449	WR	163752 29-06-23	75900531	POLYETHYLENE GARBAG BAG 120 MICRON, SIZE 914MM X 609MM +/- 10MM COLOUR BLACK (PLASTIC BAG)
450	WR	165690 27-07-23	75400110	PROTECTIVE CAP TO KBI PART NO.B75404 ALONG WITH BREATHER PLUG TO KBI PART NO B66529/5
451	WR	116846 27-10-21	76011380	Electrodes Class 'D' 3.15 mm x 450 mm Spec. Mat. Specification: IRS, M-28/2020
452	WR	116905 27-10-21	76115902	Flux cored MIG/MAG welding filler wire with shielded gas, class IV size 1.2 mm Spec. No IRS: M-46/20 with amendment no 1. grade E81T1-W2C as per AWS:A 5.29-10
453	WR	209014 11-02-25	75030172	Hose Pipe 1 for Brake Cylinder for BOXNHL (BMBS) Wagon, RDSOs Drg. No. 09034-S-11, Alt, 5 or latest, Item No.24 & KBI Drg. No. I.4.2036 or Similar. Specification No. WD-23 BMBS-2008
454	ECR	8168 01-08-17	56468131	Battery operated LED Base torch Light Cum Flashing hand signal lamp specification no RDSO/SPN/195/2008/REV 2.2
455	ECR	5480 22-05-17	75900828	Acrylic reflector, 80mm, RDSO Sk no.-8520
456	ECR	5482 22-05-17	75320137	Sealing Ring for 20NB Pipe to RCF's Drg. No.-CC-35318, Alt No.-"d".
457	ECR	6604 07-07-17	56468131	Battery operated LED based torch light cum flushing had signal lamps.
458	ECR	13184 23-11-17	75050020	Rubber Hand Gloves, Size- 18 inch length, made from natural rubber, Colour- Yellow, having protection from wide range of chemicals, IS:4770/1991, Brand- Ansel/Diamond/Jayco or similar
459	ECR	16896 03-02-18	76210078	Eye shield with Coloured glass (108x82mm) to BSS-679.
460	ECR	17308 09-02-18	76011460	Basic coated low hydrogen type of welding electrode of IRS Class E2 Electrode dia 4mm
461	ECR	16795 01-02-18	75560021	A set of cable ties (Non-returnable Lock) each set containing one one nos.
462	ECR	29859 05-08-18	76016262	Cutting Electrode of IRS Class-N1 size - 3.15x350mm
463	ECR	30467 18-08-18	76015282	Stainless steel electrode, size 3.15 x 350 mm. Drawing IRS:M-28/12 ,Code as per IS:5206-2003, class M-4.
464	ECR	30474 18-08-18	76010934	MS Welding Electrode, Class A2, size 3.15x350mm, Spec.No.IRS:M:28/12, with qual no. 2 of 2003,Code as per IS:814-2004.
465	ECR	32795 25-09-18	75615216	Non-skid monolithic flooring polymerized floor topping compound, color spectrum blue. RDSO/C-9704 of Aug 1997.
466	ECR	32798 25-09-18	75400250	Decorative thermosetting synthetic resin bonded laminated sheet, size 2440 x 1220 x 3 mm, Upgraded blue. Drawing RDSO/C-K-514 Rev-O of Dec 2005 with 04 amendments last amendment No. 04 of October -2013 shade code NAC-SP-05.
467	ECR	32800 25-09-18	75613451	Flexible PVC flooring sheet, size 7000 x 1620 x 2 mm thick with 15 meter of 2 mm dia PVC electrode upgraded NAC, color blue Drawing. RDSO/2006/CG-12 Rev-1 of Aug 2008, Sample code NAC-FLG02.
468	ECR	32821 25-09-18	75613797	Vinyl coated upholstery fabric, artificial leather, color blue upgraded.Drawing RDSO/2008/CG-07, Sample code ALNAC-03, with Amendment slip no-1 of Nov 2008.
469	ECR	35712 31-10-18	75610012	PVC Braded Transparent pipe(Hose)
470	ECR	30465 18-08-18	76018714	Stainless steel electrode, size 2.5 x 350 mm. Drawing IRS:M-28/12 Code as per IS-5206-2003, class M2.
471	ECR	92956 28-09-20	75031371	Hose flexible (Steel Corrugated) wire mashed on Top for compressor delivery air 1-1/2" ID X 26.5" long both end female swivel nut. Make- Hydraulic Syndicate or Similar.

472	ECR	113704 07-09-21	75613827	PVC FLOORING ROLL 2X1850X14000MM, COLOUR AS PER SAMPLE NO. ACFLG-01, as per Drawing: RDSO/2006/CG-12 REVISION 1 WITH AMENDMENT SLIP NO. 3 OF AUGUST 2016 WITH PVC WELDING ELECTRODE DIA 4MM=12 MTRS PER ROLL
473	ECR	113706 07-09-21	75613438	PVC FLOORING ROLL 2X1850X14000MM, COLOUR AS PER SAMPLE NO. NACFLG-02 FOR LHB COACHES as per Drg / spec: RDSO/2006/CG-12 REVISION 1 WITH AMENDMENT SLIP NO. 3 OF AUGUST 2016 WITH PVC WELDING ELECTRODE DIA 4MM=12 MTRS PER ROLL
474	ECR	146365 18-11-22	75010320	V Belt SP PT 2120 (Green Belt), Make/Brand-Fenner or Ecodrive or Continental.
475	ECR	146500 19-11-22	75018330	BELT V RIBBED, FOR 24V ALTERNATOR
476	ECR	150722 08-01-23	76019731	Electrode to size Dia 2.5mmx350mm length shall be low hydrogen type (basic coated) electrode with good welding characteristic and it shall be suitable for welding steel of IS:2062/latest or equivalent. The electrode shall be approved by RDSO under IRS Class 'A4' of IRS M28/2002 to the code EB 532xH2JX of IS:814/91 ('X' of the code refers to the welding current & voltage condition as recommended by the electrode manufacturer). The butt-welded test specimen prepared using the subject electrode shall pass 180-degree transverse bend test (Both root and face bends) on testing as per IS:3600-83 part-5 with Mandrel Dia (D) being 3T (T-thickness of the parent material). The electrode shall be operatable on AC as well as DC in which DC+VE is mandatory. Packing condition shall be as per clause 5.1.1 of IRS-M-28/2002. The pre-heating temperature and duration shall be specified on the electrode packets (Carton). The shelf life of the electrode shall be 12 months from date of receipt in stores or 18 months from the date of manufacture, whichever is more. In stores or 18 months from the date of manufacture, whichever is more.
477	ECR	133889 09-06-22	75350026	Wire Braided Pressure Hose Pipe 25MM Fitted With End Hexagonal Nut And Nipple With Washer Size 25MM, Total Length of Hose Pipe is 110cm Suitable For Suction Line Of Water Pump in LHB Type AC Coaches.
478	ECR	173047 09-11-23	75030111	FLEXIBLE HOSE PIPE FOR BOGIE AND BRAKE CYLINDER 1/2X600 MM.
479	ECR	173041 09-11-23	75017581	Ribbed V Belt - BX 29,
480	ECR	180255 28-02-24	75201331	S (Snake) Mat, Plastic Hygiene Mat, 5mm thickness approx. Colour-Red, Material -Virgin. Make- Durosoft or similar. As per GeM Contract-durowipe Carpet Or Rug Underlays (60 X 90 cm) Brand : durowipe
481	ECR	174978 16-12-23	76115604	FLUX CORED MIG/MAG WELDING FILLER WIRE WITH SHIELDED GAS. CLASS IV SPECN. IRS M-46-20 WITH AMENDMENT -1 GRADE AS PER AWS A5. 29-10 GRADE E81T1-W2C SIZE 1.2 MM IN SPOOL OF 12.5 KGS EACH,MAKE AS PER RDSO APPROVED VENDEOR LIST
482	ECR	189127 10-06-24	75035017	"SYNTHETIC THERMOPLASTIC POLYMER WATER HOSE OF NOMINAL BORE SIZE 50 MM, MATERIAL CONFORMING TO IS: 12585-1988, TYPE-II WITH AMND.SLIP NO.-1 OF SEPT-2003." TYPE 2 (ISI MARKED)
483	ECR	174977 16-12-23	76011380	Manual Metal Arc Welding Electrode, Class-D, Type of coating: Heavy Size 3.15 mm (dia) X 450 mm (length), Specification:IRS M-28-2020, (Version 1.0), Code-E8018W2 as per AWS A5.5/5.5M:2014
484	ECR	195160 26-08-24	56450450	Relay, Non-AC Immune, plug-in-type, style 'QN1' neutral line, 50V DC 8F.8B contacts, front and back contacts metal to carbon with plug board, retaining clips and connectors confirming to BRS: 930, IRS: S34-68 & IRS: S23-88.The interlocking for this unit shall be "ABCEF."(This will be used for EI system.).
485	ECR	193408 08-08-24	75101210	BELLOW DUCT ASSEMBLY COMPLETE WITH METALLIC FRAMES, PROVIDED WITH FIRE RETARDANT EPDM GASKETS ON BOTH SIDES, 2 NOS EACH FOR FRESH AIR AND RETURN AIR AND 1 NO FOR SUPPLY AIR PER RMPU, MADE OF ARAMID/PARA ARAMID FABRIC WITH SILICON RUBBER COATING ON BOTH SIDES TO RDSO SPECN. NO: RDSO/PE/SPEC/AC/0197- 2020 (REV 0) FOR RMPU FOR LHB EOG/HOG TYPE AC COACHES AS PER DRAWING NO:RDSO/PE/SK0069-2004 (REV.3)
486	ECR	210830 03-03-25	76015488	Low heat input type chamfering & gouging electrodes, Class-N3, Specification No. IRS-M-28/12, Size-4mm X 350mm.
487	ECR	210825 03-03-25	76900071	MIG/MAG welding filler wire to IRS-M46-2020, Class-VI. Type: Solid with shielding gas grade ER 308L, Size: dia 1.2mm net weight per spool not more than 12.50 kg.
488	ECR	195696 30-08-24	75320230	Grooved Rubber Profile for safety strap of Retention tank as per ICF drg No. ICFSK3-6-3-201 Alt-Nil. Matl.& Spec. As per drg. enclosed
489	ECR	195703 30-08-24	75050171	Sealing Rubber for WC Toilet to Drg.no. CG-16035
490	ECOR	9229 23-08-17	56500324	TRACK FEED BATTERY CHARGER FOR CHARGING 1 OR 2 OR 3 OR 4 LEAD ACID CELLS OF 2V 80 AH RATING OF CHARGER= 10A, AS PER RDSO SPECN IRS:S-89/2013
491	ECOR	30297 14-08-18	56080013	High availability Single Section Digital Axle counter [HASSDAC] of make CEL, Model 720P[HASSDAC] or GG Tronics, Model G36R [HASSDAC] complete or similar with dual sensor as per RDSO Specification no-RDSO/SPN/177/2012 with version 3.0 or latest.
492	ECOR	30290 14-08-18	56480891	Electric Point machine IRS Type 143mm throw (AC immunity upto 160 Volt AC) non-trilable to operate on 110V DC complete with lock detector, cable termination box and slide for lock and detector rotary locking Universal type as per Specification No. IRS-S-24/2002 with amendment-1, RDSO drawing no.RDSO/S-10800 or latest and motor IRS -S-37/82 and.3 with RDSO Drg no.-S-10910.
493	ECOR	30287 14-08-18	56500221	PVC Insulated Armoured, Unscreened, Underground Railway Signalling cable (Copper conductor) size 12 core x 1.5 sq.mm.
494	ECOR	30286 14-08-18	56500439	PVC Insulated Armoured, Unscreened, Underground Railway Signalling cable (Copper conductor) size 30 core x 1.5 sq.mm.
495	ECOR	30285 14-08-18	56480040	Ground connection complete suitable for high thrust rotary locking IRS Electric point machine as per Drg no SA-3361f/M for 60 KG rail with insulating materials.
496	ECOR	30289 14-08-18	56080025	Single Section Digital Axil counter set as per RDSO specification no.RDSO/SPN/177/2012, Ver-3 or latest. Each set consisi of; (1) Mounting accessoriers for rail contact, 02 sets (each set contains Tx, Rx coil 02 Nos. each.) Track side electronic unit with evaluator, (4) Clamp with deflector plates, (5) Reset box 02 Nos. (6) Protecting device (Though RDSO Specn. No. of this item is same as the item against PL.No. 56080013, but the items are different hence new PL no. may be allotted for this item.).
497	ECOR	31318 03-09-18	56110054	10 Pair Polythene Insulated and Polythene sheathed jelly filled underground cable of 0.63 mm dia. Copper conductor Poly-Al moisture barrier and steel tape armoured confirming to RDSO Specification No. IRS: TC-41/97 with amendment No.2 or latest.
498	ECOR	31315 03-09-18	56110080	20 Pair Polythene Insulated and Polythene sheathed jelly filled underground cable of 0.63 mm dia. Copper conductor Poly-Al moisture barrier and steel tape confirming to RDSO Specification No. IRS: TC-41/97 with amendment No.2 or latest.

499	ECOR	31282 01-09-18	56040040	Four port ADSL 2 plus router with downstream up to 24 Mbps upstream 1 Mbps RJ- 11 connector for connection to 24/26 AWG twisted Pair cable Four 10/100 base T..
500	ECOR	31289 01-09-18	56119550	8. Underground Railway Jelly filled 06 Quad cable 0.9 mm dia. As per IRS Specification No. IRS: TC-30/2005, [Ver.1] with amendment 4 or latest if any.
501	ECOR	43400 23-01-19	75100060	LEATHER GAUNTLETS COMPRISING OF ONE LH AND RH FOR WELDERS SIZE 400mm, TO DRAWING /SPECIFICATION IS:2573/1986 [2ND REV], TYPE-
502	ECOR	43413 23-01-19	76011197	Manual Metal Arc Welding Electrode, Class - A2(Rutile type), Type of Coating - Medium , Size - 4.00 x 450 mm, to Drawing / Specification IRS M-28/2017 , Code as per IS:814/2004.
503	ECOR	43938 24-01-19	75209561	LEATHER GAUNTLETS COMPRISING OF ONE LH AND RH FOR WELDERS SIZE 400mm, TO DRAWING /SPECIFICATION IS:2573/1986 [2ND REV], TYPE-1
504	ECOR	43942 24-01-19	75326395	Fire Retardant Densified Polyester Block for Lower & Upper Berth of GSCN Coaches, Size: 1830 mm x 550 mm x 51 mm, to Drawing /Specification RDSO Specn. No. C-K607(Rev-2), Amendment -1, dimensional tolerances as per IS spec. IS:2102(PART-1)/1993, Designation-V
505	ECOR	43946 24-01-19	75403043	Vinyl coated upholstery fabric [Artificial leather] for AC coaches, Width - 127cm to drawing/specification RDSO/2008/CG-07, Amndt. No.4, As per RDSO approved sample code no. ALAC-01.
506	ECOR	43954 24-01-19	75403717	Decorative Thermosetting Synthetic Resin Bonded Laminated Sheet, Size: 2440 mm x 1220mm x 3mm , to Drawing / Specification RDSO Specn. C-K514 , Amendment No. 7, Corrigendum- 1 , RDSO approved Sample Code No. ACSP02 for AC Coaches.
507	ECOR	43964 24-01-19	75613815	Flexible Poly Vinyl Chloride (PVC) Flooring Sheets, Size-2mm thick x 1620mm width x 7000mm length , to Drawing / Specification RDSO/2006/CG-12 (Rev.01 of Aug. 08 with 3 amendments - Last amendment No. 3 issued in August 16 & Corrigendum-1 of June -2015), RDSO approved shade No. ACFLG-01, PVC welding electrode of 2mm dia @ 30 metres per sheet to RDSO spec. RDSO/2006/CG-12 to be supplied by Firm free of cost alongwith the PVC flooring sheets.
508	ECOR	43663 24-01-19	76011197	Manual Metal Arc Welding Electrode , Class - A2 (Rutile type), Type of Coating - Medium , Size - 3.15 x 350 mm ,
509	ECOR	43650 24-01-19	75612173	Flexible Poly Vinyl Chloride [PVC] Flooring Sheets, Size-2mm thick x 1620mm width x 7000mm length,
510	ECOR	43872 24-01-19	75325070	RUBBER PAD FOR AXLE PULLEY FOR 25KW ALTERNATOR AS PER RDSOs DRG. NO.SKEL-4021 ALT. 2 OR LATEST MADE OF POLYCHLOROPRENE RUBBER COMPOUND GRADE-F, CONFORMING TO PROPERTIES AS LAID DOWN IN CL.3.2.4.1 AND 3.2.4.2 OF RDSOs SPECIFICATION NO. IRS R48-88.
511	ECOR	57094 04-06-19	56501006	PVC INSULATED,ARMOURED,UNSCREENED,UNDERGROUND RAILWAY SIGNALLING CABLE [COPPER CONDUCTOR] SIZE 24 CORE X 1.5 Sq mm. CONFORMING TO RDSO SPECIFICATION No IRS:S:63/2014 (REV 4.0)
512	ECOR	57098 04-06-19	56500830	PVC INSULATED,ARMOURED,UNSCREENED,UNDERGROUND RAILWAY SIGNALLING CABLE [COPPER CONDUCTOR] SIZE 19 CORE X 1.5 Sq mm CONFORMING TO RDSO SPECIFICATION No IRS: S:63/2014 (REV 4.0)
513	ECOR	57101 04-06-19	56509960	PVC INSULATED,ARMOURED,UNSCREENED,UNDERGROUND RAILWAY SIGNALLING POWER CABLE [ALUMINIUM CONDUCTOR] SIZE 02 CORE X 25 Sq mm
514	ECOR	57105 04-06-19	56500476	MONOMODE OPTIC FIBRE CABLE FOR USE IN INDIAN RAILWAY TELECOMMUNICATION NETWORK AS PER SPECIFICATION NO. IRS:TC 55/2006, Rev. 1 WITH AMENDMENT NO.3 OR LATEST (24 FIBRE ARMOURED OFC)
515	ECOR	57091 04-06-19	56500488	UNDERGROUND RAILWAY JELLY FILLED 06 QUAD CABLE 0.9MM DIA AS PER IRS SPECIFICATION No IRS:TC:30/2005 [VER 1] WITH AMENDMENT 5 or latest if any. Make/Brand-Self.
516	ECOR	59097 24-06-19	76110035	Solid MIG/MAG Welding Filler Wire , Dia -0.8 mm, Class -I , to Drawing /Specification IRS M-46/13 , Amendment No. 1 , Grade S3C503 as perIS:6419-2004.
517	ECOR	59100 24-06-19	76014060	Stainless Steel Electrodes , Class-M4, Size:3.15 x 350 mm , to Drawing/Specification IRS: M-28/17, Code E23.12LR26 as per IS:5206-2003.
518	ECOR	59101 24-06-19	76010090	Manual Metal Arc Welding Electrode, Class-M1, Type of Coating Heavy, toDrawing /Specification IRS:M-28/12 with Amendment No. 1 , Code as perIS:5206/2003, Size: 4 X 350 mm.
519	ECOR	59102 24-06-19	76015310	Welding Electrodes class M-5 , size 3.15 x 350 mm to RDSO approved Specn. No. IRS:M-28/12 , CodeE18. 8MnR26 as per IS:5206-2003.
520	ECOR	59107 24-06-19	76015373	Welding Electrodes class N-1, size 3.15 x 350 mm , current range 150-230Aon AC & DC (-) (OCV-50) to RDSO approved Specn.No.IRS:M
521	ECOR	59108 24-06-19	76011471	Welding Electrodes class E-2 , size 4 x 350 mm to RDSO approvedSpecn.No. IRS : M-28/12, Code E55BG1Ni26 as per IS: 1395-2003
522	ECOR	59155 25-06-19	75034827	Thermoplastic Hoses (Textile Reinforced), Nominal Bore - 50 mm , to Drawing/ Specification IS:12585 / 1988 , Type - 2 , Length of each pipe - 15 metresRailway logo 'IR' in suitable size be marked with indelible ink on every halfmetre length & the hose should have ISI marking IS:12585 , Type- 2.
523	ECOR	59149 25-06-19	75030020	Steel wire reinforced PVC hose - 50mm dia [inside] in coil of 20mtrs to drawing/specification IS-9537[Pt-5] /2000, Amendment No.1.
524	ECOR	59148 25-06-19	75036459	Rubber Hose for Oxy Acetylene Welding & Cutting with Braided TextileReinforcement in Red Colour, Size-8mm x 7.5mtr in length to Drawing/Specification IS:447/1988(Reaffirmed-2003)B
525	ECOR	59119 25-06-19	75540010	DOOR MAT SIZE 560MM X 915MM 22 X 36 INCH , IS : 11420 of 1985 WITH LATEST AMMENDMENTS
526	ECOR	59116 25-06-19	75540022	DOOR MAT SIZE 762MM X 1220MM AS PER IS 11420/85
527	ECOR	59113 25-06-19	75900099	Polyurethane Putty , to Drawing / Specification RDSOs specn No.M&C/PCN/100/2009.
528	ECOR	59112 25-06-19	75909649	Unsintered Poly Tetra Fluoro Ethylene (PTFE) tape for Thread Sealingapplication, Size: 25 mm width x 12 mtrs length, to Drawing / Specification IS:14643/99.
529	ECOR	59111 25-06-19	76011380	Manual Metal Arc Welding Electrode , Class : D, Type of Coating - Heavy,Size : 3.15 x 450 mm , to Drawing / Specification IRS: M-28/17 , CodeE8018W2 as per AWS 5.5.
530	ECOR	59109 24-06-19	76019998	Welding Electrodes class N-2, size 4 x 350 mm to RDSO approved Specn.No. IRS :M-28/12
531	ECOR	56384 24-05-19	75908438	Helmet with Head Lamp PETZL TIKKA XP ATEX head torch E81 powerful I LED hazardous location headlamp with 3 lighting levels and boost mode or similar. The Helmet should confirm to IS: 2925. Head lamp brightness:- 35 Lumens, Flood beam: LED X4, powerful head lamp (as per approved sample)
532	ECOR	83152 20-03-20	75327132	Rubber Profile for LHB AC Coaches. Drg No. LW 54141, Alt. Nil.

533	ECOR	136008 11-07-22	75326980	DENSIFIED THERMAL BONDED POLYESTER BLOCKS AS PER RDSO's SPECN.NO. C-K607, REV-2. OF DECEMBER 2015 OR LATEST. SIZE:- (57.5X 540 X 923)mm. TO RCF's DRG.NO.LW 61193, ITEM NO -1, ALT.NO.'a OR LATEST. DENSITY 60 Kg/m3. confirming to UIC fire retardant properties. Items required in blocks (Without groove & radius) as per dimension.
534	ECOR	135999 11-07-22	75386975	DENSIFIED THERMAL BONDED POLYESTER BLOCKS TO RDSO's SPECN.NO. C-K607, OF REV-2 OF DECEMBER 2015 OR LATEST. SIZE : (50 X 500 X 559) mm. AS PER RCF'S DRG.NO.LE 61209, ITEM NO -6, ALT.NO.'e OR LATEST. DENSITY- 60 Kg/m3 Confirming to UIC fire retardant properties. Items required in block (without groove & radius) as per dimension.
535	ECOR	135944 11-07-22	75326954	DENSIFIED THERMAL BONDED POLYESTER BLOCK TO RDSO's SPEC. NO. C-K607, REV-2, SIZE - 61 X 560 X 1854 MM FOR LHB SIDE UPPER, confirming to UIC fire retardant properties, item required in block (without groove & radius) as per dimension.
536	ECOR	140520 08-09-22	76114030	SOLID MIG/MAG WELDING FILLER WIRE, CLASS IV TO IRS M: 46/13 WITH AMENDMENT NO.1, GRADE ER80S-G AS PER AWS: A 5.28-10, SIZE: 1.2MM Firm's Accepted Make/Brand : SUP....
537	ECOR	180523 04-03-24	75050122	ELECTRIC RUBBER HAND GLOVES WITH ISI MARK AS PER IS 13774 (1993), TEST POTENTIAL - 33000 VOLTS, WORKING POTENTIAL - 26500 VOLTS. SIZE 360 - 380 MM LENGTH
538	ECOR	215859 16-05-25	76010170	Welding Electrode of Size : 3.15 mm Diameter x 350
539	NCR	59339 26-06-19	56119550	Underground Railway Jelly field Quad cable for signaling and Telecom installation of size 6Quad x 0.9MM Copper Conductor dia as per SPC. No. IRS. TC-30/2005 [Ver.1] with Amendment-5
540	NCR	59340 26-06-19	56110133	24 Fibre armoured optical fibre cable as per RDSO Spec. No. IRS: TC: 55/2006[Rev. 1] with amendment no. 3 or latest.
541	NCR	75733 31-12-19	76210856	BRAZING FLUX MATERIAL (LIQUID) AS PER DIN-EN-1045-FH-10, SUITABLE TO WITHSTAND TEMPERATURE UP TO 950 CENTIGRADE , MAKE-EUTECTOR FLUX 1801 OF (L&T) OR ESAB OR DIFFUSION ENGG.ONLY. SUPPLIER SHOULD SUBMIT OEM'S / OEM'S AUTHORIZED DEALERS PURCHASE CERTIFICATE
542	NCR	73831 06-12-19	76115124	Brazing Rod size 2 mm dia 600 mm long as per spec. no. DIN-EN-1044-AG-203
543	NCR	85719 20-05-20	76100066	RUPTUM SILVER BRAZING FOIL SIZE:- 500 MM LENGTH X 10 MM WIDTH X 0.8 MM THICK. SILVER CONTENT:- 49% TO 51% AS PER IS:- 2927-1975 Gr: BA Cu Ag-9
544	NCR	110631 31-07-21	75613888	Flexible Poly vinyl Chloride (PVC) Flooring Sheet In rolls of Size:1850 mm widthX16.3 meter long of 2 mm nominal thickness for LHB NAC coaches. Note: firm should supply suitable PVC welding electrode of length 2XWXL RDSO Spec. no-RDSO/2006/CG-12(REV-1) with amendment slip no-4 august 2018 or latest. colour as per RDSO approved sample code NAC FLG-02
545	NCR	161454 01-06-23	75610103	SLEEV PVC (COMMERTIAL QUALITY) FOR CN COACHES SIZE-ID-30, OD-33 MM COLOUR SHADE OF MATERIAL SHELL BE PER RDSO SAMPLE CODE NO.-AL-NAC-03. RDSO SAMPLE CODE NO.-AL-NAC-03.
546	NCR	130392 23-04-22	75400030	Decorative Thermosetting Synthetic Resin Bonded Laminated Sheets Size- 2440mm x 1220mm x 3mm thickness as per RDSO's Spec. no. C-K 514 (Rev 0 of Dec 2005 with 7 amendments, last amendment no. 7 issued in August 2016 & Corrigendum 1 of June 2015) colour shed Code No. AC-SP-02
547	NCR	165572 26-07-23	76010958	Manual Metal Arc Welding Electrode, Class C1 as per IRS:M28-02 or latest (E63BD126), as per IS:1395-2013, size 4x450 mm
548	NCR	164948 18-07-23	75208040	CUT RESISTANT HAND GLOVES CONFIRMING TO DLW SPECIFICATION MP/SAFETY/SPEC./PPE/24 (REVISION-12) DATED 31.07.2014.
549	NCR	122682 13-01-22	75030123	Flexible hose (650 mm) for LHB coaches body to bogie connection. RDSO Drg No.-CG-19036.Spec No-KBI Part No-1.3.941/2 or FTIL Part No-708008400.
550	NCR	182498 27-03-24	76210236	Heavy Duty Earthing Clamp (Crocodile Type), ISI marked and Specification attached at Annexure-A.
551	NCR	122608 12-01-22	75050158	Rubber Hollow Mat Size-1000 MM X 1500 MM. Drg No- CWS/BCT/12/03/2020/Rubber Hollow Mat.
552	NWR	521 28-12-16	76014162	MANUAL METAL ARC WELDING ELECTROD DIA 2.5 mm CLASS M-4, TYPE OF COATING HEAVY, CONFORMING TO SPEC No IRSM28/12 CODE 'E23,12LR 26' AS PER IS. 5206-83 (FIRST REVISION)
553	NWR	7224 20-07-17	75904226	FIRE RETARDANT THERMAL INDULATION FOAM SHEET, 12 MM THICKNESS, BLACK COLOUR, SUITABLE FOR LHB VARIANT AC COACHES CONFIRMING TO RDSO SPEC No. RDSO/PE/SPEC/AC/0061-2005(REV-1) OR LATEST
554	NWR	24801 25-05-18	76019925	MANUAL METAL ARC WELDING ELECTRODE IRS CLASS M2 , HEAVY COATED, 5mm X 350mm LENGHT, CONFIRMING TO IRSM:28-2012
555	NWR	25207 04-06-18	76010790	SUPA BASE X PLUS SPECIAL ELECTRODES FOR MILD STEEL WELDING COADING AWS/SFA5.IE 7018 IS: 814 EB5426H3JK
556	NWR	39228 10-12-18	75403225	ACRYLIC SHEET TRANSPARENT TO SIZE 120 X 915 X 3 mm THICK TI IS : 7569/87
557	NWR	65697 31-08-19	76015270	Manual metal arc welding electrode, size 2.5mm class M-4
558	NWR	69739 15-10-19	75401710	PVC SLEEVE OF SIZE 30+/- 1MM IDX1.5MM THICK X 50 MTRS LONG (IN A ROLL) TYPE ST 1 COLOUR SHADE OF MATERIAL AS PER RDSO SAMPLE CODE NO. ALAC-01
559	NWR	69735 15-10-19	75401745	PVC SLEEVE OF SIZE30+/- 1MM IDX1.5MM THICKX50 MTRS LONG (IN A ROLL) TYPE ST 1 COLOUR SHADE OF MATERIAL AS PER RDSO SAMPLE CODE NO. ALNAC-03
560	NWR	57883 13-06-19	76115112	COPPER TO COPPER BRAZING ROD SIZE 3.15 MM. LENGTH 500 MM, MATERIAL SHOULD BE BA-CU-P-3, AS PER RUPATAM-2 OF M/S ESAB, CONFIRMING TO IS:2927-1975 OR LATEST ACCEPTED MAKE L&T/ADVANI/ESAB IS:2927-1975 Spec:IS: 2927-1975
561	NWR	75172 23-12-19	56501006	SIGNAL CABLE, 24 CORE PVC INSULATED UNDER GROUND UNECRNEED ARMoured CABLE COPPER CONDUCTOR 240X1.5mm2 as per RDSO Spec IRS-S-63/2014 Rev 4.0
562	NWR	75181 23-12-19	56480647	ELECTRIC POINT OPERATING MACHHINE,IRS TYPE 143 MM STROKE, AC IMMUNITY 160 V AC, NON-TRAILABLE TO OPERATE ON 110 V DC, WITH LOCK, DETECTOR, CABLE TERMINAL BOX WITH TWO NUMBERS OF TELESCOPIC PIPES AND SLIDES FOR LOCK & DETECTOR, ROTARY LOCKING, UNIVERSAL TYPE WITH GROUND CONNECTION COMPLETE FOR 52 KG./60 KG. POINT ON PSC SLEEPER, AS PER SPECN. NO. IRS-S-24/2002 AMENDMENT-1 OR LATEST WITH DRAWING NO. S-3361-62 & IRS-S-23/88 OR LATEST IF ANY. SPECN. NO. 37/82 AMD-3 & DRG. NO. S-10910 (143 MM THROW AS PER DRG. NO. RDSO/S-10800) ONE TOOL KIT SHALL CONSISTS OF FOLLOWING ITEMS. (ONE TOOL KIT SHAL BE S

563	NWR	75167 23-12-19	56150210	LOW MAINTENANCE LEAD ACID STAIONARY SECONDARY CELL WITH PPCP WITH INTER CELL CONNECTORS & NUTS & BOLTS CAPACITY 2V 80 AH. SPECN. NO. IRS:S:88/2004 OR WITH LATEST AMENDMENT IF ANY. .
564	NWR	75178 23-12-19	56110091	PVC INSULATED UNDERGROUND, UNSCREENED CABLE FOR RAILWAY SIGNALLING 2 CORE x 2.5 SQ MM AS PER SPECIFICATION NO IRS-S-63/2014[REV. 4.0] INCLUDING LATEST AMENDMENT.THE CORE OF CABLE SHALL BE IDENTIFIED AS PER PARA 3.2.5 OF THE SPECIFICATION
565	NWR	80077 17-02-20	75018305	V-BELT SIZE C-109 CONFORMING TO I.S. 2494(PT-1) 1994. FOR AUXGEN/ EXICTER GEN 100 V FPR 1400 HHP DEMU. V BELT FROM THE SAME BATCH SHALL BE PACKED IN SETS OF 5 NOS. EACH MAKE :- DUNLOP/ ECO DRIVE/ FENNER & PIX TRANSMISSION. Note : MATERIAL SHOULD BE PROCURED FROM OEM/AUTHORIZED DEALER ONLY.
566	NWR	80131 18-02-20	56450345	fail safe electronic flasher (relay room) spec. IRISO/SPN/173/2002 AND AMEND .2
567	NWR	79363 08-02-20	56440030	panel button gray
568	NWR	88061 02-07-20	56502345	FUSE " G "TYPE NON DETERIORATING INDICATING TYPE 0.6 AMP CAPACITY GENERALTY USED FOR RLY. SIGNALLING INSTALLATION CONFIRMING TO RDSO SPEC. No. IRS-S-80/92.
569	NWR	87794 28-06-20	56500956	FUSE " G "TYPE NON DETERIORATING INDICATING TYPE 1.6 AMP CAPACITY GENERALTY FORRLY SIGNALLING INSTALLATION SPEC ;IRS-S-78/92 OR LATEST
570	NWR	83029 18-03-20	56450151	TIMER 0-60 SEC
571	NWR	92451 17-09-20	56060026	Choke B Type to suit, specification No. IRS:S-65/83(Amendment No. -1) for single Rail track circuit on 25KV 50Hz, AC section Spec:
572	NWR	92454 17-09-20	56468027	LED ROUTE SIGNAL LIGHTING UNIT,110 V AC RETROFITABLE IN EXISTING CLS HOUSING AND COMPATIBLE WITH AC LED ECR AS PER RDSO SPEC. NO. RDSO/SPN/153/2011 REV. 4.1.
573	NWR	92457 17-09-20	56468015	SHUNT LED SIGNAL LIGHTING UNIT RETROFITABLE IN EXISTING CLS HOUSING AS PER RDSO SPECIFICATION NO. RDSO/SPN/153/2011 REV. 4.1 WITH LATEST AMENDMENTS/VERSION
574	NWR	92460 17-09-20	56468064	LED CALLING OF SIGNAL LIGHTING UNIT,110 V AC RETROFITABLE IN EXISTING CLS HOUSING AND COMPATIBLE WITH AC LED ECR AS PER EDSO SPEC.NO.RDSO/SPN/153/2011 REV. 4.1.
575	NWR	92462 17-09-20	56451106	RELAY, AC IMMUNISED, PLUG IN TYPE, STYLE' QTA2'DC NEUTRAL TRACK, 9 OHM, 2F-1B CONTACTS, FRONT AND BACK CONTACTS METAL TO CARBON, COMPLET WITH PLUG BOARD, RETAINING CLIP AND CONNECTORS CONFIRMING TO DRS: 939A, BRS:966, (APPENDIX F2), IRS:S-34 AND IRS:S -23 OF LATEST (AS APPLICABLE). THE INTERLOCKING CODE FOR THIS UNIT SHALL BE FGHKX.
576	NWR	92463 17-09-20	56450175	RELAY, AC IMMUNE, PLUG IN TYPE, STYLE QNA1, DC NEUTRAL LINE, 24V DC, 8F/8B CONTACTS METAL TO CARBON WITH PLUG BOARD, RETAINING CLIP AND CONNECTORS CONFIRMING TO BRS: 931A, IRS-S-60, IRS-S-34 AND IRS-S-23 (AS APPLICABLE). THE INTERLOCKING CODE FOR THIS UNIT SHALL BE ABDGH OF LATEST.
577	NWR	92465 17-09-20	56452032	RELAY, AC IMMUNE, PLUG IN TYPE, STYLE QNA1, DC NEUTRAL LINE, 24V DC, 12F/4B CONTACTS METAL TO CARBON WITH PLUG BOARD, RATAINING CLIP AND CONNECTORS CONFIRMING TO BRS: 931A, IRS-S-60, IRS-S-34 AND IRS-S-23 (AS APPLICABLE). THE INTERLOCKIG CODE FOR THIS UNIT SHALL BE ABDFH OF LATEST.
578	NWR	92476 17-09-20	56450450	RELAY QN1, 50V VOLT, 8F/8B CONTACT, BRS-930A, NON ACI DC NEUTRAL LINE RELAY INTERLOCKED CODE ABDEF. THIS WILL BE USED FOR E(ELECTRINIC INTERLOCKING) SYSTEM.
579	NWR	92483 17-09-20	56451039	RELY AC IMMUNE PLUG-IN-TYPE STYLE QBAT, DC BASED TRACK 9 OHOS 2F/2B CONTACTS, FRONT AND BACK CONTACTS META TO CARBON COMPLETE WITH PLUG BOARD RATAINING CLIP & CONNECTORS CONFIRMING TO RDS/SPN/84-88, IRS:S:34 & IRS:S:23 (AS APPLICABLE) THE INTERLOCING CODE FOR THIS UNIT SHALL BE ABEJK
580	NWR	89824 29-07-20	56450205	REALY AC IMMUNE PLUG IN TYPE STYLE QNA1, DC NEUTRAL LINE ,24V DC, 12F/4B CONTACTS METAL TO CARBON WITH PLUGE BOARD,RETAINING CLIP AND CONNECTORS CNFRIMING TO BRS 931A,IRS-S-60,IRS-S-34 AND IRS-S-23 AS APPLICABLE .THE INTER SOCKING CODE FOR THIS UNIT SHALL BE ABDFH OR LATEST.
581	NWR	89885 30-07-20	56450229	RELAY AC IMMUNISED PLUG IN TYPE STYLE QTA2 DC NEUTRAL TRACK 9 OHM,2F-1B CONTACTS FRONT AND BACK CONTACTS METAL TO CARBON COMPLETE WITH PLUGE BOARD RETAINING CLIP AND CONNECTORS CONFIRMING TO BRS;939A BRS;966[APPENDIX F2] IRS ;S-34 AND IRS;S-23 OR LATEST [AS APPLICABLE] THE INTERLOCKING CODE FOR THIS UNIT SHALL BE FGHKX
582	NWR	92493 17-09-20	56900016	SUPPLY OF YELLOW RETRO REFLECTIVE SHEET FOR LC BOOM PRISMATIC GRADE FEFLECTIVE SHEET OF SIZE 305X290MM ONE SET CONSIST OF 18 PIECES. (1.6 SQ MTETER)
583	NWR	92461 17-09-20	56301704	A SET OF GROUND CONNECTION FOR 52KG/60KG RAILS COMPLETE FOR WORKING MOTOR OPERATED POINT MACHINE SUITABLE FOR ORDINARY TARNOUTS RAIL SWITCHES TO RDSO DRG. NO. SA 9151-52 WITH LATST AMENDMENT IF ANY SHALL CONSISTS OF FOLLOWING 16 ITEMS: (1) DETECTOR ROD (NEAR END) DRG. SA -9105-1 NO.,(02) DETECTOR ROD (FOR END) DRG. SA-9104-01 NO.,(03) LOCK ROD DRG. SA-9107-01 NO.,(04) DRIVE ROD DRG. SA-9106-01.,(05) SWITH EXTENSION BRACKET DRG. SA 9103-02 NOS., (06) LOCK STRECHER BAR DRG. SA-9102- 01 NO.,(07) DRIVE LUG DRG. S-8806-01 NO., (08) INSULATING BUSH DRG. S-8813-02 NOS., (09) INSULATING PLATE DRG. 8804- 01 NO., (10) INSULATING PLATE DRG.S-8803-02 NOS. DETAIL IN TERMS
584	NWR	99573 01-02-21	75540873	MAT DOOR COIR SIZE 100 CM X 60 CM, MASS - 4800 GM PER SQM, PILE HIGHT 22 MM COLOUE & DESIGN STENCILED.
585	NWR	89819 29-07-20	56301613	A SET OF GROUND CONNECTION FOR 52 Kg/60Kg RAIL COMPLETE FOR ORDINARY TURN OUT RAIL SWITCHES TO RDSO DRG NO RDSO/s-3262 WITH LATEST AMENDMENT IF ANY shall CONSISTS OF FOLLOWING ITEMS ;[01] Lock rod (near end) Drg. No. RDSO/S3273/1 No. (2) Lock rod (far end) Drg No. RDSO/S3271-1 No. (3) Detector rod (near end) Drg. No. RDSO/S-3269-1 No. (4) Detector rod (far end) Drg. No. RDSO/s-3267-1 No. (5) Switch extension bracket, Drg No. /RDSO/S3264-02 No. (6) Drive lug, DRG No. S/8806-1 No. (7) Drive rod , Drg No. -SA 8805-1No. (8) Bolt special head , Drg. No. SA312/M-6 No. (9) Washer (Punched)MS, M20-14 No. (10) Bolt MS Hex. HD, M20X200 with hex nut-4 No.
586	NWR	105040 23-04-21	75033264	HOSE SET 15 METERS, PART HYDRAULIC NO. HS14 OF AVLOCK MAKE OR EQUIVALENT
587	NWR	89550 22-07-20	56460016	LED ROUT SIGNAL LIGHTINGUNITE110V AC RETOFITABLE IN EXISTING CLS HOUSING AND COMPATIBLE WITH AC LED ESR AS PER RDSO SPEC NO. RDSO/SPN/153/2011 REW 4.1.
588	NWR	92474 17-09-20	56110145	VF TRANSFORMER for unloaded quad cable impedance ratio (470:600) Ohms SPEC. NO. IRS:TC 76/2000 AMDT. NO.1.

589	NWR	121337 23-12-21	75904287	HPL Sheet 3x1220x2440 mm. shade RAL-9006, Matt finish, gloss value 10-12 at 45 degree as per MDTs-086 Revision-nil.
590	NWR	124175 31-01-22	75018317	V-Belt C-110 for Traction Alternator of 1600 HP DMEU/DPC make Fenner Roflex or Similar.As per IS 2494/1994 Pt.-I & SS 9790/1995
591	NWR	92501 17-09-20	56158026	48V -200 AH VRLA BATTERY BANK CONSISTING OF 24X2 VOLT 200 AH MAINTENANCE FREE VRLA BATTERIES, DULY CHARGE WITH REQUIRED CONTAINER ACCESSORIES LINE CONNECTORS, CLAMP LUGS, INTERLINKS ECT. AS PER RDSO SPEC.NO. IRS-S-93/96A WITH AMDT 1 OR LATEST
592	NWR	149970 23-12-22	75400066	High Pressure Laminate(HPL) Sheet 3x1220x2440 mm. shade RAL-9006, Matt finish, gloss value 10-12 at 45 degree as per MDTs-086 Rev-1.
593	NWR	150900 10-01-23	76117510	Solid MIG/MAG welding filler wire, class IV size 0.8 mm diameter confirming to IRS: M-46/2020, Grade ER 80S-G as per AWS: A5.28M:2020, The gross weight of the spool including wire shall not be more than 12.5 Kg.
594	NWR	134638 16-06-22	75037026	ISI MARKED RUBBER HOSE FOR OXYGEN ACETYLENE WELDING AND CUTTING WITH BRAIDED TEXTILE RE- INFORCEMENT IN BLACK OR BLUE CONFORMING TO IS:447/1988 (REAFFIRMED-1998) OF SIZE: 8MM BORE X 15 MTRS LENGTH.
595	NWR	149262 17-12-22	76011847	Welding Electrode, Class-M5, IS-5206/03, E18.8MnR26, IRSM 28/201 7, Type of Coating: Heavy, Size: 5.00 x 350 mm.
596	NWR	134649 16-06-22	75613839	Flexible poly vinyl chloride (PVC) flooring sheet of heterogeneous type in length of 14000 mm, width 1620 mm and thickness 2 mm, Colour , shade and pattern as per RDSO approved sample No.NAC FLG-02 for Non-AC coaches circulated vide RDSO's letter no. MC/CB/Flooring/CG-12 dated 21.01.16 along with 2mm dia PVC electrode of same shade and length confirming to RDSO specification No. RDSO/2006/CG-12(Rev-01 of Aug 08 with 2 Amendments-Last Amendment no.2 issued in September 2015 & Corrigendum No.1 of June 2015.
597	NWR	134664 16-06-22	76217450	NOZZLE MIXING CUTTER WITH ONE ANM NOZZLE SIZE 1/16" BOTTOM POSITION LEVER, ANGLE HEAD 90 DEGREE, LENGTH 450 MM, NMC-250 OF ESAB , 303 OF ADOR MAKE, PROFILE CUT OF L&T MAKE AS PER IS: 7653-1975,In 303 of ADOR make & profile cut of L&T make, firms make and IS no should be embossed on the forged body of cutter with OEM authorized certificate. IN NM 250 of ESAB, sticker of firm name, model no and ISI mark should be pasted sticker and Sr. no of torch should be Embossed/Engraved on the forged body of cutter along with OEM authorized certificate"
598	NWR	134651 16-06-22	75905048	SHEET ACRYLIC (PERSPEX) TRANSPARENT 1220MM LENGTH X 915MM WIDTH X 6 MM THICK TO IS: 7569/1987.Type -A Grade -II. The date of supply of the material should be within 60 days from the date of manufacture.
599	NWR	134648 16-06-22	75407607	Vinyl Coated Upholstery Fabric for AC coaches.(The colour, shade and pattern of this material shall be as per sample code no.AL AC-01 or as agreed to between the purchaser and supplier) As per RDSO Specn. No. RDSO/2008/CG-07 (Rev 0 of Aug 08 with Amendment no. 4 issued in September -2015 or latest a n d & corrigendum -1 of May -2015 or latest) Accepted description: Vinyl Coated Upholstery Fabric for AC coaches.(The colour, shade and pattern of this material shall be as per sample code no.AL AC-01 or as agreed to between the purchaser and supplier) As per RDSO Specn. No.RDSO/2008/CG-07 (Rev 0 of Aug 08 with 5 Amendments- Last Amendment No.5 issued in August-2016 and & corrigendum -1 of May -2015
600	NWR	134662 16-06-22	76016845	MANUAL METAL ARC WELDING ELECTRODE, CLASS-M5, TYPE OF COATING : HEAVY, (SPECN. NO. IRS:M-28/12 AMENDMENT-1& 2 or latest), SIZE 4.00 X 350 MM. CODE E 18.8 MnR 26. Accepted description: MANUAL METAL ARC WELDING ELECTRODE, CLASS-M5, TYPE OF COATING : HEAVY, (SPECN. NO. IRS:M28/12 AMENDMENT-1& 2), SIZE 4.00 X 350 MM. CODE E 18.8 MnR 26
601	NWR	134659 16-06-22	76011471	Manual metal ARC welding electrodes class E-2 size 4X350 mm type of coating H to Specification No IRS M-28/02 amendment no 1&2.(For RDSO approved sources only)
602	NWR	180713 07-03-24	76013716	ALUMINUM TIG WELDING WIRE CLASS 4043, SIZE -2.4 TO 3.2 X1000 MM. CHEMICAL COMPOSITION AL BAL. Si 4.5-6.0, FE 0.60 MAX, CU 0.30 MAX, TI 0.15 MAX, ZN 0.10 MAX,MN 0.15 MAX, MG 0.20 MAX BY WEIGHT%.
603	NWR	180720 07-03-24	76017047	Stainless Steel TIG welding wires Class ER 308 / ER 308L, SIZE: 2.40 TO 3.10 X1000 mm. Chemical composition C 0.03, Mn 1-2.5, Si 0.30-0.65, Cr 19.5-22, Ni 9-11, S 0.03 max, P 0.03 max, Mo 0.75 max, Cu 0.75 max BY Weight %
604	NWR	161067 27-05-23	75050160	NEOPRENE RUBBER CAP (CANOPY) FOR CONDENSOR MOTOR PROTECTION FROM RAIN WATER AS PER SR.DEE (CHG) BCT'S DRAWING, NEOPRENE RUBBER GRADE HARDNESS : 50-55 MATERIAL SHALL BE FIRE RETERDANT AS PER IS: 7809 PART - II & RUBBER IS AS PER IRS R- 48-88.
605	NWR	211930 23-03-25	75440027	WELDING ARM GUARD MADE OF HIGH QUALITY CHROME TANNED LEATHER TO PROTECT ARM DURING WELDING.ARM GUARD JOINT WITH KEVLAR STICHD WITH BUCKLE WITH CHROME LEATHER WELDING ARM GUARD MADE OF HIGH QUALITY CHROME TANNED LEATHER TO PROTECT ARM DURING WELDING.ARM GUARD JOINT WITH KEVLAR STICHD WITH BUCKLE WITH CHROME LEATHER STRAP AS PER IS:6153-1971 WITH FLAME RETARDENT & HEAT RESISTANT LINNING OF TECHNICAL TEXTILE BLENDS OF BASOFIL NOMEX. KEVLAR AND FLAME RETARDENT VISCOUS CONFORMING TO IS : 11871-1986.
606	SECR	3437 06-03-17	75613463	PVC CONNECTION, SIZE-375 MM x0.5' (1/2"), MATERIAL- PTMT.
607	SECR	19697 09-03-18	75017570	(Old PL: 75980691) " V " Belt C- 113 for Air Compressor TRC - 2507 of 1400 HHP DEMU / DPC. Make : Turboflax, Fenner ,Pix Inter national. Spec:
608	SECR	19700 09-03-18	75017556	(Old PL: 75980708) V.Belt CX-70(Cogged) for Water pump of 1400 HHP DEMU/DPC Make : Turboflax, Fenner ,Pix Inter national . Spec:Make.Turboflax,Fenner ,Pix Inter national.
609	SECR	20122 12-03-18	54222242	(Old PL 50980087) OFC Joint encloser (24 fiber).
610	SECR	35105 25-10-18	75034803	WATER HOSE THERMOPLASTIC SYNTHETIC TEXTILE REINFORCED, COVER-SMOOTH FINISH, 20MM NOM. BORE X 15M. LONG TO SPEC.IS:12585-88 WITH AMENDMENT NO.1 OF SEP.'03 (REAFFIRMED 2008), TYPE 2.
611	SECR	95502 18-11-20	75403833	DECORATIVE THERMOSETTING SYNTHETIC RESIN BONDED LAMINATED SHEET (LP SHEET) TO SIZE 3 X 1200 X 2400 MM FOR NON-AC COACHING STOCK TO RDSO APPROVED SAMPLE CODE NAC-SP05. TO RDSO SPEC. NO. C-K 514, (REV.0 OF DEC.2005 WITH 7 AMENDMENTS-LAST AMD.NO. 7 ISSUED IN AUG.2016 & CORRIGENDUM NO.1 OF JUN2015
612	SECR	88124 03-07-20	75400091	Set of safety protective clothing for welders. supplied sets must consist of-(1) light wt. leather Apron(Jointed) size-1210x615x2mm(approx). qty-01 no(2) Light wt. leather leg guard, size-445x310x1.5mm (approx) qty-02nos(3) light wt. leather Arm guard, size 490x210/145x1.5mm (approx), qty-02 nos

613	SECR	112216 17-08-21	75050092	Cut resistance hand gloves in pair for one left hand and one right hand,conforming to EN: 388-2016 and CE certificate, Specification- Material Polyurethane, Liner colour - Blue/Black, Coating colour-Black ,Grip-smooth palm,Cuff style-straight with over lock thread beaded cuff area,Thickness-13 gauge,length-260 mm, Palm size-8 & 9,Performance level designation -4443C.Make-3M,Karam,DPL or Swalka-Kel.
614	SECR	65125 28-08-19	54900050	Collapsible (Folding)Canvas Stretcher specn. are as following: 1) Stretcher made of 25 mm dia X 10 swg alluminium tube. 2)Folding hings and clamps mild steel flat 25 X 19 mm forged.3) Handles covered with heavy duty rubber grip. 4)Patient carrying plane 0.75 mm thick washable canvas 5) Gross weight 5 kgs. 6) Canvas carrying bag. 7) Open stretcher (Inclusive of 4" handles) 84" X 23". 8) Folded stretcher length 42".
615	SECR	151125 12-01-23	75321014	Densified thermal bonded polyester blocks for transverse seat (LOWER SEAT) OF size 90 mm x 480 mm x 1720 mm for AC-2 tier coachesConfirming To RDSO Specification No C-K607 (Rev.2) WGSCWAC6-6-1-608 ITEM-1 alt. w/2
616	SECR	151127 12-01-23	75327259	DENSIFIED THERMAL BONDED POLYESTER BLOCK CUSHION FOR UPPER BERTH & BACK REST BERTH SIDE OF II TIER AC COACHESTO SIZE:- 2030 X 660 X 50 MM SPECN MATERIAL TO RDSO SPEC. NO.C-K 607, REV.2 OF DEC 2015.
617	SECR	151955 23-01-23	75320253	EPDM Rubber cable cleat suitable for Traction Motor cable of 300 Sqmm cable with 4 nos. entry along with mounting arrangement on WAG-7 type loco boggie as per ELS/BIA Drg. No. TRS/BIA/D-01/E3/02-11.
618	SECR	164512 11-07-23	76014186	GRAPHITE ROD ELECTRODE MUST BE HIGH PURITY GRAPHITE (SPECTRO GRAPHIC GRADE) SUITABLE FOR MOA II PLUS SPECTRO GRAPH METER,SIZE:-0.24 INCH DIA,6.0 INCH LONG ELEMENT: Al,B,Cr,Cu ,Fe,Na,Mg,Ni,Ca,Si,Sn,Pb, Zn,Mo,P,Ag & Ti SHOULD BE 00 ppm. Note: Per box/tub contain 50 nos. Rods. (As per ASTM D6595-00 Size: 0.243"x6.0" (6.15+-0.03)x(152.4+-1.57)
619	SECR	151117 12-01-23	75327302	DENSIFIED THERMAL BONDED POLYESTER BLOCK CUSHION FOR LONGITUDINAL SEAT OF SIZE 90 X 495 X 615 mm FOR II TIER ACCOACHES TO ITEM NO. 5 OF ICF DRG NO WGSCWAC4-6-1-411, ALT n/4 SPECN. MATERIAL TO RDSO spec NO CK-607 Rev2. of Dec 2015.
620	SECR	151039 12-01-23	75407607	VINYL COATED UPHOLSTERY FABRIC(ARTIFICIAL LEATHER) FOR AC COACHING STOCK TO RDSO APPROVED SAMPLE NO. ALAC -01TO RDSO SPEC. NO.RDSO/2008/CG -07, (REV.0 OF AUG.'08,WITH 5 AMENDMENTS LAST AMD.NO.5 IS ISSUED IN AUG-2016 &CORRIGENDUM 1 OF MAY 2015)
621	SECR	163141 20-06-23	75900543	Industrial safety helmet, Head form size 585 mm, Conforming to En:397-2021, Fitted with ratchet type adjustment and chin strap, Helmet must be furnished with (i) Side slot for the fitment of face and hearing accessories (as per clause 4.10 of EN:397) (ii) Shuttered ventilation holes (as per clause 4.9 of EN:397), (iii) comfort band (as per clause 4.7.3 of EN:397), (iv) Chin strap (as per clause 4.8 of EN:397) (v)Adjustable cradle to fit different head sizes (as per clause 3.5.3 of EN:397). Railway logo should be hot printed with WRS/R name, on the front. Helmet supplied should not have their manufacturing dates older than 9 months from the date of release of the purchase. Tenders must invariably submit CE affiliation certification of the make offered by them, without which their offer will not be considered. Successful tenders must enclose requisite product test certificate(s) from the authorised lab along with the supply. Consignee may further conduct testing of sample(s) from the authorised lab , if desirable. Make & model : Model Hardhat HP3M-H701V of 3M or PN-542 of KARAM or HPSAV-FRSS1-W of Saviour.Colour (nearest shades are acceptable with prior approval):(i) Yellow :1500 Nos (ii) Green : 150 Nos (iii) White : 50 Nos (iv)Purple : 50
622	SECR	164459 10-07-23	75322857	HEAVY DUTY POLYCHOLOROPRENE(NEOPRENE)RUBBER SHEET.SIZE:1000 MM WIDTH, 2 MM THICK X 10 METERS LENGTH IN ROLLS AS PER CLW'S SPECN. NO.CLW/ES/R-24/D.
623	SECR	151120 12-01-23	75321210	DENSIFIED THERMAL BONDED POLYESTER BLOCK CUSHION FOR TRANSVERSE MIDDLE, UPPER AND SIDE UPPER BERTH OF III TIERAC COACHES TO SIZE 1795 X 583 X 95 mm .to item no 6 of RCF Drg no AE -61444,Alt. f SPECN. MATERIAL TO RDSO SPEC.NO CK -607 REV2 OF DEC 2015
624	SECR	173068 09-11-23	75010021	INDUSTRIAL SAFETY BELT TYPE-2 AS PER IS:3521-1999.
625	SECR	172993 09-11-23	76901830	SAFETY HELMET AS PER BLW SPECIFICATION No.Safety/Spec./Safety Helmet/08(Rev-10) date 11.09.2023.
626	SECR	165198 20-07-23	75050134	Class-D type Rubber Hand Gloves made with suitable insulating Rubber for electrical applications use, without any joint in Hand Gloves, Test Voltage 40000 Volt and working Voltage 36000 Volt & Breakdown voltage 50000 Volt, size length 400 mm, palm size 10 inches confirming to as per EN-60903 IEC: 60903. Make Brand:-3M, reflomax, venus, orafol, Jyot. The bidder has to submit a test certificate for the material from an NABL accredited test lab for all the rating partner of material, offer without such certificate will be summarily rejected. A certificate that material has been purchased from the OEM/authorized dealer of OEM along with 1 year guarantee/warranty certificate & test certificate from prescribed institute or OEM to be submitted at the time of supply.
627	SECR	168589 01-09-23	75327478	Rubber Gasket water and acid proof size 40 mm (breadth) x 6 mm (Thick) For WAG-7 Locos Battery Box , Material type -Buna-N.
628	SECR	170810 07-10-23	76015257	Electrode Stainless Steel Size : 3.15 x 350 mm. IRS Class 'M 2 Type of Coating : Heavy as per specification no. IRS : M 28/2020) and IS : 5206/R-2019), (AWS Code : E19.9/LR 26). (warranty) Up to 30 months from the date of supply)
629	SECR	178211 02-02-24	76116220	SOLID MIG/MAG WELDING FILLER WIRE, CLASS VI SIZE 1.2 MM (SPEC.NO.IRS M-46/2020) GRADE ER 308 LAS PER AWS: A 5.9/5.9M: 2017 IN SPOOL OF 12.5 KGS/ROLL
630	SECR	183872 10-04-24	75050146	Rubber Gloves for Electrical Purposes Type 4 (Guntle type) For use at Voltage not exceeding 17000V, AC.
631	SECR	193626 10-08-24	75350040	Heavy duty pneumatic, Air hose pipe, length-26mtrs. inner dia-12.5mm. Pr. 17.85 Kgcm2. Make Poly hose or Ascent India or Phoenix or ESKAY (Warranty Period : Upto 30 months from the date of supply
632	SECR	182447 27-03-24	75030135	Set of flexible reinforced rubber pipe to Specn.SAE-100 R1 suitable for working pressure 20 Kg for VCB/DJ WITH 3/8" metallic swivel nuts at both ends. The metallic nut should confirm to ISS-226 GI. Coated. Set consists of 2 items, 2 Nos as below size of pipe I. OD-17.5mm, ID-8.0mm length 610mm Qty.1 No II. OD-17.5 mm, ID8.0mm length 254mm Qty.1 No
633	SECR	198578 11-10-24	75403043	Fire Retardant vinyl coated upholstery fabric (Artificial leather) for economic coaches color purple violet RAL -4007 with width 127 to 132 CMS, conforming to RDSO STR No. RDSO /2008 /CG/-07 REV -01 OF September 2023 in rolls of 30 meters. (Warranty Period : Up to 54 months from the date of supply)
634	SECR	175974 01-01-24	75320356	Rubber Sealing for cover plate as per Drg. No. CG-14054, Alt-3, Item No-14
635	SECR	175965 01-01-24	75320370	Sealing Rubber (for S trap 100 mm interface) as per Drg. No. CG-14095 alt 2.
636	SECR	175960 01-01-24	75320381	Sealing Rubber as per Drawing No. CG-16035.

637	SECR	175957 01-01-24	75320230	Grooved Rubber Profile for safety strap of retention tank as per drawing-No. ICF/SK3-6-3-201 Alt.-Nil or Latest
638	SECR	175956 01-01-24	75030093	Rubber Hose Nominal Dia:70 MM, Type- B Length=375 MM to IS 14933-2001 .As per DRG.No.16008 Item No. 4 Alt-2.
639	SECR	175854 30-12-23	75030081	Rubber Hose for S - Trap Arrangement nominal dia (Bore) 70 MM and length 225 MM with one side end tapered to nominal dia 45MM colour black as per IS : 14933 - 2001 type - B with latest amendment along with stainless steel (AISI304) Hose Clamp size 80MM to IS : 4762 : 2002 with latest amendment.
640	SWR	5521 23-05-17	75203467	Green Colour Biodegradable Disposable garbage Bag of size 40 X 45 cms with 20 microns thick of both side printing in single colour (Matter enclosed in Annexure) (As per material specification, the raw material of the bag is plastic which comes under major group 75. This material specification has been provided by Railway Board vide Annexure-I of letter No.2015/M(C)/165/1, dated.22.05.2015. This item is linked to the mission "Swachh Rail Swachh Bharat". Hence, may please allot UPL under 75 group for this item at the earliest please)
641	SWR	10421 21-09-17	75100058	Canvas Waterproof Bag Size L-20" X H-18" X W-18" . Canvas should be made of Cotton & Polyester composition/Mix, Check Weaves, Thickness 1mm, Colour Grey or Dark Green as per Sr.DME/C&W/UBL Drg No.L-17/01/16 enclosed.
642	SWR	20213 13-03-18	56110029	PVC Insulated, Underground Armoured, Unscreened Power cable Copper of Size 3 Core X 10 Sq.mm as per Specification.No. IRS:S-63/2007 Amdt No.3 or latest & IS:1554 (Part-I).
643	SWR	57904 14-06-19	56500324	Track feed battery charger with 110V AC input for charging 80Ah Secondary cells with 10 Amps output to 1 or 2 or 3 or 4 cells with one potential free contact. RDSO specification No. IRS:89-2013 with latest amendment.
644	SWR	94905 28-10-20	75030883	Spiral Hose having working pressure 690 Bar size: 3/8 inch Inside Diameter X 10 Metres length with end fitting, on both ends 3/8 inch female nut. Make: Poly hose/ Sparage/ Rasvin/ Forcstream.
645	SWR	100694 19-02-21	75610036	PVC Sleeving for Berth chain of 32 mm Outside Diameter X 0.8 mm thickness X 100 Mtr Lemgth (In a Roll). Material shall be confirming to IS: 11654, Part-1/1986. Colour: Brown.
646	SWR	100708 19-02-21	75610050	PVC Sleeving for Berth chain of 32 mm Outside Diameter X 0.8 mm thickness X 100 Mtr Lemgth (In a Roll). Material shall be confirming to IS: 11654, Part-1/1986. Colour: Blue.
647	SWR	125039 10-02-22	56158026	48V-200AH VRLA Battery, consisting of 24 nos of 2V/200ah cells in factory charged condition inserted in MS rack with inter cell & inter module connector as per RDSO specn. IRS:S:93/96 WITH amendment-1 or latest
648	SWR	125432 14-02-22	75613438	Fire Retardent PVC Sleeve of 46mm dia 0.8mm thick in continuous length per roll of 100 mtrs length colour Black. Material shall be confirming to IS:11654, Part-1/1986.
649	SWR	125421 14-02-22	75614467	Fire Retardent PVC Sleeve of 42mm dia 0.8mm thick in continuous length per roll of 100 mtrs length, colour Black. Material should be confirming to IS:11654, Part-1/1986.
650	SWR	191862 17-07-24	75328252	REST(RUBBER SHEET) FOR UNDERSLUNG WATER TANKS OF LHB COACHES TO DRG No CC63114
651	SWR	181912 22-03-24	75018329	V-BELT SIZE C - 109 CONFIRMING TO IS: 2494 [PT-1] 1994. FOR AUX - GEN / AXCITER GEN 100 V FOR 1400 HHP DEMU. V - BELT FROM THE SAME BATCH SHALL BE PACKED IN SETS OF 5 NOS. EACH. MAKE:- DUNLOP/ ECO DRIVE/ FENNER & PIX TRANSMISSION. Note : Material should be procured from OEM/ Authorized dealer only.
652	WCR	6467 05-07-17	76210054	Google Plain white (Safety eye wear) as per CRWS specification No 4 attached.
653	WCR	9243 23-08-17	76210066	Leather Leg Guard for welders as per CRWS specification No 21 attached
654	WCR	9235 23-08-17	76211538	Goggle light green for cutters as per CRWS specification No 05
655	WCR	9246 23-08-17	76218971	Maintenance free respirators for welders as per CRWS specification No 12
656	WCR	9230 23-08-17	76900010	Leather Apron for Welders as per CRWS Specification No 19 attached
657	WCR	15491 11-01-18	75100060	LEATHER HAND GLOVES AS PER CRWS SPECN.No.07 OF DOCUMENT No.WI/SAFETY/006 (Rev.02) AS PER ANNEXURE ATTECHED.
658	WCR	10236 16-09-17	76011483	ELECTRODES CLASS N1 SIZE 4 X 450MM TO IRSM 28/12 APPROVED BY RDSO. The date of supply of the material should be within 60 days from the date of manufacture.
659	WCR	20287 13-03-18	56500660	Web detector receiving coil for single section digital axle counter CEL make (Phase Reversal Type), as per RDSO Spec. No. RDSO/SPN/177/2012 (ver.-3) however latest spec./amendment will be applicable at the time of procurement of material.
660	WCR	17618 15-02-18	76300043	1/16" NOZZLES TYPE-ANM FOR OXY-ACETYLENE MANUAL CUTTING BLOW PIPES, MAKE ADOR/L&T/ EASB TO: IS 7653-1975 OR LATEST.
661	WCR	17619 15-02-18	76010600	Welding electrode H3-B class size 4.00x350mm(Min life 35GMT)
662	WCR	17620 15-02-18	76014046	WELDING ELECTRODE SIZE 3.15 X 350 MM CLASS M -2 AS PER IRS: M - 28 - 12 WITH LATEST AMND.
663	WCR	9245 23-08-17	75908475	Welding Helmet for welders as per CRWS specification No 10 attached.
664	WCR	9228 23-08-17	75908451	Safety helmet as per CRWS specification No 17 attached.
665	WCR	23345 04-05-18	56150210	Low Maintenance Lead Acid Secondary Cell. 2 Volt, 80 AH. as per RDSO Spec.No. IRS:S-88/2004 or latest. 1 set consist of 12 nos cells along with maintenance tool kit.
666	WCR	9636 05-09-17	76904611	Face Shield As per CRWS specification No 06 attached
667	WCR	15593 13-01-18	76010090	Manual Metal Arc Welding Electrode Class-M1 Size 3.15 x350 mm long to IS-5206/2003 and IRS-M-28/2012 E 19-9 Rz6 (Heavy coated)
668	WCR	25704 13-06-18	56460016	Route LED Signal lighting unit,110VAC, retrofittable in existing CLS housing and compatible with AC LED ECR as per RDSO Specification No. RDSO/SPN/153/2011,Rev.4.1 draft or latest.
669	WCR	17476 12-02-18	75610036	PVC Sleeve ID-30mm , OD-33mm confirming to IS:1951 and color equivalent to RDSO/LKO sample code AL-NAC-03 of Vinyl Coated Upholstery Fabric for Non AC coaches.
670	WCR	57392 07-06-19	56480891	ELECTRIC POINT MACHINE UNIVERSAL TYPE ROTARY LOCKING (AC IMMUNITY 160 VOLT AC) NON TRAILABLE TO OPERATE ON 110 VOLT DC COMPLETE WITH LOCK, DETECTOR CABLE TERMINATION BOX AND SLIDES FOR LOCK AND DETECTORS AS PER IRS-S-24/2002 (WITH LATEST AMENDMENTS IF ANY)
671	WCR	68559 25-09-19	76116220	SOLID MIG/MAG WELDING FILLER WIRE, CLASS VI SIZE 1.2 MM (SPEC.NO.IRS M-46/13 WITH AMENDMENT NO.1 GRADE ER 308 L AS PER AWS:A5.9-10)IN SPOOL OF 12.5 KGS/ROLL

672	WCR	48524 14-03-19	76114030	Copper Coated solid filler wire class IV, Size 1.2 mm, for MIG/MAG welding as per AWS code SFA5.28 ER80SG
673	WCR	36508 12-11-18	75908335	Steel wire reinforced vinyle hose 40 mm as per RCF Drg No CC-71248 item No 5, material confirming to IS-9537 (part-5)2000
674	WCR	84642 30-04-20	56509923	Cartridge fuse 4 Amp non deteriorating type low voltage electric fuse for Rly. Signalling rated current 4 Amp rated voltage 240 Volt AC/DC confirming to spec. No. IRS.S.78/92
675	WCR	84684 30-04-20	56301571	Supply of Electric Point Machine [Rotary locking Type] 110 V DC operations, [AC Immunity 160V] NON-TRAILABLE, complete with lock Detector, cable termination box and slides for lock and detector. As per RDSO Specification No. IRS: S-24/2002 with amendment-1 or latest. Requirement of point machine is 143 mm throw only as per RDSO Drg. No. RDSO/S-10800.
676	WCR	93029 29-09-20	75400080	HPL Sheet 1.2x1220x2440 MM Shade RAL-9006 MATT FINISH, GLOSS VALUE 10-12 AT 45 DEGREE as per MDTS-086 REVISION-01, Brown paper should be provided between adjacent layers (Finish Side Only) to avoid scratches.
677	WCR	93189 01-10-20	75320150	Rubber sheet for pasting on UIC vestibule of Size-1 Meter x 1 Meter x 2mm thick, material confirming to RDSO Specn. No. RDSO/2007/CF-05 WITH AMND. SLIP No. -5 of AUGUST-2016
678	WCR	93035 29-09-20	75320230	Grooved Rubber Profile for safety strap of retention tank as per drawing-No. ICF/SK3-6-3-201 Alt.-Nil or Latest
679	WCR	99483 28-01-21	75030081	Rubber Hose for S - Trap Arrangement nominal dia (Bore) 70 MM and length 225 MM with one side end tapered to nominal dia 45MM colour black as per IS : 14933 - 2001 type - B with latest amendment along with stainless steel (AISI304) Hose Clamp size 80MM to IS : 4762 : 2002 with latest amendment.
680	WCR	99484 28-01-21	75030093	Rubber Hose for S - Trap Arrangement as per drawing no.CG-16008 item-4, Alt.-2 nominal dia (Bore) 70mm and length 375mm with one side end tapered to nominal dia 45mm colour Black. Material as per IS:14933-2001 type B with latest amendment.
681	WCR	110707 02-08-21	75613438	PVC FLOORING ROLL 2X1850X14000MM with PVC welding Electrode wire dia 2MM of same colour shade and length, COLOUR AS PER SAMPLE NO. NACFLG-02, for LHB coaches as per specification No. RDSO/2006/CG-12 REVISION 1 WITH AMENDMENT SLIP NO.3 OF AUGUST 2016 and corrigendum No. 1 of June 2015 or latest. The material shall be procured from approved sources only.
682	WCR	132370 18-05-22	76901828	Half Face Piece Silicon Respirators as per CRWS specification WI/SAFETY/006 specification No 14.
683	WCR	167902 23-08-23	76010594	MANUAL METAL ARC WELDING ELECTRODES, DIA 4.0 MM, CLASS M4, TYPE OF COATING HEAVY Mati & Spec. Confirming SPECN.
684	WCR	156160 18-03-23	76210030	Gas Cutter (Nozzle Mixing type cutting blow pipe with LPG Nozzle) (Nozzle size -B - 3/64") to IS:7653/1975, Cutting Capacity - 30 mm thick MS plate, Type of Cutter - Nozzle mixing table, Angle head forged brass, Body - Forged Brass, Pipe - Seamless stainless steel, Handle & Control Knob - Metallic to ensure longer life, Make :- ADOR, ESAB, L&T SWC, Messers or similar.
685	WCR	173190 10-11-23	75350038	Flexible Polymer Reinforced Thermoplastic Hose for suction and delivery lines as per IS 15265: 2003, ID-75mm and minimum thickness 5mm.
686	WCR	173070 09-11-23	75324179	SEALING RUBBER AS PER DRAWING NO.CG 16035
687	WCR	192361 24-07-24	75200028	TOOL KIT BAG for track maintainers - Material used - matte Nylon -1680 Black, Red & Orange color, canvas for lining. as per specification annexure attached.
688	WCR	174430 07-12-23	75610127	Flexible polyvinyl chloride (PVC) flooring sheet of heterogeneous type in length of 14000mm, width 1620mm and thickness 2mm, Colour, shade and pattern WC-Brick Red along with 2mm dia PVC electrode of same shade and length confirming to RDSO specification No. RDSO/2006/CG-12(Rev-01 of Aug 08 or latest with 3 Amendments-Last Amendment no.3 issued in August-2016 or latest & Corrigendum No.1 of June 2015 or latest.
689	WCR	185465 03-05-24	75400121	Vinyl Coated Upholstery Fabric for Humsafar coaches (Chocolate browny) (The colour, shade and pattern of this material shall be as per approved Sample or as agreed between the purchaser and supplier) As per RDSO Spec No. RDSO/2008/CG-07, (Rev 3 of Aug 08 with 5 amendments or latest.
690	WCR	209742 19-02-25	75034888	Hood Guard for water Ingress Protection . Size 10" X 20 metres Length, thickness 0.30 +/- 0.08 mm, Tensile Strength & Elongation confirming to IS:7809 . Tape should be Water Resistance ,Oil Resistance, Alkalic Resistance. IS 7809 Part-III Sec 2 : 1981
691	WCR	210500 25-02-25	75327326	Densified Thermal Bonded Polyester blocks for single seat size- 55 x 490 x 600 mm , item No. 4 as per ICF Drg. No- SCN6-6-1-610, Alt-u/2 and conforming to RDSO Spec. No. C - K607 Rev. 2 of Dec 2015 with amndt. 1 of Aug'2016.
692	WCR	210163 21-02-25	75320400	Chemical (Acid Alkali) Resistant hand gloves made out of beetadierrce Achryenetril Rubber with fine gapping size large (No. 10) green colour. One sample should be got approved before bulk supply.
693	WCR	191616 13-07-24	75350063	Corrugated Flexible PVC drainage Pipe, thickness- 2mm having transition fit to item no. 1 (Dia-27mm) to drawing no. C/SK(Misc)-070 in roll length of 30 meters (Commercial quality).
694	METRO	29777 03-08-18	56151410	48 V/200 AH SMF secondary cells for S & T Installations, IRS:S-93/96 (A) with latest amendment
695	METRO	29773 03-08-18	56158038	65 AH/12 VOLT SMF SECONDARY CELLS FOR S&T INSTALLATIONS.
696	METRO	29761 03-08-18	56150040	VALVE REGULATED (SEALED) LEAD ACID STATIONARY BATTERY FOR S&T INSTALLATIONS - 12 V/120 AH,RDSO SPEC NO. IRS:S-93/96 (A)
697	METRO	29757 03-08-18	56150120	Valve Regulated (Sealed) Lead Acid Stationary battery for S &T installations -2V /120 AH,RDSO Spec. No. IRS:S-93/96(A)
698	METRO	29743 02-08-18	56150106	Low Maintenance Lead Acid Stationary secondary cells for S&T installations -2V/120AH,RDSO Spec. No. IRS:S-88/2004
699	METRO	29740 02-08-18	56150090	Low Maintenance Laed Acid Stationary secondary cells for S & T installations -2V/200AH,RDSO Spec No. IRS:S-88/2004
700	METRO	29721 02-08-18	56158014	Valve Regulated (Sealed) Lead Acid Stationary Battery for S & T installation - 2 V/200AH, RDSO Spec No. IRS:S-93/96(A)
701	METRO	27815 11-07-18	75030032	HOSE FOR MOTOR COMPRESSOR AS PER KBI PART NO.C148407 FOR AC RAKES OF KOLKATA METRO
702	METRO	33886 03-10-18	75050031	INSULATING RUBBER CAP FOR TRCC OF AC RAKES AS PER METRO RAILWAY'S DRAWING NO. MR/POH/AC/0-015
703	METRO	32179 13-09-18	75326930	CUSHION RUBBER FOR TRCC AS PER M.RLY' DRAWING NO. MR/POH/AC-0-005 FOR AC RAKES OF KOLKATA METRO

704	METRO	33985 04-10-18	75500024	SET OF DIFFERENT TYPES OF RUBBER GASKETS AND RUBBER GROOMETS FOR TRACTION MOTOR OF AC RAKES OF KOLKATA METRO AS PER ANNEXURE ENCLOSED.
705	METRO	46226 14-02-19	75500036	SET OF GASKET FOR CSC OF AC RAKES OF KOLKATA METRO. ONE SET CONSIST OF: (I) GASKET FOR CSC COVER AS PER DRAWING NO. MR/POH/7-5-282 - 4MTRS./SET. (II) GASKET FOR GEAR BOX AS PER DRAWING NO. MR/POH/7-5-0284- 01NO./SET. NB: MATERIAL TO BE PROCURED FROM RDSO/ICF/CLW/DLW/RCF APPROVED SOURCES FOR SIMILAR ITEMS.
706	METRO	74985 20-12-19	75030159	MR/ BP HOSE FOR BHEL-AC RAKES OF KOLKATA METRO AS PER METRO RAILWAY'S DRAWING NO. MR/POH/AC-3-5-005 WITH LATEST ALTERATION, IF ANY.
707	METRO	74988 20-12-19	75050080	INSULATING RUBBER PAD FOR TRCC OF BHEL-AC RAKES OF KOLKATA METRO AS PER METRO RAILWAY'S DRAWING NO. MR/POH/AC-0-014, WITH LATEST ALTERATION, IF ANY.
708	METRO	99567 30-01-21	75030070	SET OF DIFFERENT TYPES OF RUBBER HOSES FOR MR-300 SERIES AC RAKES OF KOLKATA METRO. EACH SET CONSISTS OF THE FOLLOWING ITEMS. 1]3/8" ID HOSE AS PER EN853-1SN FOR PISTON VALVE AS PER DRG.NO.MR/POH-3-5-0119 ALT-A OR LATEST, IF ANY (ITEM NO.1) WITH CONNECTOR/NIPPLE AS PER DRG. NO. MR/POH-3-5-0120 -16NO. 2]1/4" ID HOSE (B16) AS PER EN853-1SN FOR SERVICE & PARKING BRAKE (BOGIE TO BODY) AS PER DRG.NO.MR/POH-3-5-0119 ALT-A OR LATEST, IF ANY (ITEM NO.2) WITH CONNECTOR/NIPPLE AS PER DRG.NO.MR/POH-3-5-0120 -16NO. 3]1/2" ID HOSE (C04) AS PER EN854-2TE FOR SERVICE BRAKE TBU AS PER DRG.NO. MR/POH-3-5-0119 ALT-A OR LATEST, IF ANY (ITEM NO.3) WITH CONNECTOR/NIPPLE AS PER DRG. NO.MR/POH-3-5-0122 ALT-a OR LATEST- 64NO. 4]1/2" ID HOSE AS PER EN853-1SN FOR 20LTRS RESERVOIR & AIR BELLOW AS PER DRG.NO.MR/POH-3-5-0119 ALT-A OR LATEST, IF ANY (ITEM NO. 4) WITH CONNECTOR/NIPPLE AS PER DRG.NO.MR/POH-3-5-0122 ALT-a OR LATEST- 80NO. 5]1/4" ID HOSE (C05) AS PER EN854-2TE FOR SERVICE & PARKING BRAKE TBU AS PER DRG.NO.MR/POH-3-5-0119 ALT-A OR LATEST, IF ANY (ITEM NO.5) WITH CONNECTOR/NIPPLE AS PER DRG.NO.MR/POH-3-5-0120 -32NO. 6]3/4" ID HOSE AS PER EN853-1SN FOR ASS INCOMING HOSE AS PER DRG.NO. MR/POH-3-5-0119 ALT-A OR LATEST, IF ANY (ITEM NO.6) WITH CONNECTOR/NIPPLE AS PER DRG. NO. MR/POH-3-5-0121 -16NO. 7]5/8" ID HOSE (B13) AS PER EN854-2TE FOR BOGIE TO BODY BC PIPE LINE AS PER DRG.NO.MR/POH-3-5-0119 ALT-A OR LATEST, IF ANY (ITEM NO.7) WITH CONNECTOR/NIPPLE AS PER DRG.NO.MR/POH-3-5-0121 -16NO. 8]3/8" ID HOSE AS PER EN853-1SN FOR PRESSURE GAUGES (MR/BP & AR/BC) WITH CONNECTOR/NIPPLE AS PER DRG.NO.MR/POH-3-5-013 -12NO. 9]1" ID HOSE (A02) SAE 100R7 FOR VV-120 MOTOR COMPRESSOR WITH CONNECTOR/NIPPLE AS PER DRG.NO.MR/POH/AC-3-5-014 -4NO. 10]HOSE AND HOSE CLAMP FOR VV-120 COMPRESSOR AS PER DRG.NO.MR/POH/AC-3-5-016 [01PACKET CONSISTS OF HOSE L-60 (ITEM-1 OF DRG)-01NO, HOSE L-40 (ITEM-2 OF DRG)-1NO AND HOSE CLAMP (ITEM-3 OF DRG)-4NOS] -4PACKETS.
709	CLW	1530 07-02-17	76214590	LENS COLOURED GLASS (3+1/4)"X(4+1/4)" CONFORMING TO DIN-13
710	CLW	9321 28-08-17	75207953	Leather Gauntlet for MIG Welders for protection of heat absorption and radiation.CLW's Spec no-MSO/33/Specn/V-02/MIG Dated-15.03.11,IS:2573-1986.
711	CLW	20850 22-03-18	75544878	Manila Rope 24 mm dia.Length 220 Mtrs. Conforming to IS:1084/1994,Make-Delta Rope Manufactures Co.
712	CLW	25929 19-06-18	75900051	Industrial Safety Leather Shoe,Type-A (Male) with Steel Toe cap Design A Low shoe as per CLW Spec No. MSO/33/Tech/Specification/Rev.4 dated 21.07.14 and MSO/09 dated 28.10.14 and conforming to IS 15298 (part 2) 2011.
713	CLW	25931 19-06-18	75900040	Industrial Safety Leather Shoe,Type-B (Male) with Non- conductive Fibre Toe as per CLW Spec No. MSO/33/Tech/Specification/Rev.4 and MSO/09 dated 28.10.14 and conforming to IS 15298 (part 2) 2011.
714	CLW	25932 19-06-18	75900038	Industrial Safety Leather Shoe for Steel Foundry Type-N,heat resistant sole with Steel Toe as per CLW Spec No.MSO/33/Tech/Specification/Rev.4 dated 21.07.14 and MSO/09 dated 28.10.14 and conforming to IS 15298 (part 2) 2011.
715	CLW	25933 19-06-18	75908992	Ladies Industrial Safety Leather Shoe Type-A with Steel Toe as per CLW Spec No. MSO/33/Tech/Specification/Rev.4 dated 21.07.14 and MSO/09 dated 28.10.14 and conforming to IS 15298 (part 2) 2011.
716	CLW	25934 19-06-18	75908980	Ladies Industrial Safety Leather Shoe Type-B with Non- Conductive Fibre Toe as per CLW Spec No. MSO/33/Tech/Specification/Rev.4 dated 21.07.14 and MSO/09 dated 28.10.14 and conforming to IS 15298 (part 2) 2011.
717	CLW	25945 20-06-18	75901201	Half Face Mask Set (Consisting of Half Face Mask-01 no,Cartridge-04 nos.Pre-Filter Retainer-04 nos,Pre-Filter-120 nos) Specification No:IS:9473:2002.
718	CLW	29246 28-07-18	76100042	SAW WIRE 2MM DIA SPECN.NO. AWS/SFAS/17ELB DIN-855754
719	CLW	31441 04-09-18	75908967	GAUNTLET,LEATHER (HOT MATERIAL HANDLING) RH+LH,350MM +/-5MM LG,IS:1187
720	CLW	31611 06-09-18	75900841	Worn Drive Hose Clip suitable for using 10mm bore hose to IS Specification IS-4762/1984.
721	CLW	31247 31-08-18	76218703	PRESSURE REGULATOR FOR GAS CYLINDER USE IN WELDING,CUTTING AND RELATED PROCESSES TO BE USED WITH GAS-ACETYLENE,NO OF STAGES IN REGULATOR TWO,PRESSURE GAUGES FITTED,02 OUTLETS VALVE.O&A: TWO STAGE ACETYLENE REGULATOR AS PER IS: 6901/2009.BRAND:SWC MAKE-"OWN".
722	CLW	34059 06-10-18	76100054	COPPER WELDING WIRE FOR MIG WELDING 1.6mm DIA,Spec.No.DIN-1733MTL-No.2
723	CLW	34050 06-10-18	75900294	ASBESTOS HAND GLOVES 18" RH & LH.
724	CLW	34336 12-10-18	76010107	Colour Glass of size:182mmx82.5mm for manual metal ARC WELDING Shade to 12DIN as per IS:5679/1-51179 .
725	CLW	50533 27-03-19	75038560	Nylon Double Braided Flexible Hose,Size:-ID:08 mm,OD:14 mm,Wall thickness:3 mm,IS:12492/1988.
726	CLW	50537 27-03-19	75038575	Nylon Double Braided Flexible Hose,Size:-ID:12 mm,OD:18 mm,Wall thickness:3 mm,IS:12492/1988.
727	CLW	50541 27-03-19	75050079	Nitrile Hand Gloves,Size:-12 inches.Super nitrile rubber green flock lined gauntlets with patterned grip-13", acid,alkali,oils chemical resistance,Weight:60 grams/ pair,Thickness-0.5 mm,as per EN-388:2003,EN-420: 2003,EN-374:2014,EN-374-1&2:203.

728	CLW	75387 24-12-19	75908451	Industrial Safety Helmet, Clw's Spec.No-MSO/33/Specification/V-03,Dated-28.04.18 and Conforming to IS: 2925/1984 or CE marked as per EN-397.
729	CLW	163769 29-06-23	76218375	High Aluminium Nozzle 4 inch dia, Drg/SPEC.No-SFM/1733/MD
730	CLW	162775 16-06-23	76450016	Graphite Electrode 10" for using 10/12/15 T Electric Arc Furnace for Melting Shop. Spec. SF/SPEC/GRAPHITE ELECTRODE/EAF , IS-1052
731	CLW	164785 17-07-23	76210145	Nipple Nozzle and Nut, Drg/ Spec no: SFM-1471
732	CLW	166111 03-08-23	76450028	ELECTRODES 10 INCH 250X1800MM GRAPHITE WITH NIPPLE FOR USE IN ELECTRIC ARC FURNACE Spec: SF/SPEC/GRAPHITE ELECTRODE/ELF
733	BLW	34601 22-10-18	76150010	COMPRESSION TYPE ALLUMINIUM TABULAR TERMINAL CONFORMING TO IS:8309:1993 DESIGNATION CAA-150-WITH 16.2MM HOLE FOR STUD
734	BLW	34598 22-10-18	76217528	TIP ADAPTER TO BE USED IN ESAB MAKE ARGON-CO2 WELDING TORCH PSF 405. MAKE: ESAB OR PROFAX
735	BLW	87958 30-06-20	75909583	PLASTIC BAG FOR HHP POWER ASSEMBLY, Length-55 Inch, width-24 Inch and Thickness of plastic sheet-0.125MM -0.150MM Note :- (1) Soft and strong plastic will be used. (2) Sample bag must be got approved by the user before supply of material.
736	BLW	88885 16-07-20	75403237	TRANSPARENT POLYTHENE SHEET , SPEC.- Roll thickness-0.125MM minimum, Width-6 feet for wrapping POWER ASSEMBLY. NOTE:-before full supply of item, supplier must get approval of the sample by user.
737	BLW	141935 28-09-22	76300079	Kit for Nozzle gas cutting for cutting of ms plate (i) Model no-6290- 1VAX , Qty 01 no (ii)Model no-6290- 2VAX, Qty- 01 no (iii)Model no-6290- 3VAX, Qty - 01 no (iv)Model no-6290- 4VAX, Qty- 01 no (v)Model no-6290- 5VAX, Qty- 01 no
738	BLW	180722 07-03-24	75900555	Technician Tool Bag Size 16" to 21" . Open mouth. A top handle carrying with shoulder strips provide easy carry by hand or shoulder and having multiple internal and external pockets with top zipped open mouth. Material- 600D Polyester. Make: Stanley Black and dekkar, Proskit, Gedore, Bluepoint, Hazet
739	BLW	209537 17-02-25	76210753	SILVER SOLDERING FLUX IN WHITE POWER FORM HAVING PH VALUE 07-09 ACTIVE AT AND ABOVE 550 DEGREE CELSIUS TILL 850 DEGREE CELSIUS. (PLW EXISTING PL NO. 76210753)
740	BLW	209624 18-02-25	76115690	COPPER COATED CO2 WELDING WIRE DIA- 1.2 MM AS PER DRG. NO. NOTE: FIRMS ARE REQUIRED TO MENTION SHELF LIFE OF AS PER SPEC. NET WEIGHT PER SPOOL NOT MORE THAN 12.5 KGS TO IRS M-46-03 FOR CLASS-1 (PLW EXISTING PL NO.76115690)
741	BLW	209539 17-02-25	76115057	SILVER BRAZING FOIL SIZE 0.25 X 75 X 300 MM (PLW EXISTING PL NO. 76115057)
742	BLW	209509 17-02-25	76115045	SILVER BRAZING ROD SIZE SIZE 1.6 X 500 MM (PLW EXISTING PL NO. 76115045)
743	ICF	1526 07-02-17	76217322	CONTACT TIP HOLDER FOR CO2 TORCHES BENZIL MB 40KD NO. 14208015
744	ICF	19434 07-03-18	75320149	SOLID RUBBER PACKING, SIZE: 25x34x475, EPDM RUBBER, COLOUR-BLACK, SHOREHARDNESS=65 +OR-5 TPL-75990076
745	ICF	53052 15-04-19	76150021	LONG LIFE CONTACT TIP CuCrZr, 1.2MM, M6 FOR NM 36 OF NUTECSYS MAKE ANDPART NO: 140N0444 OR TBI 360 OF TBI MAKE AND PART NO:340P123069 OR MB36HD OFABICOR BINZEL .ICF TPL NO:01769818480101
746	ICF	55468 13-05-19	75320216	BRAIDED RUBBER HOSE NB63 X1400MM TO IS 444-1987,TYPE-2. F/400/UL/2019-3-26/56/2744
747	ICF	53029 15-04-19	76010132	2.4MM DIA NON-CONSUMABLE TUNGSTEN ELECTRODE, 2% THORIATED ISO:6848:2004/AWS5.12, TYPE-Wth 20(RED), SIZE 2.4MM DIA X 150MM.ICF TPL NO:12769821910101
748	ICF	36812 14-11-18	75320228	HOSE 42X5P, L=240MM TO SPECN. DIN 73411.TPL NO:75990003. only this full description.
749	ICF	65101 28-08-19	76217383	NOZZLE OF 16MM FOR NM 36 OF NUTECSYS MAKE AND PART NO:145N0078 OR TBI 360OF TBI MAKE AND PART NO.345P012010 OR MB36KD OF ABICOR BINZEL MAKE AND PARTNO.145.0078 FOR MIG TORCHES.TPL NO:01769818850101
750	ICF	67541 16-09-19	76210080	NOZZLE OF 16MM FOR NM 36 OF NUTECSYS MAKE AND PART NO:145N0078 OR TBI 360 OF TBI MAKE AND PART NO.345P012010 OR MB36KD OF ABICOR BINZEL MAKE AND PART NO.145.0078 FOR MIG TORCHES.tpl no:76981885
751	ICF	40755 21-12-18	76210091	PORTABLE DIESEL ALTERNATOR CUM WELDING SET HAVING AUXILARY POWER CAPACITY OF 3KVA, 230V, SINGLE PHASE AC SUPPLY, 50HZ, AND WELDING CAPABILITY OF 175A DC(MIN) WITH DUTY CYCLE OF 60%. THE ENGINE SHALL BE AIR-COOLED, PETROL START AND PETROL RUN WITH AUTO START OR MANUAL START FEATURES. THE PORTABLE WELDING CUM GENSET SHALL GENERALLY CONFIRM TO IS:2635 (LATEST) AND ALTERNATOR SHALL CONFIRM TO IS: 4722 (LATEST). THE PORTABLE WELDING CUM GEN-SET SHALL MEET THE FOLLOWING REQUIREMENTS. 1)ENGINE-PETROL START AND PETROL RUN, AIR-COOLED 2)START MODE-AUTO OR MANUAL3)AC GENERATOR OUTPUT-230V SINGLE PHASE, 50HZ, 3KVA 4)WELDING CAPABILITY-175A(MIN), 65 V DC WITH 60% DUTY CYCLE 5)SUITABLE FOR WELDING RODSIZE-4 MM (MAXIMUM) 6)INSULATION CALSS-F 7)MECHANICAL PROTECTION-IP238)AMBIENT TEMPERATURE-UPTO 55 DEG C 9)ALTITUDE-1000M 10)DRY WEIGHT-100KG (MAXIMUM) 11)OVERALL DIMENSION(LXWXH)-750X550X675 MM (MAXIMUM) 12)TROLLEY HAVING WHEELS AND HANDLES FOR EASY MOVEMENT 13)WELDING CABLE 25 SQ MM OF 5M LENGTH WITH WELDING HOLDER AND ACCESSORIES 14) MODEL: SIMILAR TO GE-W 5500R OF M/s. HIMALAYAN POWER MACHINES NOTE:- 1)THE SUPPLIER SHALL PROVIDE AFTER SALES SERVICE ALL OVER INDIAN RAILWAYS. 2)MAINTENANCE MANUAL SHALL BE SUBMITTED ALONG WITH SUPPLY.TPL NO:39459902070101
752	ICF	113333 30-08-21	75320241	SOLID RUBBER PACKING, SIZE: 25x34x600 TO SPECN-MDTS-30EPDM RUBBER, COLOUR-BLACK, SHORE HARDNESS= 65±5
753	ICF	118584 18-11-21	75616040	2MM THICK FLEXIBLE HOMOGENEOUS PVC FLOORING SHEET OFSIZE: 2 x 1620 x 16000 MM CONFORMING TO SPECN. ICF/MD/SPEC-387,REV.NIL. COLOUR: ICF APPROVED COLOUR.THE SCOPE OF SUPPLY SHALL COVER A LENGTH OF20 METRES OF 3MM DIA COLOUR PVC ELECTRODE PER ROLL OF 16000MM LENGTH OF PVC SHEET. ELECTRODE COLOUR SHADE SHOULD MATCH THE COLOUR OF PVC FLOORING SHEET.

754	ICF	118599 19-11-21	75610097	2MM THICK FLEXIBLE HOMOGENEOUS PVC FLOORING SHEET OF SIZE: 2 x 1620 x 16000 MM CONFORMING TO SPECN. ICF/MD/SPEC-387, REV. NIL. COLOUR: ICF APPROVED COLOUR. THE SCOPE OF SUPPLY SHALL COVER A LENGTH OF 20 METRES OF 3MM DIA COLOUR PVC ELECTRODE PER ROLL OF 16000MM LENGTH OF PVC SHEET. ELECTRODE COLOUR SHADE SHOULD MATCH THE COLOUR OF PVC FLOORING SHEET.
755	ICF	123011 18-01-22	76214606	1.2mm thick CO2 solid coil wire , Grade: AWS A5.28 ER80S - G Solid Wire
756	ICF	141957 28-09-22	75103916	PLASTIC TARPULIN: CROSS LAMINATE MULTI LAYER PROTECTIVE TARPULIN, U.V STABILISED, 100% WATER PROOF, 120GSM, TO IS-14611, FINISH SIZE 18 FEET X 15 FEET WITH MINIMUM 10 EYELETS PER SHEET AND 5 FEET LENGTH 6MM NYLON WIRE ROPE PER EYE LET FOR 10 EYELETS
757	ICF	150566 05-01-23	76904544	EARTH CLAMP (GROUND) C TYPE 600 AMPS at 60% AND 300 AMPS at 100% DUTY FACTOR AS PER EN 60974 13 CESUITABLE FOR 70 to 95 SQ Welding cable. Model EC CT 600 Make SWPS or ESAB or ADOR or MESSER.
758	ICF	160847 24-05-23	75050109	CUT RESISTANT SAFETY GLOVES TO SPECIFICATION NO ICF/F/SF/SPEC01 REV NO 0
759	ICF	173636 22-11-23	76211678	ONE NUMBER OF SAFETY COVER GLASS (LASER MECH-MAKE) FOR LASER CUTTING AND WELDING MACHINE TO INV NUMBER 1417
760	ICF	195691 30-08-24	75904287	SUPPLY OF HPL SHEET 3X1220X2440MM SHADE RAL-9006, MATT FINISH, GLOSS VALUE 10-12 AT 45 DEGREE, AS PER SPECIFICATION MDTs-086 REV- 1.
761	ICF	209502 17-02-25	76210558	GAS SHIELDED FLUX CORED STAINLESS STEEL WIRE ELECTRODE TO SIZE DIA 1.2MM TO GRADE AWS A5.22 E309LMoT 1-1 THE WEIGHT OF THE WIRE ELECTRODE IN THE SPOOL SHALL BE 12.5 KGS NET. THE BRAND SHALL BE APPROVED BY RDSO FOR THE GRADE SPECIFIED
762	RCF	47001 26-02-19	75613438	PVC FLOORING ROLL 2X1620X14000MM, COLOUR AS PER SAMPLE NO. NACFLG-02 FOR CONVENTIONAL NON-AC COACHES
763	RCF	47013 26-02-19	76904398	STAINLESS STEEL WIRE 1.2 MM DIAMETER IN SPOOL OF WT. 12.5 KGS. (APPROX) AND SHALL BE ANNEALED, DRY DRAWN AND MATT FINISH. RUNNING PERFORMANCE SHALL BE SATISFACTORY WHILE WELDING.
764	RCF	47022 26-02-19	76110023	COPPER COATED CO2 WELDING FILLER SOLID WIRE SIZE 1.2MM, SHELF LIFE OF MATERIAL NOT TO BE LESS THAN ONE YEAR FROM THE DATE OF MANUFACTURING.
765	RCF	47026 26-02-19	76904404	STEEL WIRE 1.2MM IN SPOOL OF WEIGHT APPROX. 15 KG.
766	RCF	47028 26-02-19	75904287	HPL SHEET 3X1220X2440MM SHADE RAL-9006, MATT FINISH, GLOSS VALUE 10-12 AT 45 DEGREE
767	RCF	47006 26-02-19	75403286	LP SHEET 3X1220X1830MM, SHADE AS PER SAMPLE NO. NAC-SP05
768	RCF	189594 14-06-24	75615277	PVC FLOORING SHEET 2X1620X16000 MM COLOUR: RDSO APPROVED SAMPLE NO. ACFLG-01 WITH PVC ELECTRODE 3 MM DIA LENGTH OF 20 METRES PER ROLL OF 16000 MM LENGTH PVC SHEET
769	RCF	209885 20-02-25	75403651	VINYL COATED UPHOLSTERY FABRIC TO SPECN. NO. RDSO/2008/CG-07 , REV-01 OF WIDTH 1270 MM IN CONTINUOUS ROLL LENGTH OF 30 METRES MINIMUM. THE EXCESS LENGTH SHALL BE MULTIPLES OF 5 MTRS AND MAXIMUM LENGTH OF 40 MTRS. COLOUR: AS PER RDSO APPROVED SAMPLE No. ALNAC-03.
770	RWF	30341 16-08-18	75908311	25 TON AXLE JOURNAL HDPE END COVER TO RWF DRG NO. RWF-P-082.
771	RWF	30340 16-08-18	75908578	HDPE BODY PACKING FOR 25 TON AXLE AS PER RWF DRG. NO. WAP/SK/MA-334 ALT 'd'.
772	RWF	30336 16-08-18	75900075	1. Nomenclature: Ladies safety foot wear size: 6. 2. Basic requirements: (i) The ladies safety shoes shall be made of corrected grain (plain) leather, black in colour with full vamp P U (Polyurethane) Sole Oil and Acid Resistant, slip on sable design, Generally conforming to IS:15298 (Part 1 & 2): 2002 (ii) The fibre toe cap should be provided. (iii) The safety shoes shall be meant for general industrial purpose use (for Ladies use). (iv) The firms(s) submitting their offer shall be ISO 9000 certified firms(s) and a certificate in this regard must be submitted along with offer, failing to fulfill this requirement, the offer will be ignored. 3. Components requirements: (i) The thickness of Upper leather shall be 2.0 +/- 2mm. (ii) One piece leather shall be used for Upper. (iii) Chrome tanned softy leather lining shall be used for quarter. (iv) Cushioned lining shall be used for Vamp lining. (v) Cushioned padded Collar (12mm Min) shall be provided. (vi) Socks padding of 3 mm (min.) (vii) The Safety Shoes shall withstand Electrical Shock proof up to 15 KV. 4. Sole Requirements and material: (i) P U single density sole black in colour (ii) The sole should be anti slip design with cleats depth 1.5mm (Min.) (iii) The upper portion and sole of safety shoes shall be fixed together with DIP (Direct Injection Process) method/Stock on process. (iv) The sole should have hardness of 50 to 60 shores. 5. Thread: Nylon / Polyester thread of min. breaking strength 3.5kg. 6. Tie Attachment: Single strap with one Velcro strip (3" long) 7. Size: The size of shoes shall be as per English system. 8. General Requirements: (i) Shoes size, Month and Year of manufacture, manufacturers inner sole toward Heel side. (ii) The shoes shall be packed and supplied in cardboard with indication of size of shoes.
773	RWF	30338 16-08-18	75909224	LLDPE CAP FOR LHB AXLES AS PER RWF DRG NO. RWF/P-84.

774	RWF	30335 16-08-18	75908750	1.Nomenclature: Ladies safety foot wear size: 8. 2. Basic requirements: (i) The ladies safety shoes shall be made of corrected grain (plain) leather, black in colour with full vamp P U (Polyurethane) Sole Oil and Acid Resistant, slip on sable design, Generally conforming to IS:15298 (Part 1 & 2): 2002 (ii) The fibre toe cap should be provided. (iii) The safety shoes shall be meant for general industrial purpose use (for Ladies use). (iv) The firms(s) submitting their offer shall be ISO 9000 certified firms(s) and a certificate in this regard must submitted along with offer, failing to fulfill this requirement, the offer will be ignored. 3. Components requirements: (i) The thickness of Upper leather shall be 2.0+/- 2mm. (ii) One piece leather shall be used for Upper. (iii)Chrome tanned softy leather lining shall be used for quarter. (iv) Cushioned lining shall be used for Vamp lining. (v) Cushioned padded Collar (12mm Min) shall be provided. (vi) Socks padding of 3 mm (min.) (vii) The Safety Shoes shall withstand Electrical Shock proof up to 15 KV. 4. Sole Requirements and material: (i) P U single density sole black in colour (ii) The sole should be anti slip design with cleats depth 1.5mm (Min.) (iii) The upper portion and sole of safety shoes shall be fixed together with DIP (Direct Injection Process) method/Stock on process. (iv) The sole should have hardness of 50 to 60 shores.5. Thread: Nylon / Polyester thread of min. breading strength 3.5 kg. 6. Tie Attachment: Single strap with one Velcro strip (3" long) 7. Size: The size of shoes shall be as per English system. 8. General Requirements:(i) Shoes size, Month and Year of manufacture, manufacturers inner sole toward Heel side. (ii) The shoes shall be packed and supplied in cardboard with indication of size of shoes.
775	RWF	30334 16-08-18	75908256	SAFETY GLASSES WITH FOLDING SIDE MESH GUARD FITTED WITH ZERO POWER CLEAR TOUGHENED GLASSES." NOTE: 1.ONE NUMBER SAMPLE SHALL ACCOMPANY THE QUOTATION FAILING WHICH,THE OFFERS ARE LIABLE TO BE IGNORED 2.ZERO POWER TEST CERTIFICATE SHALL ACCOPANY WITH SUPPLY.
776	RWF	47138 28-02-19	76216020	FLASH BACKOXYGEN REGULATOR SIDE. MAKE: ESAB PART NO0700016554 (MODEL NO.FRT OXYGEN) OR MRSSER PART NO.MS04633 ARRESTOR FOR 87 (MODEL NO.DGN OXY) ONLY.
777	RWF	170166 26-09-23	75320265	LIGHT WEIGHT INDUSTRIAL SAFETY SHOES (ANKLE LENGTH)OF SIZE NO.6 WITH STEEL TOES, OIL/GREASE RESISTANT AND SKID PROOF SOLE OF DURABLE CONSTRUCTION SUITABLE FOR HEAVY METAL INDUSTRIES AS PER RWF SPECN.NO.RWF/M/SPECN-1/130/2022 ALT NIL DRG.NO. RWF/MISC/M-1288.
778	RWF	170165 26-09-23	75320277	LIGHT WEIGHT INDUSTRIAL SAFETY SHOES (ANKLE LENGTH) OF SIZE NO.7 WITH STEEL TOES, OIL/GREASE RESISTANT AND SKID PROOF SOLE OF DURABLE CONSTRUCTION SUITABLE FOR HEAVY METAL INDUSTRIES AS PER RWF SPECN.NO.RWF/M/SPECN-1/130/2022 ALT NIL DRG.NO. RWF/MISC/M-1288.
779	RWF	170164 26-09-23	75320289	LIGHT WEIGHT INDUSTRIAL SAFETY SHOES (ANKLE LENGTH) OF SIZE NO.8 WITH STEEL TOES, OIL/GREASE RESISTANT AND SKID PROOF SOLE OF DURABLE CONSTRUCTION SUITABLE FOR HEAVY METAL INDUSTRIES AS PER RWF SPECN.NO.RWF/M/SPECN-1/130/2022 ALT NIL DRG.NO. RWF/MISC/M-1288.
780	RWF	170163 26-09-23	75320290	LIGHT WEIGHT INDUSTRIAL SAFETY SHOES (ANKLE LENGTH) OF SIZE NO.9 WITH STEEL TOES, OIL/GREASE RESISTANT AND SKID PROOF SOLE OF DURABLE CONSTRUCTION SUITABLE FOR HEAVY METAL INDUSTRIES AS PER RWF SPECN.NO.RWF/M/SPECN-1/130/2022 ALT NIL DRG.NO. RWF/MISC/M-1288.
781	RWF	170157 26-09-23	75320307	LIGHT WEIGHT INDUSTRIAL SAFETY SHOES (ANKLE LENGTH) OF SIZE NO.10 WITH STEEL TOES, OIL/GREASE RESISTANT AND SKID PROOF SOLE OF DURABLE CONSTRUCTION SUITABLE FOR HEAVY METAL INDUSTRIES AS PER RWF SPECN.NO.RWF/M/SPECN-1/130/2022 ALT NIL DRG.NO. RWF/MISC/M-1288.
782	RWF	170156 26-09-23	75320319	LIGHT WEIGHT INDUSTRIAL SAFETY SHOES (ANKLE LENGTH) OF SIZE NO.11 WITH STEEL TOES, OIL/GREASE RESISTANT AND SKID PROOF SOLE OF DURABLE CONSTRUCTION SUITABLE FOR HEAVY METAL INDUSTRIES AS PER RWF SPECN.NO.RWF/M/SPECN-1/130/2022 ALT NIL DRG.NO. RWF/MISC/M-1288.
783	RWF	170154 26-09-23	75320344	LIGHT WEIGHT INDUSTRIAL SAFETY SHOES (ANKLE LENGTH) OF SIZE NO.12 WITH STEEL TOES, OIL/GREASE RESISTANT AND SKID PROOF SOLE OF DURABLE CONSTRUCTION SUITABLE FOR HEAVY METAL INDUSTRIES AS PER RWF SPECN.NO.RWF/M/SPECN-1/130/2022 ALT NIL DRG.NO. RWF/MISC/M-1288
784	PLW	37797 28-11-18	75050043	SAFETY HAND GLOVES USED FOR WATER SOLUBLE OIL TO HONEYWELL PART NO. 2232236 OR EQUIVALENT
785	PLW	37796 28-11-18	75050055	SAFETY HAND GLOVES USED FOR NEAT CUTTING OIL TO HONEYWELL PART NO. NF35F OR EQUIVALENT
786	PLW	37800 28-11-18	75050067	SAFETY HAND GLOVES USED FOR GENERAL PURPOSE TO HONEYWELL PART NO. 2232231OR EQUIVALENT
787	PLW	37952 01-12-18	75320162	PACKING RUBBER SIZE:-1.5X32X28.4 MM
788	PLW	46593 20-02-19	75030019	HOSE PIPE DIA 100MM, L=800 MM
789	PLW	106289 19-05-21	76110023	COPPER COATED CO2 WELDING WIRE, DIA:1.2 MM IN "MARATHON" PACK OF 250 KGS.
790	PLW	108040 24-06-21	76210108	SHIELD PART NO. 220992 COMPATIBLE TO PMX 105 PLASMA ARC CUTTING MACHINE.
791	PLW	108036 24-06-21	76210110	NOZZLES PART NO. 220990 COMPATIBLE TO PMX 105 PLASMA ARC CUTTING MACHINE.
792	PLW	108032 24-06-21	76210133	ELECTRODE PART NO. 220842 COMPATIBLE TO PMX 105 PLASMA ARC CUTTING MACHINE.
793	PLW	116320 18-10-21	76900046	PORTABLE ALTERNATOR CUM WELDING SET NOTE:- (1) OFFERED PORTABLE ALTERNATOR CUM WELDING SET TO COMPLY SALIENT FEATURES MENTIONED IN ANNEXURE (2) THE SUPPLIER SHALL PROVIDE AFTER SALES SERVICE ALL OVER INDIAN RAILWAYS DURING THE CODAL LIFE OF ITEM AND MAINTENANCE MANUAL SHALL BE SUBMITTED ALONG WITH SUPPLY.
794	PLW	142519 10-10-22	76217395	SWIRL RING PART NO.220857 COMPATIBLE TO POWERMAX 105 PLASMA ARC CUTTING MACHINE
795	PLW	142517 10-10-22	76217383	RETAINING CAP PART NO.220854 COMPATIBLE TO POWERMAX 105 PLASMA ARC CUTTING MACHINE
796	MCFRBL	41635 03-01-19	75616026	GLASS FIBRE REINFORCED EPOXY RESIN SHEET (GFRE) SIZE 1.5X1525X2440MM

797	MCFRB L	41637 03-01-19	75613438	PVC FLOORING ROLL 2X1620X14000MM, COLOUR AS PER SAMPLE NO. NACFLG-02 FOR CONVENTIONAL NON-AC COACHES
798	MCFRB L	41638 03-01-19	75613827	PVC FLOORING ROLL 2X1850X14000MM, COLOUR AS PER SAMPLE NO. ACFLG-01 FOR LHB AC COACHES
799	MCFRB L	41647 03-01-19	75401708	REXINE IN WIDTH OF 1270MM (COLOUR SHADE ALNAC-03)
800	MCFRB L	41650 03-01-19	76904404	STEEL WIRE 1.2MM IN SPOOL OF WEIGHT APPROX.15 KG.
801	MCFRB L	41646 03-01-19	75320017	RUBBER GROMMET WITH DIMENSIONS A=19 AND E=3.9MM
802	MCFRB L	41644 03-01-19	75403286	LP SHEET 3X1220X1830MM, SHADE AS PER SAMPLE NO. NAC-SP05
803	MCFRB L	41643 03-01-19	75400054	LP SHEET 3X1220X2440MM SHADE AS PER SAMPLE NO. NAC-SP05
804	MCFRB L	41640 03-01-19	75400066	HPL SHEET 3X1220X2440MM SHADE RAL-9006, MATT FINISH, GLOSS VALUE 10-12 AT 45 DEGREE
805	MCFRB L	41642 03-01-19	75400080	HPL SHEET 1.2X1220X2440MM SHADE RAL-9006 MATT FINISH, GLOSS VALUE 10-12 AT 45 DEGREE
806	MCFRB L	78665 01-02-20	76900058	Stainless Steel Wire 1.2 mm in Barrel of Weight 100 KG 125 KG for SIS Korea Robotic Welding Machine. Residual Life 12 Months from the date of receipt in MCF/RBL.
807	MCFRB L	103391 20-03-21	76217309	Contact Tip Dia. 1.2 MM Suitable for Wire of Dia. 1.2 mm
808	MCFRB L	103403 22-03-21	75016655	Nylon Lifting belt Capacity 05 Ton
809	MCFRB L	103407 22-03-21	76210200	Air plasma cutting hand torch assembly suitable for Hypertherm power max 30 AIR.
810	MCFRB L	103415 22-03-21	76300018	Swirl Ring for Hypertherm power max 30 amp. for air plasma cutting machine.
811	MCFRB L	103417 22-03-21	76300067	Shield for Hypertherm power max 30 amp. for air plasma cutting machine.
812	MCFRB L	103440 22-03-21	76904581	Contact tip holder suitable for 500A water cooled welding torch.
813	MCFRB L	103420 22-03-21	76905299	Retaining cap for Hypertherm power max 30 amp for air plasma cutting machine.
814	MCFRB L	103436 22-03-21	76904799	Gas diffuser white for 550A water cooled welding torch.
815	MCFRB L	103441 22-03-21	76904192	Steel liner length 5.4 meter suitable for filler wire dia. 1.2 mm
816	MCFRB L	103429 22-03-21	76010818	Electrode for Hypertherm power max 30 amp. for air plasma cutting machine.
817	MCFRB L	113174 27-08-21	76905354	Water Cooled MIG Welding Torch 550 Amp. Suitable for Migatronic Sigma2 500 Welding Set.
818	MCFRB L	103434 22-03-21	76900060	Nozzle Hypertherm power max 30 amp. for air plasma cutting machine.
819	MCFRB L	181534 18-03-24	75500048	Rubber packing for emergency feed terminal as per drawing No.SCNLR-7-5-011
820	MCFRB L	204256 28-12-24	76014186	Stainless Steel Solid Welding Rod for TIG Welding, Size: 1.6mm dia x 1000mm Length (100 nos. per Packet) shall conform to AWS.A/SFA 5.9/93, Grade- ER 308L.
821	MCFRB L	211604 19-03-25	75037191	Burner Hose , 3/4" SS Corrugated SS Below Hose; Length- 5 meters, 3/4" female swivel nut 90 Degree angle BSP fitting both end, WP-5 bar used in SRP-R9000 & SRP-K5000.
822	RWP	7556 22-07-17	75908499	Clear poly carbonate face shield with carrier for attachment on helmet. Material-Polycarbonate 1. Glass-Green 2. Size-8X15.5inch 3. Thickness-1.0mm 4. Protection against high-speed impact (120m/s) at extreme temperature, penetration, splash of liquids and heat. 5. 99.9% UV protection 6. Best optical quality (highest ranking a tests of spherical refractive power, astigmatic refractive power, prismatic refractive and light duffussion. 7. Protective film on both sides (Prevent damages and scratches during transportation) 8. Edges fitted with aluminium beadig for easy adjustment to face contour. 9. Conforms to EN166 and meet ANSI Z87.1 supply with carrier of visore for attachment of any helmet. One no. sample to be submitted by the firm for approval before bulk supply.
823	RWP	135367 30-06-22	76904854	Air cooled Hub cutting torch, Model No. 1982TAF, Make: HARRIS
824	RWP	114867 23-09-21	76217437	Cutting Nozzle for cutting Wheel Hubs with following Specification: 1. Type: SDS 26F 2. Cutting Gas: Oxy-Propane. 3. Make: GEGA made in Germany or PARADIGM Engg Pvt. Ltd/Bangalore or equivalent
825	RWP	149986 23-12-22	75908426	Industrial safety helmet RED colour having glazed surface finish and made as per IS-2925-1984. The helmet shall be made of ABS grade plastic material suitable for use in heat zone application. The helmet shall have NAPE Strap Type adjustable ratchet with nylon tape chin strap. Sweat absorption pad should be provided at the front of head band inside. An opening slot of 20mm X 3mm on both sides of the helmet is to be provided for fixing EAR muffs. Ventilation holes to be provided in the shell to permit circulation of air inside the helmet. The Helmet should be ISI/DGMS approved and hence the helmet shall have ISI/DGMS mark. Indian Railway monogram shall be screen printed on the front side of the helmet. The successful bidder shall submit the sample after placement of purchase order and obtain approval of the sample before bulk supply as per CVC guidelines. Offer should accompany copies of ISI/DGMS valid approval letter for Technical Scrutiny. Size: MEDIUM. Inspection will be carried out at RWP as per approved sample.
826	RWP	149959 23-12-22	75050110	Cut resistance hand gloves in pair for one left hand and one right hand,conforming to EN: 388-2016 and CE certificate, Specification- Material Polyurethane, Liner colour - Blue/Black, Coating colour-Black ,Grip-smooth palm,Cuff style-straight with over lock thread beaded cuff area,Thickness-13 gauge,length-260 mm, Palm size-8 & 9,Performance level designation -4443C.Make-3M,Karam,DPL or Swalka-Kel.

827	RWP	168316 28-08-23	75900567	Safety Spectacles (Smoke/Clear). Standard-EN-166, IS: 5983-1980 & ANSI Z 87.1-2010. Lens:- Material- Polycarbonate (PC), Color - Smoke / Clear. Lenses- Thickness- 2.0 to 2.1 mm. Optical class-1. Mechanical Strength- F(45m/s) according to EN 166. Lens Filter-2C-1.2(UV). Coating-Anti Scratch(K), Anti Fog(N). Frame:- Material- Polycarbonate(PC). Color-Grey, Yellow, Blue. Nose Pad-Universal fit soft nose pads. Weight-25 to 30 gram. Test certificate should be furnished from Government approved test laboratories along with offer.
828	RWP	150051 24-12-22	75350051	Flexible Dust Hose, size: 75 mm ID, P.V.C. Reinforced Vinyl Flexible heavy duty hose in grey colour (In length of 15 meter or its multiple).
829	RDSO	16374 24-01-18	75327582	Transparent Polythene pipe with the following specifications (1) Size = 12.5mm (0.5 inch) diameter. (2) Nature = Heavy bore (3) Pack = 30 meter approximately bundle (4) Weight = Minimum 3 to 3.750 Kg per bundle